

DECLARATION OF PERFORMANCE *BETON-H 1*.
N° C003-13

1. **Identification code:** C003-13
2. **Type, batch or serial number:**
C003-13-C2TES2 - (Batch number: see the packaging).
3. **Intended use or uses of the construction product:** in compliance with **EN 12004:2007 + A1:2012** - Appendix ZA.1.2 - High-deformable cementitious adhesive for tiles suitable for interior and exterior employment. (class C2TES2).
4. **Manufacturer:**

NORD RESINE SpA Via Fornace Vecchia, 79 – 31058 Susegana (TV) P.I. IT02169750268	
<u>Location of production</u> Via Valcellina, 26 33097 Spilimbergo - ITALIA	<u>Luogo of sale</u> via Fornace Vecchia, 79 31058 Susegana - ITALIA

5. **System of assessment and verification of constancy of performance of the construction product: SYSTEM 3.**
6. The accredited laboratory **MODENA CENTRO PROVE** issued **Test report number 20064557** related to initial type tests.
7. **Declared Performance:**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	TECHNICAL STANDARD	TECHNICAL SPECIFICATION
Initial tensile adhesion strength traction (average)	2,3 N/mm ²	EN 1348:2007	EN 12004:2007 + A1:2012
Tensile adhesion strength after thermal ageing (average)	≥ 1 N/mm ²	EN 1348:2007	
Tensile adhesion strength after water immersion(average)	≥ 1 N/mm ²	EN 1348:2007	
Tensile adhesion strength after freezing – thawing cycles (average)	≥ 1 N/mm ²	EN 1348:2007	
Reaction to fire	Class A1/A1 _{fl}	EN 13501-1	
Release of dangerous substances	See Safety Sheet	----	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Susegana, 15th May 2013

Lionello Caregnato
(Presidente del Consiglio d'Amministrazione)

A handwritten signature in black ink, appearing to read "Lionello Caregnato", written over a horizontal line.