

**DECLARATION OF PERFORMANCE: *DRY BETON SUPER***  
**N° R002-13**

1. **Identification code:** R002-13
2. **Type, batch or serial number:**
3. R002-13-CSII - (Batch number: see the packaging)
4. **Intended use or uses of the construction product:** in compliance with **EN 998-1:2010** - Appendix ZA.1 – Renovating mortar ( R ) for internal and external use. Dehumidifying Plaster.
5. **Manufacturer:**

<p><b>NORD RESINE SpA</b>          Via Fornace Vecchia, 79 – 31058 Susegana (TV)          P.I. IT02169750268</p>	
<p><u>Production site</u>          Via Valcellina, 26          3097 Spilimbergo – ITALY</p>	<p><u>Wholesale storage</u>          Via Fornace Vecchia, 79          31058 Susegana - ITALY</p>

6. **System or systems of assessment and verification of constancy of performance of the construction product: SYSTEM 4**

7. **Declared performance:**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	TECHNICAL SPECIFICATION
Adhesion	≥1 N/mm <sup>2</sup> FP:A	<b>EN 998-1:2010</b>
Water absorption after 24 h	3,3 Kg/m <sup>2</sup>	
Water vapour permeability	μ ≤10	
Thermal conductivity (λ <sub>10,Dry</sub> ) (table value; P=50%)	0,27 W/mK	
Durability (against freeze-thaw)	NPD	
Reaction to fire	Class A1	
Dangerous substances	See Safety Data Sheet	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

**CE MARK**

**IN COMPLIANCE WITH CPR 305/2011 AND WITH EN 998-1**

<b>CE</b>	<b>NORD RESINE SpA</b> <i>Via Fornace Vecchia, 79 – 31058 Susegana (TV)</i>
06 No. R002-CPR <b>EN 998-1</b>	
<b>DRY BETON SUPER</b>	
Renovating mortar ( R ) for internal and external use.	
Reaction to fire	Class A1
Water absorption	3,3 Kg/m <sup>2</sup>
Water vapour permeability	$\mu \leq 10$
Adhesion	$\geq 1$ N/mm <sup>2</sup> FP:A
Thermal conductivity ( $\lambda_{10, Dry}$ )	0,27 W/mK (average table value; P=50%)
Dangerous substances	See Safety Data Sheet

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Susegana, 10th March 2015

Lionello Caregnato  
( Chief Executive Officer)

