

DECLARATION OF PERFORMANCE : N° RC005-13

1. **Identification Code:** **GROVE RASANTE**

2. **Type, batch or serial number:**

RC005-13-R2 - (Batch number: see the packaging)

3. **Intended use or uses of the construction product:** in compliance with **EN 1504-3:2005** - Appendix ZA.1 – Non-structural repair product for concrete through CC mortar (hydraulic cement based); intended use in buildings and civil engineering works. Anti-carbonation leveling compound for concrete.

4. **Manufacturer:**

NORD RESINE SpA Via Fornace Vecchia, 79 – 31058 Susegana (TV) P.I. IT02169750268	
<u>Production site</u> Via Valcellina, 26 33097 Spilimbergo - ITALIA	<u>Wholesale storage</u> via Fornace Vecchia, 79 31058 Susegana – ITALIA

5. **System or systems of assessment and verification of constancy of performance of the construction product:** **SISTEMA 2+**

6. **Notified Body:** **ICMQ (n° di identificazione: 1305)**

Issued the certification of compliance of factory production control by performing:

- a) Initial inspection of the manufacturing plant and of factory production;
- b) Continuous surveillance, assessment and evaluation of factory production control.

7. **Declared Performance:**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	TECHNICAL SPECIFICATION
Compressive strength	Class R2	EN 1504-3:2005
Chloride ion content	≤ 0,05 %	
Adhesive bond	≥ 0,8 MPa	
Thermal compatibility: part 1, freeze-thawing	≥ 0,8 MPa	
Capillary absorption	≤ 0,5 kgxm ⁻² xh ^{-0.5}	
Dangerous substances	According to point 5.4	
Fire resistance	Class A1	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

CE MARK

IN CONFORMITY WITH CPR 305/2011 AND WITH EN 1504-3

 1305	NORD RESINE SpA <i>Via Fornace Vecchia, 79 – 31058 Susegana (TV)</i>
13 No. RC005-CPR EN 1504-3	
GROVE RASANTE	
Non-structural repair product for concrete through CC mortar (hydraulic cement based)	
Compressive strength	Class R2
Chloride ion content	≤ 0,05 %
Adhesive bond	≥ 0,8 MPa
Thermal compatibility: part 1	≥ 0,8 MPa
Capillary absorption	≤ 0,5 kgxm ⁻² xh ^{-0.5}
Dangerous substances	According to point 5.4
Fire resistance	Class A1

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Susegana, 15th May 2013

Lionello Caregnato
(Chief Executive Officer)

