

**DECLARATION OF PERFORMANCE:
N° C004-13**

1. **Identification code:** *MONOTACK FLEX WHITE/GREY*
2. **Type, batch or serial number:**
Batch number: see the packaging
3. **Intended use or uses of the construction product:** in compliance with **EN 12004:2007 + A1:2012** - Appendix ZA.1.2 – Adhesive for tiles in the form of cementitious adhesives. Internal and external use. Type: C2TES1.
4. **Manufacturer:**

<p>NORD RESINE SpA Via Fornace Vecchia, 79 – 31058 Susegana (TV) P.I. IT02169750268</p>	
<p><u>Production site</u> Via Valcellina, 26 3097 Spilimbergo – ITALY</p>	<p><u>Wholesale storage</u> Via Fornace Vecchia, 79 31058 Susegana - ITALY</p>

5. **System or systems of assessment and verification of constancy of performance of the construction product:** SYSTEM 3.
6. **The notified testing laboratory** *MODENA CENTRO PROVE* **issued the test reports No. 20064549** (GREY color) e **No. 20064550** (WHITE color).
7. **Declared performance:**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	TECHNICAL SPECIFICATION
Reaction to fire	Class A1/A1 _{fl}	EN 12004:2007 + A1:2012
Initial tensile adhesion strength	≥ 1 N/mm ²	
Tensile adhesion strength after heat ageing	≥ 1 N/mm ²	
Tensile adhesion strength after water immersion	≥ 1 N/mm ²	
Tensile adhesion strength after freeze-thaw cycles	≥ 1 N/mm ²	
Release of dangerous substances	See Safety Data Sheet	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.
9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Susegana, 15th May 2013

Lionello Caregnato
(Chief Executive Officer)

