

**DECLARATION OF PERFORMANCE :  
N° C008-13**

1. **Identification code: MONOTACK H BOND WHITE AND GREY**
2. **Type, batch or serial number:**  
(Batch number: see the packaging)
3. **Intended use or uses of the construction product: in compliance with EN 12004:2007 + A1:2012 - Appendix ZA.1.2 – Highly deformable cementitious tiles adhesive, for internal and external use, class C2TES2.**
4. **Manufacturer:**

<p><b>NORD RESINE SpA</b> Via Fornace Vecchia, 79 – 31058 Susegana (TV) P.I. IT02169750268</p>	
<p><u>Production site</u> Via Valcellina, 26 3097 Spilimbergo – ITALY</p>	<p><u>Wholesale storage</u> Via Fornace Vecchia, 79 31058 Susegana - ITALY</p>

5. **System or systems of assessment and verification of constancy of performance of the construction product: SYSTEM 3.**
6. The notified testing laboratory **MODENA CENTRO PROVE** issued the test reports n° 20064557 (GREY color) and n° 200664558 (WHITE color).
7. **Declared performance:**


ESSENTIAL CHARACTERISTICS	PERFORMANCE	Technical Standard	Harmonized technical specification
Reaction to fire	Class A1/A1 <sub>fl</sub>	EN 13501-1	<b>EN 12004:2007 + A1:2012</b>
Initial tensile adhesion strength	≥ 1 N/mm <sup>2</sup>	EN 1348:2007	
Tensile adhesion strength after heat ageing	≥ 1 N/mm <sup>2</sup>	EN 1348:2007	
Tensile adhesion strength after water immersion	≥ 1 N/mm <sup>2</sup>	EN 1348:2007	
Tensile adhesion strength after freeze-thaw cycles	≥ 1 N/mm <sup>2</sup>	EN 1348:2007	
Release of dangerous substances	See Safety Data Sheet	----	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Susegana, 15th May 2013

Lionello Caregnato  
(Chief Executive Officer)

A handwritten signature in black ink, appearing to read "Lionello Caregnato", written over the printed name.