

DECLARATION OF PERFORMANCE: N° RC025-CPR

1. **Identification code:** **NORDBLACK**
2. **Type, batch or serial number:** (Batch number: see the packaging).
3. **Intended use or uses of the construction product:** in compliance with **EN 1504-2:2004** - Appendix ZA.1e – Product for surface protection (moisture control and increasing resistivity).
Liquid waterproof membrane for concrete surface protection.

4. **Manufacturer:**

NORD RESINE SpA
Via Fornace Vecchia, 79 – 31058 Susegana (TV)
P.I. IT02169750268

5. **System or systems of assessment and verification of constancy of performance of the construction product:** **SYSTEM 2+**
SYSTEM 4 : Reaction to fire

6. **The Notified Body ICMQ S.p.A.** (No. 1305) issued the test reports No. **1305-CPR-1167** related to factory production control and performed the:
 - a. initial inspection of the manufacturing plant and of factory production;
 - b. continuous surveillance, assessment and evaluation of factory production control.

7. **Declared performance:**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	TECHNICAL SPECIFICATION
Water vapor permeability	class II	EN 1504-2: 2004
Capillary absorption and permeability to water	$w < 0,1 \text{ Kg}/(\text{m}^2 \times \text{h}^{0,5})$	
Adhesion strength by pull off test	$\geq 0,8 \text{ N}/\text{mm}^2$	
Reaction to fire	class F	
Dangerous substances	See Safety Sheet	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

CE MARK

IN COMPLIANCE WITH CPR 305/2011 AND WITH EN 1504-2.

CE 1305	NORD RESINE SpA <i>Via Fornace Vecchia, 79 – 31058 Susegana (TV)</i>
15 No. RC025-CPR EN 1504-2	
NORDBLACK	
One component coating for concrete surface protection through moisture control and increasing resistivity.	
Water vapor permeability	class II
Capillary absorption and permeability to water	$w < 0,1 \text{ Kg}/(\text{m}^2 \times \text{h}^{0,5})$
Adhesion strength by pull off test	$\geq 0,8 \text{ N}/\text{mm}^2$
Reaction to fire	class F
Dangerous substances	See Safety Sheet

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Susegana, 20th February 2015

Lionello Caregnato
(Chief Executive Officer)

