

**DECLARATION OF PERFORMANCE :  
N° SR018-CPR**

1. **Identification code:** **NORDPUR ESTERNI**
2. **Type, batch or serial number:**  
Batch number: see the packaging
3. **Intended use or uses of the construction product:** in compliance with **EN 13813:2002** - Appendix ZA.1.5 – Synthetic Resin Materials for screed. Resin coating.
4. **Manufacturer:**

**NORD RESINE SpA**  
Via Fornace Vecchia, 79 – 31058 Susegana (TV)  
P.I. IT02169750268

5. **System or systems of assessment and verification of constancy of performance of the construction product:** **SYSTEM 4**  
**SYSTEM 3 for Fire Reaction**
6. The Notified Laboratory **MASINI (N° 0068)** issued the test report n° 1184-2015 related to reaction to fire.
7. **Declared performance:**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	TECHNICAL SPECIFICATION
Water permeability	NPD	<b>EN 13813 : 2002</b>
Wear resistance BCA	AR0,5	
Adhesion strength	B2,0	
Impact resistance	IR10	
Sound insulation	NPD	
Sound absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Reaction to fire	Class B <sub>fl</sub> -s1	
Release of corrosive substances	SR	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

**CE MARK**

**IN COMPLIANCE WITH CPR 305/2011 AND WITH EN 13813**

<b>CE</b>	<b>NORD RESINE SpA</b> <i>Via Fornace Vecchia, 79-31058 Susegana(TV)</i>
<b>15</b> <b>N° SR018-CPR</b> <b>EN 13813 – SR-B2,0-AR0,5-IR10</b>	
<b>NORDPUR ESTERNI</b>	
<b>Synthetic resin screed material for internal flooring use</b>	
Reaction to fire	Class B <sub>fl</sub> -s1
Release of corrosive substances	SR
Wear resistance	AR0,5
Adhesion strength	B2,0
Impact resistance	IR10

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Susegana, 20th May 2015

Lionello Caregnato  
( Chief Executive Officer)

