

**DECLARATION OF PERFORMANCE :
N° S002-CPR**

1. **Identification Code:** **NORDSIL AC**
2. **Type, batch or serial number:**
Batch number: see the packaging
3. **Intended use or uses of the construction product:** in compliance with **EN 15651-1:2012 (type F EXT-INT class 20 LM), EN 15651-2:2012 (type G), EN 15651-3:2012 (type S).**

Sealant for non-structural use, for interior and exterior use, for joints in facade elements, glass walls and for hygienic employment.

4. **Manufacturer:**

NORD RESINE SpA
Via Fornace Vecchia, 79 – 31058 Susegana (TV)
P.I. IT02169750268

5. **System or systems of assessment and verification of constancy of performance of the construction product:** **SYSTEM 3**
Fire reaction: **SYSTEM 3.**
6. - The notified body **GINGER CRBTP (No. 0074)** evaluated the performance based on sampling carried out by the and issued the Test Reports.
- The notified body **EFFECTIS (No. 1234)** evaluated the performance based on sampling carried out by the and issued the Test Reports.

7. Declared Performance:

Conditioning: method A

Substrate:

- Glass walls: - glass
- Facades: - mortar type M2 (with primer: BETONSEAL PRIMER)
- anodised aluminium (with primer: BETONSEAL PRIMER)
- Hygienic employment
- anodised aluminium

ESSENTIAL CHARACTERISTIC	PERFORMANCE	TECHNICAL SPECIFICATION
Reaction to fire	Class E	EN 15651-1,2,3:2012
Release of dangerous substances	See Safety Sheet	
Water and air resistance:		
- Resistance to the flow	≤ 3 mm	
- Volume loss	≤ 10 %	
- Tensile properties in constant condition for the extension, after water immersion	no fractures NPD	
- Secant tensile modulus at -30°C	NPD	
- Tensile properties at maintained extension at -30°C	NPD	
- Elastic recovery	≥ 60%	
- Adhesive/cohesive properties after heat, water and artificial light exposure	Passed	
- Growth of bacteria	0	
Durability	Passed	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

CE	NORD RESINE SpA Via Fornace Vecchia, 79 – 31058 Susegana (TV)
14 No. SC002-CPR EN 15651- parts 1-2-3	
NORDSIL AC	
Sealant for non-structural use in joints in facade elements, glass walls and hygienic uses. Type: F-EXT-INT/G/S	

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Susegana, 15th December 2015

Lionello Caregnato
(Chief Executive Officer)

