

DECLARATION OF PERFORMANCE :
N° SR024-CPR

1. **Identification code:** **Q-RASANTE**
2. **Type, batch or serial number:**
(Batch number: see the packaging)
3. **Intended use or uses of the construction product:** in compliance with **EN 13813:2002** - Appendix ZA.1.5 – Synthetic Resin Materials for screed. Epoxy water based mortar for flooring use.
4. **Manufacturer:**

NORD RESINE SpA
Via Fornace Vecchia, 79 – 31058 Susegana (TV)
P.I. IT02169750268

5. **System or systems of assessment and verification of constancy of performance of the construction product:** **SYSTEM 4**

6. **Declared performance:**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	TECHNICAL SPECIFICATION
Water permeability	NPD	EN 13813 : 2002
Wear resistance BCA	AR0,5	
Adhesion strength	B2,0	
Impact resistance	IR4	
Sound insulation	NPD	
Sound absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Reaction to fire	Class F	
Release of corrosive substances	SR	

7. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

CE	
NORD RESINE SpA Via Fornace Vecchia, 79-31058 Susegana (TV)	
15	
EN 13813 : 2002 - SR-B2,0-AR0,5-IR4	
<i>No. SR024-CPR</i>	
Q-SMALTO	
Synthetic resin coating for internal use	
Reaction to fire	F
Release of corrosive substances	SR
Wear resistance	AR0,5
Adhesion strength	B2,0
Impact resistance	IR4

**DECLARATION OF PERFORMANCE:
N° RC024-CPR**

1. **Identification code:** **Q-RASANTE**
2. **Type, batch or serial number:** (Batch number: see the packaging).
3. **Intended use or uses of the construction product:** in compliance with **EN 1504-2:2004** - Appendix ZA.1e - Product for surface protection - Coating - (moisture control / increasing resistivity).
4. **Manufacturer:**

NORD RESINE SpA
Via Fornace Vecchia, 79 - 31058 Susegana (TV)
P.I. IT02169750268

5. **System or systems of assessment and verification of constancy of performance of the construction product:** **SYSTEM 2+**
6. The Notified Body ICMQ (No. 1305) issued the test reports No. **1305-CPR-1167** and performed the:
 - a. initial inspection of the manufacturing plant and of factory production;
 - b. continuous surveillance, assessment and evaluation of factory production control.

7. **Declared performance:**


ESSENTIAL CHARACTERISTICS	PERFORMANCE	TECHNICAL SPECIFICATION
Water vapour permeability	class I	EN 1504:2004
Capillary absorption and permeability to water	$w < 0,1 \text{ Kg}/(\text{m}^2 \times \text{h}^{0,5})$	
Adhesion strength by pull off test	$\geq 2 \text{ N}/\text{mm}^2$	
Reaction to fire	Euroclass F	
Dangerous substances	See Safety Sheet	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

CE MARK

IN COMPLIANCE WITH CPR 305/2011 AND WITH 1504-2.

	<p>NORD RESINE SpA Via Fornace Vecchia, 79 – 31058 Susegana (TV)</p>	
<p>15 No.RC024-CPR EN 1504-2</p>		
<p>Q-RASANTE</p>		
<p>Coating for surface protection of concrete through moisture control and resistivity increase.</p>		
<p>Water vapour permeability</p>	<p>Class I</p>	
<p>Capillary absorption and permeability to water</p>	<p>$w < 0,1 \text{ Kg}/(\text{m}^2 \times \text{h}^{0,5})$</p>	
<p>Adhesion strength by pull off test</p>	<p>$\geq 2 \text{ N}/\text{mm}^2$</p>	
<p>Dangerous substances</p>	<p>See Safety Sheet</p>	

Susegana, 2nd September 2015

Lionello Caregnato
(Chief Executive Officer)

