

DECLARATION OF PERFORMANCE : N° RC005-CPR

1. **Identification Code:** **RASANTE 2000 2K**

2. **Type, batch or serial number:**

Batch number: see the packaging

3. **Intended use or uses of the construction product:** in compliance with **EN 998-1:2010** - Appendix ZA.1 – Mortar for plaster, interior and exterior use, for general purposes (GP).

Skim coat for civil engineering purposes, for internal and exterior uses.

4. **Manufacturer:**

NORD RESINE SpA Via Fornace Vecchia, 79 – 31058 Susegana (TV) P.I. IT02169750268	
<u>Production site</u> Via Valcellina, 26 33097 Spilimbergo - ITALIA	<u>Wholesale storage</u> via Fornace Vecchia, 79 31058 Susegana – ITALIA

5. **System or systems of assessment and verification of constancy of performance of the construction product:** **SISTEMA 4**

6. **Declared Performance:**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	TECHNICAL SPECIFICATION
Adhesive bond	$\geq 2 \text{ N/mm}^2$ – FB:B	EN 989-1:2010
Water absorption after 24h	W1	
Water vapour permeability	$\mu \leq 50$	
Thermal conductivity ($\lambda_{10,Dry}$) (table value; P=50%)	0,83 W/mK	
Durability (freeze-thawing)	NPD	
Reaction to fire	F	
Dangerous substances	See Safety Sheet	

7. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6

CE MARK
IN COMPLIANCE WITH CPR 305/2011 AND TO EN 998-1.

CE	NORD RESINE SpA <i>Via Fornace Vecchia, 79 – 31058 Susegana (TV)</i>
14 N° R005-CPR EN 998-1	
RASANTE 2000 2K	
Mortar for plaster, for general purposes (GP), interior and exterior use.	
Water absorption	W1
Water vapour permeability	$\mu \leq 50$
Adhesive bond	$\geq 2 \text{ N/mm}^2$ – FB:B
Thermal conductivity ($\lambda_{10,Dry}$)	0,83 W/mK (average table value, P=50%)
Dangerous substances	See Safety Sheet

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Susegana, 15th December 2014

Lionello Caregnato
(Chief Executive Officer)

