

DECLARATION OF PERFORMANCE: N° RC007-13

1. **Identification code: RIVENORD LAST**

2. **Type, batch or serial number:**

Batch number: see the packaging

3. **Intended use or uses of the construction product**, in compliance with **EN 1504-2:2004** - Appendix ZA.1d + ZA.1e - Products for surface protection - Coating (Protection against penetration hazard (PI) + Moisture control (MC) and Increased resistance (IR).

4. **Manufacturer:**

<p>NORD RESINE SpA Via Fornace Vecchia, 79 - 31058 Susegana (TV) P.I. IT02169750268</p>
--

5. **System or systems of assessment and verification of constancy of performance of the construction product: SYSTEM 2+**

6. **Notified Body: ICMQ (identification number: 1305)**


Issued the certification of compliance of factory production control (**Number: 1305-CPR-1167**) and performed the:

- a) Initial inspection of the manufacturing plant and of factory production;
- b) Continuous surveillance, assessment and evaluation of factory production control.

7. Declared Performance:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	TECHNICAL SPECIFICATION
CO ₂ Permeability	$S_D > 50 \text{ m}$	EN 1504-2 :2004
Water vapour permeability	class I	
Capillary absorption and permeability to water	$w < 0,1 \text{ Kg}/(\text{m}^2 \times \text{h}^{0,5})$	
Adhesion following thermal compatibility after:		
• freezing - thawing cycles with thawing salts immersion	$\geq 0,8 \text{ N}/\text{mm}^2$	
• thermal shock	$\geq 0,8 \text{ N}/\text{mm}^2$	
• thermal cycles without thawing salts immersion	$\geq 0,8 \text{ N}/\text{mm}^2$	
Exposition to the conditioning of artificial atmospheric agents	No visible defect	
Crack bridging resistance	Class A3	
Adhesion strength by pull off test	$\geq 0,8 \text{ N}/\text{mm}^2$	
Reaction to fire	Euroclass: F	
Release of dangerous substances	According to point 5.4	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

 1305	NORD RESINE SpA <i>Via Fornace Vecchia, 79 – 31058 Susegana (TV)</i>
13 N° RC007-13 RIVENORD LAST Batch number: see the packaging	
EN 1504-2:2004 Products for surface protection Coating	
CO ₂ Permeability	S _D > 50 m
Water vapour permeability	class I
Capillary absorption and permeability to water	w < 0,1 Kg/(m ² x h ^{0,5})
Adhesion following thermal compatibility after:	
• freezing - thawing cycles with thawing salts immersion	≥ 0,8 N/mm ²
• thermal shock	≥ 0,8 N/mm ²
• thermal cycles without thawing salts immersion	≥ 0,8 N/mm ²
Exposition to the conditioning of artificial atmospheric agents	No visible defect
Crack bridging resistance	Class A3
Adhesion strength by pull off test	≥ 0,8 N/mm ²
Reaction to fire	Euroclass: F
Release of dangerous substances	According to point 5.4

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Susegana, 20th December 2013

Lionello Caregnato
 (Chief Executive Officer)

