

Revision nr.4 Dated 19/10/2023 Printed on 19/10/2023
Page n. 1 / 13
Replaced revision:3 (Dated 27/11/2020)

ΕN

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 15M

Product name **EPOGREEN BOND EST (A)**

1.2. Relevant identified uses of the substance or mixture and uses advised against

PRIMER FOR EPOGREEN

1.3. Details of the supplier of the safety data sheet

NORD RESINE S.p.A. Name Full address Via Fornace Vecchia, 79 District and Country

31058 Susegana (TV)

Italia

Tel. +39 0438-437511 Fax +39 0438-435155

e-mail address of the competent person

responsible for the Safety Data Sheet annabreda@nordresine.com

NORD RESINE S.p.A. Supplier:

1.4. Emergency telephone number

For urgent inquiries refer to +39 0438 437511

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Reproductive toxicity, effects on or via lactation H362 May cause harm to breast-fed children.

Hazardous to the aquatic environment, acute H400 Very toxic to aquatic life.

toxicity, category 1

Hazardous to the aquatic environment, chronic H410 Very toxic to aquatic life with long lasting effects.

toxicity, category 1

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H362 May cause harm to breast-fed children.

H410 Very toxic to aquatic life with long lasting effects.

@EPY 11.5.2 - SDS 1004.14





15M - EPOGREEN BOND EST (A)

Revision nr.4 Dated 19/10/2023 Printed on 19/10/2023 Page n. 2 / 13 Replaced revision:3 (Dated 27/11/2020)

SECTION 2. Hazards identification .../>>

Precautionary statements:

Do not breathe dust / fume / gas / mist / vapours / spray. P260

P201 Obtain special instructions before use.

P263 Avoid contact during pregnancy and while nursing.

P273 Avoid release to the environment.

Collect spillage. P391

P308+P313 IF exposed or concerned: Get medical advice / attention.

CHLORINATED PARAFFINS, C14-17 Contains:

VOC (Directive 2004/42/EC):

Two-pack reactive performance coatings for specific end use such as floors.

VOC given in g/litre of product in a ready-to-use condition: 29,16 Limit value: 500.00

- Catalysed with : **EPOGREEN BOND (B)**

2.3. Other hazards

PBT substances contained:

CHLORINATED PARAFFINS, C14-17

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification Classification (EC) 1272/2008 (CLP) x = Conc. %

4,4'-PROPANE-2,2-DIYLDIPHENOL, POLYMER WITH 2-METHYLOXIRANE

INDEX $4 \le x < 8$ Skin Irrit. 2 H315

500-097-4 FC CAS 37353-75-6

CHLORINATED PARAFFINS, C14-17

INDEX 602-095-00-X $4 \le x < 8$ Lact. H362, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=10,

EUH066

EC 287-477-0 CAS 85535-85-9 REACH Reg. 01-2119519269-33

DIPROPYLENE GLYCOL MONOMETHYL ETHER

INDEX $0 \le x < 1$ Substance with a community workplace exposure limit.

252-104-2 FC CAS 34590-94-8 REACH Reg. 01-2119450011-60

TOLUENE

Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin INDEX 601-021-00-3 0 < x < 1

Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412

EC 203-625-9 108-88-3 CAS

01-2119471310-51 REACH Reg.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.



Printed on 19/10/2023
Page n. 3 / 13
Replaced revision:3 (Dated 27/11/2020)

Revision nr.4 Dated 19/10/2023

SECTION 4. First aid measures .../>>

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.



Revision nr.4 Dated 19/10/2023 Printed on 19/10/2023 Page n. 4 / 13 Replaced revision:3 (Dated 27/11/2020)

SECTION 7. Handling and storage .../>>

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und
DEO	Deutschland	Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung
		gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	Fanasa	, 0
FRA	España	Límites de exposición profesional para agentes químicos en España 2021
	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των
		οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας
		2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με
	M	την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki
115) (tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama
17.4	10.10	na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3,
		eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os
		agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os
		riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające
		rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych
		dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru
		modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
		(Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU)
		2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive
		2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive
		91/322/EEC.
	TLV-ACGIH	ACGIH 2022



15M - EPOGREEN BOND EST (A)

Revision nr.4 Dated 19/10/2023 Printed on 19/10/2023 Page n. 5/ 1/3 Replaced revision:3 (Dated 27/11/2020)

SECTION 8. Exposure controls/personal protection

			CI	HLORINATED	PARAFFINS, C	14-17			
hreshold Limit Va	alue								
Type	Country	untry TWA/8h		STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
AGW	DEU	6	0,3	48	2,4	INHAL	11		
AGW	DEU	6	0,3	48	2,4	SKIN	11		
redicted no-effec	t concentra	ation - PNEC							
Normal value in fresh water							0,001	mg/l	
Normal value in	marine water	er					0,0002	mg/l	
Normal value for	r fresh watei	r sediment					13	mg/kg/d	
Normal value for						2,6	mg/kg/d		
Normal value of	STP microo	organisms					80	mg/l	
Normal value for	r the terrestr	ial compartn	nent				11,9	mg/kg/d	
ealth - Derived n	o-effect lev	el - DNEL / I	DMEL						
	Effe	cts on consu	mers			Effects on workers			
Route of exposu	ire Acu	te Acu	ıte	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	loca	ıl sys	temic	local	systemic	local	systemic	local	systemic
Oral					0,58				
					mg/kg bw/d				
Inhalation					6,7				2
					mg/m3				mg/m3
Skin					28,75				47,9
					mg/kg bw/d				mg/kg
									bw/d

			DIPROP	LENE GLYCO	DE MONOME.	THYL ETHER			
reshold Limit V		TIA/A/CI		OTEL /45		D	Ol		
Туре			STEL/15			Observations			
T1.)/	075	mg/m3	ppm	mg/m3	ppm	OLCINI			
TLV	CZE	270	43,74	550	89,1	SKIN			
AGW	DEU	310	50	310	50				
MAK	DEU	310	50	310	50				
VLA	ESP	308	50			SKIN			
VLEP	FRA	308	50			SKIN			
TLV	GRC	600	100	900	150				
AK	HUN	308							
GVI/KGVI	HRV	308	50			SKIN			
VLEP	ITA	308	50			SKIN			
TGG	NLD	300							
VLE	PRT	308	50			SKIN			
NDS/NDSCh	POL	240		480		SKIN			
TLV	ROU	308	50			SKIN			
MV	SVN	308	50			SKIN			
WEL	GBR	308	50			SKIN			
OEL	EU	308	50			SKIN			
TLV-ACGIH			50						
redicted no-effe	ct concentra	ation - PNE	С						
Normal value in	fresh water						19	mg/l	
Normal value in	marine wate	er					1,9	mg/l	
Normal value for fresh water sediment							70,2	mg/kg	
Normal value for	or marine wa	ter sedimen					7,02	mg/kg	
Normal value for	or water, inte	rmittent rele	ase				190	mg/l	
Normal value of	f STP microc	rganisms					4168	mg/l	
Normal value for	or the terrestr	ial comparti	ment				2,74	mg/kg	
ealth - Derived r	no-effect lev	el - DNEL /	DMEL						
	Effe	cts on cons	umers			Effects on w	orkers		
Route of expos	ure Acu	te Ac	ute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	loca	ıl sys	stemic	local	systemic	local	systemic	local	systemic
Oral		•			1,67		•		
					mg/kg/d				
Inhalation					37,2				310
					mg/m3				mg/m3
Skin					15				65
					mg/kg/d				mg/kg/d



15M - EPOGREEN BOND EST (A)

Revision nr.4 Dated 19/10/2023 Printed on 19/10/2023 Page n. 6 / 13 Replaced revision:3 (Dated 27/11/2020)

SECTION 8. Exposure controls/personal protection

				то	LUENE	
Threshold Limit V	/alue					
Туре	Country	TWA/8h		STEL/15	min	Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	192	50,112	384	100,224	SKIN
AGW	DEU	190	50	760	200	SKIN
MAK	DEU	190	50	760	200	SKIN
VLA	ESP	192	50	384	100	SKIN
VLEP	FRA	76,8	20	384	100	SKIN
TLV	GRC	192	50	384	100	
AK	HUN	190		380		SKIN
GVI/KGVI	HRV	192	50	384	100	SKIN
VLEP	ITA	192	50			SKIN
TGG	NLD	150		384		
VLE	PRT	192	50	384	100	SKIN
NDS/NDSCh	POL	100		200		SKIN
TLV	ROU	192	50	384	100	SKIN
MV	SVN	192	50	384	100	SKIN
WEL	GBR	191	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH			20			

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

NND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

hazard; MED = medium hazard; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Value Information

Appearance liquid
Colour beige
Odour characteristic



15M - EPOGREEN BOND EST (A)

Revision nr.4 Dated 19/10/2023 Printed on 19/10/2023 Page n. 7 / 13 Replaced revision:3 (Dated 27/11/2020)

SECTION 9. Physical and chemical properties .../>>

Melting point / freezing point not available Initial boiling point 200 °C Flammability not available not available Lower explosive limit Upper explosive limit not available 100 Flash point Auto-ignition temperature not available Decomposition temperature not available not available Kinematic viscosity not available Solubility not available Partition coefficient: n-octanol/water not available Vapour pressure not available Density and/or relative density 0,99 kg/l Relative vapour density not available Particle characteristics not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC): 4,15 % - 41,09 g/litre VOC (volatile carbon) 0,09 % - 0,85 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Forms peroxides with: air.

TOLUENE

Avoid exposure to: light.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

CHLORINATED PARAFFINS, C14-17

SADT >200°C/392°F.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

May react violently with: strong oxidising agents.

TOLUENE

Risk of explosion on contact with: fuming sulphuric acid,nitric acid,silver perchlorate,nitrogen dioxide,non-metal halogenates,acetic acid,organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Avoid exposure to: sources of heat. Possibility of explosion.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available





Revision nr.4 Dated 19/10/2023 Printed on 19/10/2023 Page n. 8 / 13 Replaced revision:3 (Dated 27/11/2020)

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

TOLUENE

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

TOLUENE

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

ATE (Oral) of the mixture:

ATE (Dermal) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

CHLORINATED PARAFFINS, C14-17

LD50 (Oral): > 4000 mg/kg Rat - Wistar LC50 (Inhalation vapours): > 48,17 mg/l/1h Rat

TOLUENE

 LD50 (Dermal):
 12124 mg/kg Rabbit

 LD50 (Oral):
 5580 mg/kg Rat

 LC50 (Inhalation vapours):
 28,1 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

TOLUENE





Printed on 19/10/2023
Page n. 9 / 13
Replaced revision:3 (Dated 27/11/2020)

SECTION 11. Toxicological information .../>>

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC,

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

May cause harm to breast-fed children.

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

CHLORINATED PARAFFINS, C14-17

LC50 - for Fish > 5000 mg/l/96h Alburnus alburnus 0,0077 mg/l/48h Daphnia magna EC50 - for Crustacea

EC50 - for Algae / Aquatic Plants > 3,2 mg/l/72h Pseudokirchnerella subcapitata

Chronic NOEC for Crustacea 0,01 mg/l Daphnia magna

12.2. Persistence and degradability

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

TOLUENE

Solubility in water 100 - 1000 mg/l

Rapidly degradable

CHLORINATED PARAFFINS, C14-17

Solubility in water < 0.1 mg/l

NOT rapidly degradable

12.3. Bioaccumulative potential

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Partition coefficient: n-octanol/water 0,0043

TOLUENE

Partition coefficient: n-octanol/water 2.73 90

CHLORINATED PARAFFINS, C14-17

Partition coefficient: n-octanol/water 7,2



Revision nr.4 Dated 19/10/2023 Printed on 19/10/2023
Page n. 10 / 13
Replaced revision:3 (Dated 27/11/2020)

SECTION 12. Ecological information .../>>

12.4. Mobility in soil

CHI ORINATED PARAFFINS C14-17

Partition coefficient: soil/water

12.5. Results of PBT and vPvB assessment

PBT substances contained: CHLORINATED PARAFFINS, C14-17

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not

submitted to ADR provisions.

In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity ≤ 5Kg or IMDG:

5L, is not submitted to IMDG Code provisions.

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to

IATA dangerous goods regulations.

14.2. UN proper shipping name

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CHLORINATED PARAFFINS, C14-17) IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CHLORINATED PARAFFINS, C14-17) IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CHLORINATED PARAFFINS, C14-17)



15M - EPOGREEN BOND EST (A)

Revision nr.4 Dated 19/10/2023 Printed on 19/10/2023
Page n. 11 / 13
Replaced revision:3 (Dated 27/11/2020)

SECTION 14. Transport information .../>>

14.3. Transport hazard class(es)

ADR / RID:

Class: 9

Label: 9

IMDG:

Class: 9

Label: 9

IATA:

Class: 9

Label: 9



14.4. Packing group

ADR / RID, IMDG, IATA:

14.5. Environmental hazards

ADR / RID:

Environmentally Hazardous

IMDG:

Marine Pollutant

IATA:

Environmentally Hazardous



14.6. Special precautions for user

ADR / RID:

HIN - Kemler: 90

Limited Quantities: 5 L

Tunnel restriction code: (-)

IMDG: IATA:

Special provision: -EMS: F-A, S-F Cargo:

Passengers:

Limited Quantities: 5 L Maximum quantity: 450 L Maximum quantity: 450 L

Special provision: A97, A158, A197, A215 Packaging instructions: 964 Packaging instructions: 964

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

E1

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

3 - 40

Point Contained substance

Point 75

Point **TOLUENE**

REACH Reg.: 01-2119471310-51

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable

Substances in Candidate List (Art. 59 REACH)

CHLORINATED PARAFFINS, C14-17 REACH Reg.: 01-2119519269-33

Substances subject to authorisation (Annex XIV REACH)



15M - EPOGREEN BOND EST (A)

Revision nr.4 Dated 19/10/2023 Printed on 19/10/2023 Page n. 12 / 13 Replaced revision:3 (Dated 27/11/2020)

SECTION 15. Regulatory information .../>>

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC):

Two-pack reactive performance coatings for specific end use such as floors.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2

Repr. 2 Reproductive toxicity, category 2

Lact. Reproductive toxicity, effects on or via lactation

Asp. Tox. 1 Aspiration hazard, category 1

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Skin Irrit. 2 Skin irritation, category 2

STOT SE 3

Aquatic Acute 1

Aquatic Chronic 1

Aquatic Chronic 3

Specific target organ toxicity - single exposure, category 3

Hazardous to the aquatic environment, acute toxicity, category 1

Hazardous to the aquatic environment, chronic toxicity, category 1

Hazardous to the aquatic environment, chronic toxicity, category 3

H225 Highly flammable liquid and vapour.
 H361d Suspected of damaging the unborn child.
 H362 May cause harm to breast-fed children.
 H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration



15M - EPOGREEN BOND EST (A)

Revision nr.4 Dated 19/10/2023 Printed on 19/10/2023 Page n. 13 / 13 Replaced revision:3 (Dated 27/11/2020)

SECTION 16. Other information .../>>

- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.