

## Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: **22M**  
Product name: **EASY-LAST COAT (A)**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **BI-COMPONENT COLOURED TOP COAT FOR EASY-LAST 901**

#### 1.3. Details of the supplier of the safety data sheet

Name: **NORD RESINE S.p.A.**  
Full address: **Via Fornace Vecchia, 79**  
District and Country: **31058 Susegana (TV)  
Italia**  
Tel.: **+39 0438-437511**  
Fax: **+39 0438-435155**e-mail address of the competent person responsible for the Safety Data Sheet: **annabreda@nordresine.com**Product distribution by: **NORD RESINE S.p.A.**

#### 1.4. Emergency telephone number

For urgent inquiries refer to: **+39 0438 437511**

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:  
Flammable liquid, category 3 H226 Flammable liquid and vapour.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

Signal words: **Warning**

Hazard statements:

**H226** Flammable liquid and vapour.  
**EUH208** Contains: **FATTY ACIDS, TALL-OIL COMPDS.WITH OLEYLAMINE**  
**1,6-hexanediyil-bis (2- (2- (1-ethylpentyl) -3-oxazolidinyl) ethyl) carbamate**  
May produce an allergic reaction.

Precautionary statements:

**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### SECTION 2. Hazards identification ... / >>

**P280** Wear protective gloves/ protective clothing / eye protection / face protection.  
**P370+P378** In case of fire: use carbon anhydride, foam, nebulized water to extinguish.

VOC (Directive 2004/42/EC) :

Two - pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition :

414,56

Limit value:

500,00

- Catalysed with : 33,33 %

EASY-LAST COAT (B)

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

### SECTION 3. Composition/information on ingredients

#### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>2,2,4-TRIMETHYL-1,3-PENTANEDIOL</b>		
CAS	144-19-4 1 ≤ x < 5	Eye Irrit. 2 H319
EC		
INDEX		
<b>2-BUTYL-2-ETHYL-1,3-PROPANEDIOL</b>		
CAS	115-84-4 1 ≤ x < 5	Eye Irrit. 2 H319
EC	204-11-7	
INDEX		
<b>2-METHOXY-1-METHYLETHYL ACETATE</b>		
CAS	108-65-6 1 ≤ x < 5	Flam. Liq. 3 H226, STOT SE 3 H336
EC	203-603-9	
INDEX	607-195-00-7	
Reg. no.	01-2119475791-29	
<b>Reaction mass of ethylbenzene and m-xylene and p-xylene</b>		
CAS	1 ≤ x < 5	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note/notes according to Annex VI to the CLP Regulation: C
EC	905-562-9	
INDEX		
Reg. no.	01-2119555267-33	
<b>1,6-hexanediyl-bis (2- (2- (1-ethylpentyl) -3-oxazolidinyl) ethyl) carbamate</b>		
CAS	140921-24-0 0 ≤ x < 1	Skin Sens. 1 H317
EC	411-700-4	
INDEX	616-079-00-5	
Reg. no.	01-0000015906-63	
<b>N-BUTYL ACETATE</b>		
CAS	123-86-4 0 ≤ x < 1	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC	204-658-1	
INDEX	607-025-00-1	
Reg. no.	01-2119485493-29	
<b>XYLENE (MIXTURE OF ISOMERS)</b>		
CAS	1330-20-7 0 ≤ x < 1	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note/notes according to Annex VI to the CLP Regulation: C
EC	215-535-7	
INDEX	601-022-00-9	
Reg. no.	01-2119488216-32	
<b>ETHYLBENZENE</b>		
CAS	100-41-4 0 ≤ x < 1	Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373
EC	202-849-4	
INDEX	601-023-00-4	
Reg. no.	01-2119489370-35	

### SECTION 3. Composition/information on ingredients ... / >>

#### FATTY ACIDS, TALL-OIL COMPDS.WITH OLEYLAMINE

CAS 85711-55-3  $0 \leq x < 0,1$  STOT RE 2 H373, Eye Dam. 1 H318, Skin Sens. 1A H317  
EC 288-315-1  
INDEX  
Reg. no. 01-2119974148-28

#### QUARTZ

CAS 14808-60-7  $0 \leq x < 1$  STOT RE 1 H372  
EC 238-878-4  
INDEX

#### METHYL ETHYL KETONE

CAS 78-93-3  $0 \leq x < 1$  Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066  
EC 201-159-0  
INDEX 606-002-00-3  
Reg. no. 01-2119457290-43

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### SECTION 4. First aid measures

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

### SECTION 5. Firefighting measures

#### 5.1. Extinguishing media

##### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

##### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

##### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

#### 5.3. Advice for firefighters

##### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

##### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### SECTION 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency

### SECTION 6. Accidental release measures ... / >>

procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

### SECTION 7. Handling and storage

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

### SECTION 8. Exposure controls/personal protection

#### 8.1. Control parameters

Regulatory References:

CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
HUN	Magyarország	A pénzügyminiszter 7/2018. (VIII. 29.) PM rendelete a munkahelyek kémiai biztonságáról szóló 25/2000. (IX. 30.) EüM-SZCSM együttes rendelet módosításáról.
HRV	Hrvatska	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/18)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
SVN	Slovenija	Uradni list Republike Slovenije 20.12.2019 - Uradnem listu RS št. 78/19 -PRAVILNIK o varovanju

### SECTION 8. Exposure controls/personal protection ... / >>

GBR EU	United Kingdom OEL EU	delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu EH40/2005 Workplace exposure limits (Third edition, published 2018) Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2020

#### 2,2,4-TRIMETHYL-1,3-PENTANEDIOL

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	0,109	mg/l
Normal value in marine water	0,0109	mg/l
Normal value for fresh water sediment	0,903	mg/kg/d
Normal value for marine water sediment	0,903	mg/kg/d
Normal value of STP microorganisms	20	mg/l

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation				2,6 mg/m3				6,61 mg/m3
Skin				6,0 mg/kg bw/d				7,03 mg/kg bw/d

#### 2-METHOXY-1-METHYLETHYL ACETATE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	270	49,14	550	100,1	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
VLA	ESP	275	50	550	100	SKIN
VLEP	FRA	275	50	550	100	SKIN
TLV	GRC	275	50	550	100	
AK	HUN	275		550		
GVI/KGVI	HRV	275	50	550	100	SKIN
VLEP	ITA	275	50	550	100	SKIN
TGG	NLD	550				
VLE	PRT	275	50	550	100	SKIN
NDS/NDSch	POL	260		520		SKIN
TLV	ROU	275	50	550	100	SKIN
MV	SVN	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	mg/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value for water, intermittent release	6,35	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	0,29	mg/kg

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				1,67 mg/kg/d				
Inhalation				33 mg/m3				275 mg/m3
Skin				54,8 mg/kg/d				153,5 mg/kg/d

### SECTION 8. Exposure controls/personal protection ... / >>

#### Reaction mass of ethylbenzene and m-xylene and p-xylene

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
VLEP	ITA	221	50	442	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	0,25	mg/l
Normal value in marine water	0,25	mg/l
Normal value for marine water sediment	14,33	mg/kg
Normal value for the terrestrial compartment	2,41	mg/kg

#### N-BUTYL ACETATE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
TLV	CZE	950	196,65	1200	248,4	
AGW	DEU	300	62	600 (C)	124 (C)	
VLA	ESP	724	150	965	200	
VLEP	FRA	710	150	940	200	
TLV	GRC	710	150	950	200	
AK	HUN	241		723		
GVI/KGVI	HRV	724	150	966	200	
TGG	NLD	150				
NDS/NDSch	POL	240		720		
TLV	ROU	715	150	950	200	
MV	SVN	300	62	600	124	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

### SECTION 8. Exposure controls/personal protection ... / >>

#### XYLENE (MIXTURE OF ISOMERS)

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
TLV	CZE	200	46	400	92	SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
TLV	GRC	435	100	650	150	
GVI/KGVI	HRV	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
TGG	NLD	210		442		SKIN
VLE	PRT	221	50	442	100	SKIN
NDS/NDSch	POL	100		200		SKIN
TLV	ROU	221	50	442	100	SKIN
MV	SVN	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg
Normal value for water, intermittent release	0,327	mg/l
Normal value of STP microorganisms	6,58	mg/l
Normal value for the terrestrial compartment	2,31	mg/kg

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral								1,6 mg/kg/d
Inhalation				14,8 mg/m <sup>3</sup>	289 mg/m <sup>3</sup>	289 mg/m <sup>3</sup>		77 mg/m <sup>3</sup>
Skin				108 mg/kg/d				180 mg/kg/d

#### ETHYLBENZENE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
TLV	CZE	200	45,4	500	113,5	SKIN
AGW	DEU	88	20	176	40	SKIN
MAK	DEU	88	20	176	40	SKIN
VLA	ESP	441	100	884	200	SKIN
VLEP	FRA	88,4	20	442	100	SKIN
TLV	GRC	435	100	545	125	
AK	HUN	442		884		SKIN
GVI/KGVI	HRV	442	100	884	200	SKIN
VLEP	ITA	442	100	884	200	SKIN
TGG	NLD	215		430		SKIN
VLE	PRT	442	100	884	200	SKIN
NDS/NDSch	POL	200		400		SKIN
TLV	ROU	442	100	884	200	SKIN
MV	SVN	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

### SECTION 8. Exposure controls/personal protection ... / >>

#### FATTY ACIDS, TALL-OIL COMPD.S.WITH OLEYLAMINE

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,012 mg/kg/d				
Skin				0,012 mg/kg/d				0,024 mg/kg/d

#### QUARTZ

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		0,05			RESP
VLEP	FRA	0,1				RESP
GVI/KGVI	HRV	0,1				
VLEP	ITA	0,1				RESP
TGG	NLD	0,075				RESP
NDS/NDSch	POL	0,1				RESP
MV	SVN	0,15				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				

#### METHYL ETHYL KETONE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	600	200,4	900	300,6	
AGW	DEU	600	200	600	200	SKIN
MAK	DEU	600	200	600	200	SKIN
VLA	ESP	600	200	900	300	
VLEP	FRA	600	200	900	300	SKIN
TLV	GRC	600	200	900	300	
AK	HUN	600		900		SKIN
GVI/KGVI	HRV	600	200	900	300	
VLEP	ITA	600	200	900	300	
TGG	NLD	590		500		SKIN
VLE	PRT	600	200	900	300	
NDS/NDSch	POL	450		900		SKIN
TLV	ROU	600	200	900	300	
MV	SVN	600	200	900	300	SKIN
WEL	GBR	600	200	899	300	SKIN
OEL	EU	600	200	900	300	
TLV-ACGIH		590	200	885	300	

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	55,8	mg/l
Normal value in marine water	55,8	mg/l
Normal value for fresh water sediment	284,74	mg/kg
Normal value of STP microorganisms	709	mg/l
Normal value for the food chain (secondary poisoning)	100	mg/kg
Normal value for the terrestrial compartment	22,5	mg/kg

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				31 mg/kg bw/d				
Inhalation				106 mg/m3				600 mg/m3
Skin				412 mg/kg bw/d				1161 mg/kg bw/d

##### Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.  
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.



### SECTION 8. Exposure controls/personal protection ... / >>

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

##### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

##### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

##### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

##### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

##### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

### SECTION 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	TYPICAL	
Odour	characteristic of solvent	
Odour threshold	Not available	
pH	Not available	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Boiling range	Not available	
Flash point	26 °C	
Evaporation Rate	Not available	
Flammability of solids and gases	Not available	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	Not available	
Vapour density	Not available	
Relative density	1,6	
Solubility	Not available	
Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
Viscosity	Not available	
Explosive properties	Not available	
Oxidising properties	Not available	

#### 9.2. Other information

VOC (Directive 2004/42/EC) : 5,50 % - 87,96 g/litre

**SECTION 10. Stability and reactivity****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

**2-METHOXY-1-METHYLETHYL ACETATE**

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

**N-BUTYL ACETATE**

Decomposes on contact with: water.

**METHYL ETHYL KETONE**

Reacts with: light metals, strong oxidants. Attacks various types of plastic materials. Decomposes under the effect of heat.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

The vapours may also form explosive mixtures with the air.

**2-METHOXY-1-METHYLETHYL ACETATE**

May react violently with: oxidising substances, strong acids, alkaline metals.

**N-BUTYL ACETATE**

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

**XYLENE (MIXTURE OF ISOMERS)**

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

**ETHYLBENZENE**

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

**METHYL ETHYL KETONE**

May form peroxides with: air, light, strong oxidising agents. Risk of explosion on contact with: hydrogen peroxide, nitric acid, sulphuric acid. May react dangerously with: oxidising agents, trichloromethane, alkalis. Forms explosive mixtures with: air.

**10.4. Conditions to avoid**

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

**N-BUTYL ACETATE**

Avoid exposure to: moisture, sources of heat, naked flames.

**METHYL ETHYL KETONE**

Avoid exposure to: sources of heat.

**10.5. Incompatible materials****2-METHOXY-1-METHYLETHYL ACETATE**

Incompatible with: oxidising substances, strong acids, alkaline metals.

**N-BUTYL ACETATE**

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

**METHYL ETHYL KETONE**

Incompatible with: strong oxidants, inorganic acids, ammonia, copper, chloroform.

**10.6. Hazardous decomposition products**

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

**ETHYLBENZENE**

May develop: methane, styrene, hydrogen, ethane.

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on toxicological effects**

Metabolism, toxicokinetics, mechanism of action and other information

**SECTION 11. Toxicological information ... / >>****2-METHOXY-1-METHYLETHYL ACETATE**

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure**2-METHOXY-1-METHYLETHYL ACETATE**

WORKERS: inhalation; contact with the skin.

**N-BUTYL ACETATE**

WORKERS: inhalation; contact with the skin.

**XYLENE (MIXTURE OF ISOMERS)**

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of environmental air.

**ETHYLBENZENE**

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**2-METHOXY-1-METHYLETHYL ACETATE**

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

**N-BUTYL ACETATE**

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

**XYLENE (MIXTURE OF ISOMERS)**

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

**ETHYLBENZENE**

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (IspeSl). Is irritating for skin, conjunctiva and respiratory tract.

Interactive effects**N-BUTYL ACETATE**

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

**XYLENE (MIXTURE OF ISOMERS)**

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	>2000 mg/kg

**2-METHOXY-1-METHYLETHYL ACETATE**

LD50 (Oral)	8530 mg/kg Rat
LD50 (Dermal)	> 5000 mg/kg Rat

**SECTION 11. Toxicological information ... / >>**

<b>ETHYLBENZENE</b>	
LD50 (Oral)	3500 mg/kg Rat
LD50 (Dermal)	15354 mg/kg Rabbit
LC50 (Inhalation)	17,2 mg/l/4h Rat
<b>METHYL ETHYL KETONE</b>	
LD50 (Oral)	2737 mg/kg Rat
LD50 (Dermal)	6480 mg/kg Rabbit
LC50 (Inhalation)	23,5 mg/l/8h Rat
<b>N-BUTYL ACETATE</b>	
LD50 (Oral)	> 6400 mg/kg Rat
LD50 (Dermal)	> 5000 mg/kg Rabbit
LC50 (Inhalation)	21,1 mg/l/4h Rat
<b>FATTY ACIDS, TALL-OIL COMPDS.WITH OLEYLAMINE</b>	
LD50 (Oral)	> 2000 mg/kg Rat
<b>2,2,4-TRIMETHYL-1,3-PENTANEDIOL</b>	
LD50 (Oral)	3730 mg/kg Rat
LD50 (Dermal)	> 5000 mg/kg Rabbit
<b>2-BUTYL-2-ETHYL-1,3-PROPANEDIOL</b>	
LD50 (Oral)	2900 mg/kg Rat
LD50 (Dermal)	3810 mg/kg Rabbit
<b>Reaction mass of ethylbenzene and m-xylene and p-xylene</b>	
LD50 (Oral)	3523 mg/l Rat
LD50 (Dermal)	12126 mg/kg Rabbit
LC50 (Inhalation)	27,124 mg/l/4h Rat
<b>XYLENE (MIXTURE OF ISOMERS)</b>	
LD50 (Oral)	3523 mg/kg Rat
LD50 (Dermal)	4350 mg/kg Rabbit
LC50 (Inhalation)	26 mg/l/4h Rat

**SKIN CORROSION / IRRITATION**

Does not meet the classification criteria for this hazard class

**SERIOUS EYE DAMAGE / IRRITATION**

Does not meet the classification criteria for this hazard class

**RESPIRATORY OR SKIN SENSITISATION**

May produce an allergic reaction.

Contains:

**FATTY ACIDS, TALL-OIL COMPDS.WITH OLEYLAMINE**

1,6-hexanediyl-bis (2- (2- (1-ethylpentyl) -3-oxazolidinyl) ethyl) carbamate

**GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

**CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

**XYLENE (MIXTURE OF ISOMERS)**

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).  
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

**ETHYLBENZENE**

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).  
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

**SECTION 11. Toxicological information** ... / >>REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

**12.1. Toxicity**

## FATTY ACIDS, TALL-OIL COMPDS.WITH OLEYLAMINE

LC50 - for Fish > 100 mg/l/96h Oncorhynchus mykiss  
EC50 - for Crustacea 15,2 mg/l/48h Daphnia magna

## Reaction mass of ethylbenzene and m-xylene and p-xylene

LC50 - for Fish 2,6 mg/l/96h p-xilene

**12.2. Persistence and degradability**

## 2-METHOXY-1-METHYLETHYL ACETATE

Solubility in water > 10000 mg/l  
Rapidly degradable

## ETHYLBENZENE

Solubility in water 1000 - 10000 mg/l  
Rapidly degradable

## METHYL ETHYL KETONE

Solubility in water > 10000 mg/l  
Rapidly degradable

## N-BUTYL ACETATE

Solubility in water 1000 - 10000 mg/l

## FATTY ACIDS, TALL-OIL COMPDS.WITH OLEYLAMINE

Rapidly degradable

## Reaction mass of ethylbenzene and m-xylene and p-xylene

Rapidly degradable

## XYLENE (MIXTURE OF ISOMERS)

Solubility in water 100 - 1000 mg/l  
Degradability: information not available**12.3. Bioaccumulative potential**

## 2-METHOXY-1-METHYLETHYL ACETATE

Partition coefficient: n-octanol/water 1,2

## ETHYLBENZENE

Partition coefficient: n-octanol/water 3,6

**SECTION 12. Ecological information** ... / >>

METHYL ETHYL KETONE	
Partition coefficient: n-octanol/water	0,3
N-BUTYL ACETATE	
Partition coefficient: n-octanol/water	2,3
BCF	15,3
Reaction mass of ethylbenzene and m-xylene and p-xylene	
BCF	25,9
XYLENE (MIXTURE OF ISOMERS)	
Partition coefficient: n-octanol/water	3,12
BCF	25,9

**12.4. Mobility in soil**

N-BUTYL ACETATE	
Partition coefficient: soil/water	< 3
XYLENE (MIXTURE OF ISOMERS)	
Partition coefficient: soil/water	2,73

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information****14.1. UN number**

ADR / RID, IMDG, IATA: 1263

**14.2. UN proper shipping name**

ADR / RID:	PAINT or PAINT RELATED MATERIAL
IMDG:	PAINT or PAINT RELATED MATERIAL
IATA:	PAINT or PAINT RELATED MATERIAL



**SECTION 15. Regulatory information** ... / >>**15.2. Chemical safety assessment**

A chemical safety assessment has been performed for the following contained substances  
N-BUTYL ACETATE  
METHYL ETHYL KETONE

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>STOT RE 1</b>	Specific target organ toxicity - repeated exposure, category 1
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Skin Sens. 1A</b>	Skin sensitization, category 1A
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H372</b>	Causes damage to organs through prolonged or repeated exposure.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H336</b>	May cause drowsiness or dizziness.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).



**SECTION 16. Other information** ... / >>

- GENERAL BIBLIOGRAPHY
1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
  16. Regulation (EU) 2019/521 (XII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

**Changes to previous review:**

The following sections were modified:

01 / 02 / 03 / 07 / 08 / 09 / 10 / 11 / 12 / 15 / 16.