



25J - BETON CR (A)

Printed on 18/09/2024
Page n. 1 / 14
Replaced revision:7 (Dated 20/06/2023)

(TV)

## **Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 25J

Product name **BETON CR (A)** 

NPJ0-K0V8-X00W-A70C

1.2. Relevant identified uses of the substance or mixture and uses advised against

REACTIVE PASTE BINDER, WATERPROOFING Intended use

1.3. Details of the supplier of the safety data sheet

Name NORD RESINE S.p.A. Full address Via Fornace Vecchia, 79 District and Country 31058 Susegana

Italia

Tel. +39 0438-437511 Fax +39 0438-435155

e-mail address of the competent person

responsible for the Safety Data Sheet annabreda@nordresine.com

Supplier: NORD RESINE S.p.A.

1.4. Emergency telephone number

For urgent inquiries refer to Ireland

**National Poisons Information Centre** 

+353 018092166 +353 018092566

Malta Competition and Consumer Affairs Authority (MCCAA)

+356 2395 2000

**Belgium** 

Centre Antipoisons: +32 022649636

BfR Bundesinstitut für Risikobewertung: +49 30184120

**Netherlands** 

National Poisons Information Center / University Medical Center Utrecht

+31 88 75 585 61

Croatian Institute of Public Health, Division for Toxicology: +38514686910

Swedish Poisons Information Centre: +46104566750

### **SECTION 2. Hazards identification**

## 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.



## 25J - BETON CR (A)

Revision nr.8 Dated 18/09/2024 Printed on 18/09/2024 Page n. 2 / 14 Replaced revision:7 (Dated 20/06/2023)

#### **SECTION 2. Hazards identification** .../>>

Hazard classification and indication:

H360F May damage fertility. Reproductive toxicity, category 1B

Eye irritation, category 2 H319 Causes serious eye irritation. Skin irritation, category 2 H315 Causes skin irritation.

Skin sensitization, category 1A H317 May cause an allergic skin reaction.

Hazardous to the aquatic environment, chronic H412 Harmful to aquatic life with long lasting effects.

toxicity, category 3

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words: Danger

Hazard statements:

H360F May damage fertility.

H319 Causes serious eye irritation. H315

Causes skin irritation. H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

**EUH204** Contains isocyanates. May produce an allergic reaction. **EUH205** Contains epoxy constituents. May produce an allergic reaction.

Restricted to professional users.

Precautionary statements:

Obtain special instructions before use. P201

Wear protective gloves/ protective clothing / eye protection / face protection. P280

P308+P313 IF exposed or concerned: Get medical advice / attention. P261 Avoid breathing dust / fume / gas / mist / vapours / spray. P337+P313 If eye irritation persists: Get medical advice / attention. P264 Wash thoroughly with water and soap after handling.

Contains: oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Cashew (Anacardium occidentale) Nutshell Extract, Decarboxylated, Distilled Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and

[2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Product not intended for uses provided for by Directive 2004/42/EC.

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

## **SECTION 3. Composition/information on ingredients**



## 25J - BETON CR (A)

Revision nr.8 Dated 18/09/2024 Printed on 18/09/2024 Page n. 3 / 14 Replaced revision:7 (Dated 20/06/2023)

#### SECTION 3. Composition/information on ingredients ..../>>

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

bis-[4-(2,3-epoxipropoxi)phenyl]propane

INDEX 603-073-00-2 7 ≤ x < 11 Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2

H411

EC 216-823-5 Skin Irrit. 2 H315: ≥ 5%, Eye Irrit. 2 H319: ≥ 5%

CAS 1675-54-3 REACH Reg. 01-2119456619-26

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and

[2-{{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

INDEX 5 ≤ x < 7 Skin Irrit. 2 H315, Skin Sens. 1A H317, Aquatic Chronic 2 H411

EC 701-263-0 CAS 9003-36-5 REACH Reg. 01-2119454392-40

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

INDEX 603-103-00-4 1 ≤ x < 3 Repr. 1B H360F, Skin Irrit. 2 H315, Skin Sens. 1 H317

EC 271-846-8 CAS 68609-97-2 REACH Reg. 01-2119485289-22

TITANIUM DIOXIDE

INDEX  $0.1 \le x < 0.5$  **EUH212** 

EC 236-675-5 CAS 13463-67-7 REACH Reg. 01-2119489379-17

Cashew (Anacardium occidentale) Nutshell Extract, Decarboxylated, Distilled

INDEX 0,1 ≤ x < 0,5 Acute Tox. 4 H302, Acute Tox. 4 H312, Eye Dam. 1 H318, Skin Irrit. 2 H315,

Skin Sens. 1A H317, Aquatic Chronic 3 H412

EC 700-991-6 LD50 Oral: 500 mg/kg, LD50 Dermal: 1100 mg/kg

CAS 8007-24-7 REACH Reg. 01-2119502450-57

**TOSYL CHLORIDE** 

INDEX 0 < x < 0,1 Skin Corr. 1B H314, Eye Dam. 1 H318, EUH029

EC 202-684-8 EUH029: ≥ 0%

CAS 98-59-9

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### **SECTION 4. First aid measures**

### 4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

## Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

## 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.



Revision nr.8 Dated 18/09/2024 Printed on 18/09/2024 Page n. 4 / 14 Replaced revision:7 (Dated 20/06/2023)

#### SECTION 4. First aid measures .../>>

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

#### 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get medical advice / attention.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment: see section 4.1

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

## **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

#### 5.3. Advice for firefighters

#### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### **SECTION 6. Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage**

## 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering



## 25J - BETON CR (A)

Revision nr.8 Dated 18/09/2024 Printed on 18/09/2024 Page n. 5 / 14 Replaced revision:7 (Dated 20/06/2023)

## SECTION 7. Handling and storage .../>>

places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## **SECTION 8. Exposure controls/personal protection**

#### 8.1. Control parameters

Regulatory references:

DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea si completarea hotărârii guvernului nr. 1.093/2006
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
GBR	United Kingdom TLV-ACGIH	EH40/2005 Workplace exposure limits (Fourth Edition 2020) ACGIH 2023

	TITANIUM DIOXIDE											
Threshold Limit Value												
Type	Country	TWA/8h		STEL/15mir	า	Remarks / Observations						
		mg/m3	ppm	mg/m3	ppm							
MAK	DEU	0,3		2,4		RESP Hinweis						
VLA	ESP	10										
VLEP	FRA	10										
TLV	GRC		10									
GVI/KGVI	HRV	10				INHAL						
GVI/KGVI	HRV	4				RESP						
NDS/NDSCh	POL	10				INHAL						
TLV	ROU	10		15								
ПДК	RUS	10				а, Ф						
WEL	GBR	10				INHAL						
WEL	GBR	4				RESP						
TLV-ACGIH		0,2				RESP						



Revision nr.8 Dated 18/09/2024 Printed on 18/09/2024 Page n. 6/ 1/4 Replaced revision:7 (Dated 20/06/2023)

SECTION 8. Exposure controls/personal protection .../>>

		oxirane	, mono[(C12-14	-alkyloxy)met	hyl] derivs.			
redicted no-effect cor	ncentration -	- PNEC						
Normal value in fresh	water					0,0072	mg/l	
Normal value in mari	ne water					0,00072	mg/l	
Normal value for fres	h water sedir	ment				66,77	mg/kg	
Normal value for mar	ine water sed	diment				6,677	mg/kg	
Normal value of STP	microorganis	sms				10	mg/l	
Normal value for the	terrestrial co	mpartment				80,12	mg/kg	
lealth - Derived no-eff	ect level - D	NEL / DMEL						
	Effects on	consumers			Effects on work	ers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral		1,219		1				
		mg/kg bw/d		mg/kg bw/d				
Inhalation	2,9	7,6	1,46	4,1	9,8	29	0,98	13,8
	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3
Skin	40	10	1	2,35	68	17	1,7	3,9
	mg/kg	mg/kg bw/d	mg/kg bw/d	mg/kg bw/d	mg/kg bw/d	mg/kg	mg/kg bw/d	mg/kg
	bw/d					bw/d		bw/d

		w (Anacardium	occidentale) N	utshell Extract,	Decarboxyla	ated, Distilled		
lealth - Derived no-eff	ect level - D	NEL / DMEL						
	Effects on consumers Effects on workers							
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				0,75				
				mg/kg bw/d				
Inhalation				1,31				7,4
				mg/m3				mg/m3
Skin				0,75				2,1
				mg/kg bw/d				mg/kg
								bw/d

Reaction mass of 2,2'-  [2-({2-[4-(oxiran-2-ylme	thoxy)benz	yl]phenoxy}met	hyl)oxirane an	/ <b>-</b>	d			
[2,2'-[methylenebis(2,1			dioxirane					
Predicted no-effect cor		- PNEC						
Normal value in fresh	water					0,003	mg/l	
Normal value for fres	h water sed	iment				0,294	mg/kg	
Normal value for mar	ine water se	ediment				0,029	mg/kg	
Normal value for wat	er, intermitte	ent release				0,025	mg/l	
Normal value of STP	microorgan	isms				10	mg/l	
Normal value for the	terrestrial co	mpartment				0,237	mg/kg	
lealth - Derived no-eff	ect level - D	NEL / DMEL						
	Effects o	n consumers			Effects on wo	rkers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				6,25				
				mg/kg bw/d				
Inhalation				8,7				29,39
				mg/m3				mg/m3
Skin				62,5	0,0083			104,15
				mg/kg bw/d	mg/cm2			mg/kg
					-			bw/d



25J - BETON CR (A)

Revision nr.8 Dated 18/09/2024 Printed on 18/09/2024 Page n. 7 / 14 Replaced revision:7 (Dated 20/06/2023)

### SECTION 8. Exposure controls/personal protection ..../>>

bis-[4-(2,3-epoxipropoxi)phenyl]propane											
centration	- PNEC										
Normal value in fresh water 0,006 mg//l											
ie water					0,0006	mg/l					
ı water sedi	iment				0,996	mg/kg					
ne water se	ediment				0,0996	mg/kg					
ct level - D	NEL / DMEL					5 0					
Effects or	n consumers			Effects on v	vorkers						
Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic				
local	systemic	local	systemic	local	systemic	local	systemic				
	•	VND	0,75		•		•				
			mg/kg/d								
						VND	12,25				
							mg/m3				
		VND	3,571			VND	8,33				
			mg/kg/d				mg/kg				
1	water e water water sed ne water se ct level - E Effects o Acute	centration - PNEC water e water water sediment ne water sediment ct level - DNEL / DMEL Effects on consumers Acute Acute	centration - PNEC water e water water sediment ne water sediment cet level - DNEL / DMEL Effects on consumers Acute Acute Chronic local systemic local VND	centration - PNEC water e water water sediment ne water sediment cet level - DNEL / DMEL Effects on consumers Acute Acute Chronic Chronic local systemic VND 0,75 mg/kg/d  VND 3,571	centration - PNEC water e water water sediment ne water sediment cet level - DNEL / DMEL Effects on consumers Acute Acute Chronic Chronic Acute local systemic local systemic local VND 0,75 mg/kg/d  VND 3,571	centration - PNEC           water         0,006           e water         0,0006           water sediment         0,996           ne water sediment         0,0996           net level - DNEL / DMEL         Effects on consumers           Acute         Acute         Chronic         Chronic         Acute         Acute           Iocal         systemic         local         systemic         local         systemic           VND         0,75         mg/kg/d         mg/kg/d         WND         3,571	centration - PNEC           water         0,006         mg/l           e water         0,0006         mg/l           water sediment         0,996         mg/kg           ne water sediment         0,0996         mg/kg           ct level - DNEL / DMEL         Effects on workers           Acute         Acute         Chronic           Acute         Acute         Chronic           local         systemic         local           VND         0,75         mg/kg/d           VND         VND				

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

hazard ; MED = medium hazard ; HIGH = high hazard.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Protect your hands with gloves of the following type:

Material: Nitrile rubber (NBR)

Thickness: 0,35 mm
Breakthrough time: 480 min

Material: Butyl rubber (IIR) Thickness: 0,5 mm Breakthrough time: 480 min

SKIN PROTECTION
Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

## **SECTION 9. Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

PropertiesValueInformationAppearancepaste

Colour not available



## 25J - BETON CR (A)

Revision nr.8 Dated 18/09/2024 Printed on 18/09/2024
Page n. 8 / 14
Replaced revision:7 (Dated 20/06/2023)

## SECTION 9. Physical and chemical properties ..../>>

Melting point / freezing point

Initial boiling point

Flammability

Lower explosive limit Upper explosive limit

Flash point

Auto-ignition temperature Decomposition temperature

Kinematic viscosity

Solubility

Partition coefficient: n-octanol/water

Vapour pressure

Density and/or relative density Relative vapour density

Particle characteristics

characteristic not determined

200 not determined

not determined not determined

100 not determined not determined not applicable

> not determined insoluble in water not applicable

not determined 1,64 kg/l

not determined not applicable

Reason for missing data:not determined

Reason for missing data not determined Reason for missing data:not determined

Reason for missing data:not determined Reason for missing data:not determined

Reason for missing data not determined

Reason for missing data:not determined

Reason for missing data:not determined

#### 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

## SECTION 10. Stability and reactivity

## 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

## 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

## 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

### 10.5. Incompatible materials

Information not available

#### 10.6. Hazardous decomposition products

Information not available

## **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available



Revision nr.8 Dated 18/09/2024 Printed on 18/09/2024 Page n. 9 / 14 Replaced revision:7 (Dated 20/06/2023)

### SECTION 11. Toxicological information ..../>>

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

ATE (Oral) of the mixture:

ATE (Dermal) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

TITANIUM DIOXIDE

LD50 (Oral): > 10000 mg/kg Rat

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

LD50 (Dermal): > 10000 mg/kg Rat

Cashew (Anacardium occidentale) Nutshell Extract, Decarboxylated, Distilled

LD50 (Dermal): 1100 mg/kg LD50 (Oral): 500 mg/kg

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and

[2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

LD50 (Dermal): > 2000 mg/kg Rat LD50 (Oral): > 5000 mg/kg Rat

### SKIN CORROSION / IRRITATION

Causes skin irritation

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and

[2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane The skin irritation of bisphenol F diglycidyl ether was determined to be mild to non-irritating based on the six Klimisch 1 and 2 studies conducted according to OECD guidelines.

In the experimental conditions used, only one product induced erythema and edema reactions above the significance threshold (score 2 for erythema or edema) and was classified as irritant according to EEC directive no. 83/467/1983. The other studies indicated mild irritation, but not sufficient to reach the classification threshold.

Two repeated dose cumulative irritation studies were performed and under the experimental conditions employed the test materials induced significant irritation after repeated application and a potential for cumulative skin irritation was found in albino rabbits. Effects on skin irritation/corrosion: slightly irritating.

## SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and

[2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane The ocular irritation of bisphenol F diglycidyl ether was determined to be non-irritating based on the four Klimisch 1 and 2 studies conducted according to OECD guidelines. In rabbit eye irritation tests, 0.1 ml of the test material caused no irritation and no initial pain response.

#### RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

Skin sensitization

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and

[2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane Bisphenol F diglycidyl ether (BPFDGE) tested positive for induction of skin sensitization in the mouse Local Lymph Node Assay (LLNA). Based on an EC3 value of 0.7%, BPFDGE is considered a strong skin sensitizer. According to ECHA guidelines, this EC3





## 25J - BETON CR (A)

Revision nr.8 Dated 18/09/2024 Printed on 18/09/2024 Page n. 10 / 14 Replaced revision:7 (Dated 20/06/2023)

#### SECTION 11. Toxicological information .../>>

value was converted to an EC3 value of 175 ug/cm2 and is considered the LOAEL for the induction of skin sensitization in the LLNA mouse for BPFDGE. From sensitization tests it can be concluded that BPFDGE is a sensitizer.

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

May damage fertility

#### STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## **SECTION 12. Ecological information**

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

### 12.1. Toxicity

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

LC50 - for Fish > 5000 mg/l/96h Rainbow trout

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and

 $\label{lem:control} \hbox{$[2$-(4-(oxiran-2-ylmethoxy)benzyl]phenoxy}$ methyl) oxirane \ and \ \hbox{$[2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane}$ and \ \hbox{$[2,2'-[methylenebis(2,1-phenyleneoxymethyleneoxyme$ 

LC50 - for Fish 2,54 mg/l/96h

EC50 - for Crustacea 2,55 mg/l/48h Daphnia Magna

EC50 - for Algae / Aquatic Plants 1,8 mg/l/72h

bis-[4-(2,3-epoxipropoxi)phenyl]propane

LC50 - for Fish 1,5 mg/l/96h Fish

## 12.2. Persistence and degradability

TITANIUM DIOXIDE

Solubility in water < 0,001 mg/l

Degradability: information not available

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Solubility in water 0,483 mg/l

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Solubility in water 0,1 - 100 mg/l

NOT rapidly degradable

## 12.3. Bioaccumulative potential





Revision nr.8 Dated 18/09/2024 Printed on 18/09/2024 Page n. 11 / 14 Replaced revision:7 (Dated 20/06/2023)

### **SECTION 12. Ecological information** .../>>

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Partition coefficient: n-octanol/water 6 Log Kow BCF 263

Cashew (Anacardium occidentale) Nutshell Extract, Decarboxylated, Distilled Partition coefficient: n-octanol/water > 4,78 Log Kow

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Partition coefficient: n-octanol/water > 2,918 BCF 31

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0.1%.

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

## **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

## 14.1. UN number or ID number

not applicable

### 14.2. UN proper shipping name

not applicable

## 14.3. Transport hazard class(es)

not applicable

## 14.4. Packing group

not applicable





## 25J - BETON CR (A)

Revision nr.8 Dated 18/09/2024 Printed on 18/09/2024
Page n. 12 / 14
Replaced revision:7 (Dated 20/06/2023)

#### SECTION 14. Transport information .../>>

#### 14.5. Environmental hazards

not applicable

#### 14.6. Special precautions for user

not applicable

#### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

## **SECTION 15. Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point

Contained substance Point

75

Point DIISONONYL PHTHALATE REACH Reg.: 01-2119430798-28

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

Substances subject to the Rotterdam Convention:

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

## 15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances bis-[4-(2,3-epoxipropoxi)phenyl]propane

### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Reproductive toxicity, category 1B Repr. 1B Acute Tox. 4 Acute toxicity, category 4 Skin Corr. 1B Skin corrosion, category 1B Eye Dam. 1 Serious eye damage, category 1 Eye Irrit. 2 Eye irritation, category 2 Skin Irrit. 2 Skin irritation, category 2 Skin Sens. 1 Skin sensitization, category 1 Skin Sens. 1A Skin sensitization, category 1A

**Aquatic Chronic 2** Hazardous to the aquatic environment, chronic toxicity, category 2 **Aquatic Chronic 3** Hazardous to the aquatic environment, chronic toxicity, category 3

H360F May damage fertility.

#### ΕN



## NORD RESINE S.p.A.

## 25J - BETON CR (A)

Revision nr.8 Dated 18/09/2024 Printed on 18/09/2024 Page n. 13 / 14 Replaced revision:7 (Dated 20/06/2023)

#### SECTION 16. Other information .../>>

H302 Harmful if swallowed.
H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

**EUH029** Contact with water liberates toxic gas.

**EUH204** Contains isocyanates. May produce an allergic reaction. **EUH205** Contains epoxy constituents. May produce an allergic reaction.

**EUH212** Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)



## 25J - BETON CR (A)

Revision nr.8 Dated 18/09/2024 Printed on 18/09/2024 Page n. 14 / 14 Replaced revision:7 (Dated 20/06/2023)

#### SECTION 16. Other information .../>>

- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

#### Changes to previous review:

The following sections were modified:

02 / 03 / 04 / 08 / 09 / 11 / 12 / 13 / 15 / 16.