

## Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: **26W**  
Product name: **ESTER PE (A)**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Bi-component product formulated with polyester resins**

#### 1.3. Details of the supplier of the safety data sheet

Name: **NORD RESINE S.p.A.**  
Full address: **Via Fornace Vecchia, 79**  
District and Country: **31058 Susegana (TV) Italia**  
Tel.: **+39 0438-437511**  
Fax: **+39 0438-435155**  
e-mail address of the competent person responsible for the Safety Data Sheet: **annabreda@nordresine.com**  
Supplier: **NORD RESINE S.p.A.**

#### 1.4. Emergency telephone number

For urgent inquiries refer to: **+39 0438 437511**

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

##### Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Reproductive toxicity, category 2	H361d	Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

### SECTION 2. Hazards identification ... / >>

#### Hazard statements:

<b>H226</b>	Flammable liquid and vapour.
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H372</b>	Causes damage to organs through prolonged or repeated exposure.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH208</b>	Contains: COBALT BIS 2-ETHYL HEXANOATE May produce an allergic reaction.

#### Precautionary statements:

<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P331</b>	Do NOT induce vomiting.
<b>P280</b>	Wear protective gloves/ protective clothing / eye protection / face protection.
<b>P301+P310</b>	IF SWALLOWED: immediately call a POISON CENTER / doctor.
<b>P370+P378</b>	In case of fire: use carbon anhydride, foam, nebulized water to extinguish.
<b>P261</b>	Avoid breathing dust / fume / gas / mist / vapours / spray.

**Contains:** STYRENE  
ISOPROPENYL BENZENE

#### VOC (Directive 2004/42/EC) :

Two - pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition :

412,77

Limit value:

500,00

- Catalysed with :

2,04 %

ESTER VE/PE (B)

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

## SECTION 3. Composition/information on ingredients

### 3.2. Mixtures

#### Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>STYRENE</b>		
CAS 100-42-5	$25 \leq x < 35$	Flam. Liq. 3 H226, Repr. 2 H361d, Acute Tox. 4 H332, STOT RE 1 H372, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: D LC50 Inhalation vapours: 11,8 mg/l/4h
EC 202-851-5		
INDEX 601-026-00-0		
REACH Reg. 01-2119457861-32		
<b>TITANIUM DIOXIDE</b>		
CAS 13463-67-7	$4 \leq x < 8$	EUH212
EC 236-675-5		
INDEX		
REACH Reg. 01-2119489379-17		
<b>ISOPROPENYL BENZENE</b>		
CAS 98-83-9	$1 \leq x < 2,5$	Flam. Liq. 3 H226, Eye Irrit. 2 H319, STOT SE 3 H335, Aquatic Chronic 2 H411
EC 202-705-0		
INDEX		
REACH Reg. 01-2119472426-35		

### SECTION 3. Composition/information on ingredients ... / >>

**COBALT BIS 2-ETHYL HEXANOATE**

CAS 136-52-7 0 ≤ x &lt; 1

Repr. 2 H361, Eye Irrit. 2 H319, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 3 H412

EC 205-250-6

INDEX

REACH Reg. 01-211952478-29

**2-METHOXY-1-METHYLETHYL ACETATE**

CAS 108-65-6 0 ≤ x &lt; 1

Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-603-9

INDEX 607-195-00-7

REACH Reg. 01-2119475791-29

**XYLENE (MIXTURE OF ISOMERS)**

CAS 1330-20-7 0 ≤ x &lt; 1

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C STA Dermal: 1100 mg/kg, STA Inhalation vapours: 11 mg/l

EC 215-535-7

INDEX 601-022-00-9

REACH Reg. 01-2119488216-32

**Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides**

CAS 61789-72-8 0 ≤ x &lt; 0,25

Acute Tox. 4 H302, Skin Corr. 1B H314, Eye Dam. 1 H318, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1 LD50 Oral: 398

EC 263-081-3

INDEX

REACH Reg. 01-2119970169-28

**N-BUTYL ACETATE**

CAS 123-86-4 0 ≤ x &lt; 1

Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

EC 204-658-1

INDEX 607-025-00-1

REACH Reg. 01-2119485493-29

**QUARTZ**

CAS 14808-60-7 0 ≤ x &lt; 1

STOT RE 1 H372

EC 238-878-4

INDEX

**XYLENE (MIXTURE OF ISOMERS)**

CAS 1330-20-7 0 ≤ x &lt; 1

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C STA Dermal: 1100 mg/kg, STA Inhalation vapours: 11 mg/l

EC 215-535-7

INDEX 601-022-00-9

REACH Reg. 01-2119488216-32

**ETHYLBENZENE**

CAS 100-41-4 0 ≤ x &lt; 1

Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373 LC50 Inhalation vapours: 17,2 mg/l/4h

EC 202-849-4

INDEX 601-023-00-4

REACH Reg. 01-2119489370-35

**METHYL ETHYL KETONE**

CAS 78-93-3 0 ≤ x &lt; 1

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 201-159-0

INDEX 606-002-00-3

REACH Reg. 01-2119457290-43

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### SECTION 4. First aid measures

#### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

**SECTION 4. First aid measures ... / >>****4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

**6.2. Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

**7.2. Conditions for safe storage, including any incompatibilities**

### SECTION 7. Handling and storage ... / >>

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

### SECTION 8. Exposure controls/personal protection

#### 8.1. Control parameters

Regulatory References:

CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelethez a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

### SECTION 8. Exposure controls/personal protection ... / >>

#### STYRENE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	100	23,1	400	92,4	
AGW	DEU	86	20	172	40	
MAK	DEU	86	20	172	40	
VLA	ESP	86	20	172	40	
VLEP	FRA	100	23,3	200	46,6	
TLV	GRC	425	100	1050	250	
AK	HUN	86		172		
GVI/KGVI	HRV	430	100	1080	250	SKIN
TGG	NLD	107				
NDS/NDSch	POL	50		100		
TLV	ROU	50	12	150	35	
MV	SVN	86	20	344	80	
WEL	GBR	430	100	1080	250	
TLV-ACGIH		10		20		

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	0,028	mg/l
Normal value in marine water	0,014	mg/l
Normal value for fresh water sediment	0,614	mg/kg/d
Normal value for marine water sediment	0,307	mg/kg/d
Normal value for water, intermittent release	0,04	mg/l
Normal value of STP microorganisms	5	mg/l
Normal value for the terrestrial compartment	0,2	mg/kg/d

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				2,1 mg/kg bw/d				
Inhalation	182,75 mg/m3	174,25 mg/m3		10,2 mg/m3	306 mg/m3	289 mg/m3		85 mg/m3
Skin				343 mg/kg bw/d				406 mg/kg bw/d

#### TITANIUM DIOXIDE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	10				
VLEP	FRA	10				
TLV	GRC		10			
GVI/KGVI	HRV	10				INHAL
GVI/KGVI	HRV	4				RESP
NDS/NDSch	POL	10				INHAL
TLV	ROU	10		15		
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV-ACGIH		10				

### SECTION 8. Exposure controls/personal protection ... / >>

#### ISOPROPENYLBENZENE

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	0,008	mg/l
Normal value in marine water	0,001	mg/l
Normal value for fresh water sediment	0,583	mg/kg/d
Normal value for marine water sediment	0,058	mg/kg/d
Normal value of STP microorganisms	66,15	mg/l
Normal value for the terrestrial compartment	0,112	mg/kg/d

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				11,4 mg/kg bw/d				
Inhalation	492 mg/m3			41 mg/m3				246 mg/m3
Skin				11,4 mg/kg bw/d				38 mg/kg bw/d

#### COBALT BIS 2-ETHYL HEXANOATE

##### Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations	
TLV	CZE	0,05		0,1		INHAL	Jako Co
GVI/KGVI	HRV	0,1				INHAL	
GVI/KGVI	HRV	0,1				SKIN	
WEL	GBR	0,1					As Co
TLV-ACGIH		0,02				INHAL	Co

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00051	mg/l
Normal value in marine water	0,00236	mg/l
Normal value for fresh water sediment	9,5	mg/kg
Normal value for marine water sediment	9,5	mg/kg/d
Normal value of STP microorganisms	0,37	mg/l
Normal value for the terrestrial compartment	7,9	mg/kg

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,0558 mg/kg bw/d				
Inhalation			0,2351 mg/m3				0,037 mg/m3	

### SECTION 8. Exposure controls/personal protection ... / >>

#### 2-METHOXY-1-METHYLETHYL ACETATE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
TLV	CZE	270	49,14	550	100,1	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
VLA	ESP	275	50	550	100	SKIN
VLEP	FRA	275	50	550	100	SKIN
TLV	GRC	275	50	550	100	
AK	HUN	275		550		
GVI/KGVI	HRV	275	50	550	100	SKIN
VLEP	ITA	275	50	550	100	SKIN
TGG	NLD	550				
VLE	PRT	275	50	550	100	SKIN
NDS/NDSch	POL	260		520		SKIN
TLV	ROU	275	50	550	100	SKIN
MV	SVN	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	mg/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value for water, intermittent release	6,35	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	0,29	mg/kg

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				1,67				
				mg/kg/d				
Inhalation				33				275
				mg/m <sup>3</sup>				mg/m <sup>3</sup>
Skin				54,8				153,5
				mg/kg/d				mg/kg/d

#### XYLENE (MIXTURE OF ISOMERS)

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
TLV	CZE	200	45,4	400	90,8	SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
TLV	GRC	435	100	650	150	
AK	HUN	221		442		SKIN
GVI/KGVI	HRV	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
TGG	NLD	210		442		SKIN
VLE	PRT	221	50	442	100	SKIN
NDS/NDSch	POL	100		200		SKIN
TLV	ROU	221	50	442	100	SKIN
MV	SVN	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	



### SECTION 8. Exposure controls/personal protection ... / >>

#### Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation				1,64 mg/kg				3,96 mg/kg
Skin				3,4 mg/kg bw/d				5,7 mg/kg bw/d

#### N-BUTYL ACETATE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	950	196,65	1200	248,4	
AGW	DEU	300	62	600 (C)	124 (C)	
VLA	ESP	241	50	724	150	
VLEP	FRA	710	150	940	200	
TLV	GRC	710	150	950	200	
AK	HUN	241		723		
GVI/KGVI	HRV	241	50	723	150	
VLEP	ITA	241	50	723	150	
TGG	NLD	150				
VLE	PRT	241	50	723	150	
NDS/NDSch	POL	240		720		
TLV	ROU	241	50	723	150	
MV	SVN	300	62	600	124	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

#### QUARTZ

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		0,05			RESP
VLEP	FRA	0,1				RESP
GVI/KGVI	HRV	0,1				
VLEP	ITA	0,1				RESP
TGG	NLD	0,075				RESP
VLE	PRT	0,025				RESP
NDS/NDSch	POL	0,1				RESP
TLV	ROU	0,1				RESP
MV	SVN	0,15				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				RESP

### SECTION 8. Exposure controls/personal protection ... / >>

#### XYLENE (MIXTURE OF ISOMERS)

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	200	46	400	92	SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
TLV	GRC	435	100	650	150	
GVI/KGVI	HRV	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
TGG	NLD	210		442		SKIN
VLE	PRT	221	50	442	100	SKIN
NDS/NDSch	POL	100		200		SKIN
TLV	ROU	221	50	442	100	SKIN
MV	SVN	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg
Normal value for water, intermittent release	0,327	mg/l
Normal value of STP microorganisms	6,58	mg/l
Normal value for the terrestrial compartment	2,31	mg/kg

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral								1,6 mg/kg/d
Inhalation				14,8 mg/m3	289 mg/m3	289 mg/m3		77 mg/m3
Skin				108 mg/kg/d				180 mg/kg/d

#### ETHYLBENZENE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	200	45,4	500	113,5	SKIN
AGW	DEU	88	20	176	40	SKIN
MAK	DEU	88	20	176	40	SKIN
VLA	ESP	441	100	884	200	SKIN
VLEP	FRA	88,4	20	442	100	SKIN
TLV	GRC	435	100	545	125	
AK	HUN	442		884		SKIN
GVI/KGVI	HRV	442	100	884	200	SKIN
VLEP	ITA	442	100	884	200	SKIN
TGG	NLD	215		430		SKIN
VLE	PRT	442	100	884	200	SKIN
NDS/NDSch	POL	200		400		SKIN
TLV	ROU	442	100	884	200	SKIN
MV	SVN	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

### SECTION 8. Exposure controls/personal protection ... / >>

#### METHYL ETHYL KETONE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
TLV	CZE	600	200,4	900	300,6	
AGW	DEU	600	200	600	200	SKIN
MAK	DEU	600	200	600	200	SKIN
VLA	ESP	600	200	900	300	
VLEP	FRA	600	200	900	300	SKIN
TLV	GRC	600	200	900	300	
AK	HUN	600		900		SKIN
GVI/KGVI	HRV	600	200	900	300	
VLEP	ITA	600	200	900	300	
TGG	NLD	590		500		SKIN
VLE	PRT	600	200	900	300	
NDS/NDSch	POL	450		900		SKIN
TLV	ROU	600	200	900	300	
MV	SVN	600	200	900	300	SKIN
WEL	GBR	600	200	899	300	SKIN
OEL	EU	600	200	900	300	
TLV-ACGIH		590	200	885	300	

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	55,8	mg/l
Normal value in marine water	55,8	mg/l
Normal value for fresh water sediment	284,74	mg/kg
Normal value of STP microorganisms	709	mg/l
Normal value for the food chain (secondary poisoning)	100	mg/kg
Normal value for the terrestrial compartment	22,5	mg/kg

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				31				
				mg/kg bw/d				
Inhalation				106				600
				mg/m <sup>3</sup>				mg/m <sup>3</sup>
Skin				412				1161
				mg/kg bw/d				mg/kg bw/d

##### Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.  
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of

### SECTION 8. Exposure controls/personal protection ... / >>

gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

### SECTION 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	viscous liquid	
Colour	TYPICAL	
Odour	characteristic	
Melting point / freezing point	Not available	
Initial boiling point	146 °C	
Flammability	Not available	
Lower explosive limit	1,1 % (v/v)	
Upper explosive limit	8 % (v/v)	
Flash point	> 30 °C	
Auto-ignition temperature	Not available	
pH	Not available	
Kinematic viscosity	Not available	
Solubility	Not available	
Partition coefficient: n-octanol/water	Not available	
Vapour pressure	Not available	
Density and/or relative density	1,15	
Relative vapour density	Not available	
Particle characteristics	Not applicable	

#### 9.2. Other information

##### 9.2.1. Information with regard to physical hazard classes

Information not available

##### 9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC) :	36,28 %	-	417,27	g/litre
VOC (volatile carbon)	33,39 %	-	384,04	g/litre

### SECTION 10. Stability and reactivity

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

##### STYRENE

Polymerises at temperatures above 65°C/149°F. Fire hazard. Possibility of explosion.

Added with an inhibitor that requires a small amount of dissolved oxygen at temperatures < 25°C/77°F.

##### 2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

##### N-BUTYL ACETATE

Decomposes on contact with: water.

##### METHYL ETHYL KETONE

Reacts with: light metals, strong oxidants. Attacks various types of plastic materials. Decomposes under the effect of heat.

#### 10.2. Chemical stability

**SECTION 10. Stability and reactivity** ... / >>

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

The vapours may also form explosive mixtures with the air.

**STYRENE**

May react dangerously with: peroxides, strong acids. May polymerise on contact with: aluminium trichloride, azobisisobutyronitrile, dibenzoyl peroxide, sodium. Risk of explosion on contact with: butyllithium, chlorosulphuric acid, di-tert-butyl peroxide, oxidising substances, oxygen.

**2-METHOXY-1-METHYLETHYL ACETATE**

May react violently with: oxidising substances, strong acids, alkaline metals.

**XYLENE (MIXTURE OF ISOMERS)**

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

**N-BUTYL ACETATE**

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

**XYLENE (MIXTURE OF ISOMERS)**

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

**ETHYLBENZENE**

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

**METHYL ETHYL KETONE**

May form peroxides with: air, light, strong oxidising agents. Risk of explosion on contact with: hydrogen peroxide, nitric acid, sulphuric acid. May react dangerously with: oxidising agents, trichloromethane, alkalis. Forms explosive mixtures with: air.

**10.4. Conditions to avoid**

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

**STYRENE**

Avoid contact with: oxidising substances, copper, strong acids.

**N-BUTYL ACETATE**

Avoid exposure to: moisture, sources of heat, naked flames.

**METHYL ETHYL KETONE**

Avoid exposure to: sources of heat.

**10.5. Incompatible materials****STYRENE**

Incompatible materials: plastic materials.

**2-METHOXY-1-METHYLETHYL ACETATE**

Incompatible with: oxidising substances, strong acids, alkaline metals.

**N-BUTYL ACETATE**

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

**METHYL ETHYL KETONE**

Incompatible with: strong oxidants, inorganic acids, ammonia, copper, chloroform.

**10.6. Hazardous decomposition products**

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

**ETHYLBENZENE**

May develop: methane, styrene, hydrogen, ethane.

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Metabolism, toxicokinetics, mechanism of action and other information**2-METHOXY-1-METHYLETHYL ACETATE**

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

**SECTION 11. Toxicological information ... / >>****STYRENE**

WORKERS: inhalation; contact with the skin.

**2-METHOXY-1-METHYLETHYL ACETATE**

WORKERS: inhalation; contact with the skin.

**XYLENE (MIXTURE OF ISOMERS)**

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

**N-BUTYL ACETATE**

WORKERS: inhalation; contact with the skin.

**XYLENE (MIXTURE OF ISOMERS)**

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of environmental air.

**ETHYLBENZENE**

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**STYRENE**

The acute toxicity by inhalation at 1000 ppm affects the central nervous system with headache and dizziness, lack of coordination; irritation of the eye and respiratory tract mucous membranes occurs at 500 ppm. Chronic exposure causes depression of the central and peripheral nervous system with loss of memory, headache and drowsiness starting at 20 ppm; digestive disorders with nausea and loss of appetite; irritation of the respiratory tract with chronic bronchitis; dermatosis. Repeated exposure, at low doses of inhaled substance, causes irreversible changes to hearing and may cause changes in colour vision. No certain data is available on the reversibility of the visual impairment. Repeated skin exposure causes irritation. The substance degrades the skin, which can cause dryness and cracking.

**2-METHOXY-1-METHYLETHYL ACETATE**

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

**XYLENE (MIXTURE OF ISOMERS)**

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

**N-BUTYL ACETATE**

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

**XYLENE (MIXTURE OF ISOMERS)**

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

**ETHYLBENZENE**

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesl). Is irritating for skin, conjunctiva and respiratory tract.

Interactive effects**STYRENE**

The metabolism of the substance is inhibited by ethanol. When styrene is photo-oxidised with ozone and nitrogen dioxide, as in the formation of smog, products highly irritating for the human eye may ensue.

**XYLENE (MIXTURE OF ISOMERS)**

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

**N-BUTYL ACETATE**

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed

### SECTION 11. Toxicological information ... / >>

xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

#### XYLENE (MIXTURE OF ISOMERS)

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

#### ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

#### STYRENE

LD50 (Oral):	5000 mg/kg Rat
LC50 (Inhalation vapours):	11,8 mg/l/4h Rat

#### TITANIUM DIOXIDE

LD50 (Oral):	> 10000 mg/kg Rat
--------------	-------------------

#### COBALT BIS 2-ETHYL HEXANOATE

LD50 (Dermal):	> 2000 mg/kg Rat - Wistar
LD50 (Oral):	3129 mg/kg Rat - Sprague-Dawley

#### 2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Dermal):	> 5000 mg/kg Rat
LD50 (Oral):	8530 mg/kg Rat

#### XYLENE (MIXTURE OF ISOMERS)

LD50 (Dermal):	4350 mg/kg Rabbit
STA (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	26 mg/l/4h Rat

#### Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides

LD50 (Oral):	398 mg/kg Rat
--------------	---------------

#### N-BUTYL ACETATE

LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 6400 mg/kg Rat
LC50 (Inhalation vapours):	21,1 mg/l/4h Rat

#### XYLENE (MIXTURE OF ISOMERS)

LD50 (Dermal):	4350 mg/kg Rabbit
STA (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	26 mg/l/4h Rat

#### ETHYLBENZENE

LD50 (Dermal):	15354 mg/kg Rabbit
LD50 (Oral):	3500 mg/kg Rat
LC50 (Inhalation vapours):	17,2 mg/l/4h Rat

#### METHYL ETHYL KETONE

LD50 (Dermal):	6480 mg/kg Rabbit
LD50 (Oral):	2737 mg/kg Rat
LC50 (Inhalation vapours):	23,5 mg/l/8h Rat

#### SKIN CORROSION / IRRITATION

Causes skin irritation

**SECTION 11. Toxicological information** ... / >>SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

COBALT BIS 2-ETHYL HEXANOATE

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

**STYRENE**

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2002).

Classified as "probable carcinogen" by the US National Toxicology Program (NTP) - (US DHHS, 2014).

**XYLENE (MIXTURE OF ISOMERS)**

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

**XYLENE (MIXTURE OF ISOMERS)**

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

**ETHYLBENZENE**

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).

Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Suspected of damaging the unborn child

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available

STOT - SINGLE EXPOSURE

May cause respiratory irritation

Target organs

Information not available



### SECTION 11. Toxicological information ... / >>

#### Route of exposure

Information not available

#### STOT - REPEATED EXPOSURE

Causes damage to organs

#### Target organs

Information not available

#### Route of exposure

Information not available

#### ASPIRATION HAZARD

Toxic for aspiration

### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

### SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

#### 12.1. Toxicity

##### COBALT BIS 2-ETHYL HEXANOATE

LC50 - for Fish	275 mg/l/96h Fundulus heteroclitus
EC50 - for Algae / Aquatic Plants	0,144 mg/l/72h

##### STYRENE

LC50 - for Fish	4,02 mg/l/96h Pimephales promelas
EC50 - for Crustacea	4,7 mg/l/48h Daphnia magna

##### ISOPROPENYLBENZENE

LC50 - for Fish	2,97 mg/l/96h Fish
EC50 - for Crustacea	1,645 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	11,441 mg/l/72h Alghe
Chronic NOEC for Crustacea	0,401 mg/l 21 days

##### Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides

LC50 - for Fish	0,1 mg/l/96h Fish
EC50 - for Crustacea	0,059 mg/l/48h Daphnia
EC50 - for Algae / Aquatic Plants	0,11 Algae

#### 12.2. Persistence and degradability

##### XYLENE (MIXTURE OF ISOMERS)

Solubility in water	100 - 1000 mg/l
Rapidly degradable	

##### COBALT BIS 2-ETHYL HEXANOATE

Solubility in water	> 10000 mg/l
Rapidly degradable	

##### TITANIUM DIOXIDE

Solubility in water	< 0,001 mg/l
Degradability: information not available	

##### 2-METHOXY-1-METHYLETHYL ACETATE

Solubility in water	> 10000 mg/l
Rapidly degradable	

### SECTION 12. Ecological information ... / >>

ETHYLBENZENE  
Solubility in water 1000 - 10000 mg/l  
Rapidly degradable

STYRENE  
Solubility in water 320 mg/l  
Rapidly degradable

METHYL ETHYL KETONE  
Solubility in water > 10000 mg/l  
Rapidly degradable

N-BUTYL ACETATE  
Solubility in water 1000 - 10000 mg/l

XYLENE (MIXTURE OF ISOMERS)  
Solubility in water 100 - 1000 mg/l  
Degradability: information not available

#### 12.3. Bioaccumulative potential

XYLENE (MIXTURE OF ISOMERS)  
Partition coefficient: n-octanol/water 3,12  
BCF 25,9

2-METHOXY-1-METHYLETHYL ACETATE  
Partition coefficient: n-octanol/water 1,2

ETHYLBENZENE  
Partition coefficient: n-octanol/water 3,6

STYRENE  
Partition coefficient: n-octanol/water 2,96  
BCF 74

METHYL ETHYL KETONE  
Partition coefficient: n-octanol/water 0,3

N-BUTYL ACETATE  
Partition coefficient: n-octanol/water 2,3  
BCF 15,3

Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides  
BCF 6898

XYLENE (MIXTURE OF ISOMERS)  
Partition coefficient: n-octanol/water 3,12  
BCF 25,9

#### 12.4. Mobility in soil

XYLENE (MIXTURE OF ISOMERS)  
Partition coefficient: soil/water 2,73

STYRENE  
Partition coefficient: soil/water 2,55

N-BUTYL ACETATE  
Partition coefficient: soil/water < 3

XYLENE (MIXTURE OF ISOMERS)  
Partition coefficient: soil/water 2,73

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

### SECTION 12. Ecological information ... / >>

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

### SECTION 13. Disposal considerations

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### SECTION 14. Transport information

#### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1866

The product, if packaged in packages of less than 450 litres, is not subject to ADR regulations as stated in 2.2.3.1.5.

The product, if packaged in packages of less than 450 litres, is not subject to obligations relating to marking, labelling and package testing in accordance with 2.3.2.5 of the IMDG CODE.

#### 14.2. UN proper shipping name

ADR / RID: RESIN SOLUTION

IMDG: RESIN SOLUTION

IATA: RESIN SOLUTION

#### 14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



#### 14.4. Packing group

ADR / RID, IMDG, IATA: III

#### 14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

### SECTION 14. Transport information ... / >>

#### 14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	Special provision: -	Limited Quantities: 5 L	
IATA:	EMS: F-E, S-E	Maximum quantity: 220 L	Packaging instructions: 366
	Cargo:	Maximum quantity: 60 L	Packaging instructions: 355
	Pass.:		
	Special provision:	A3	

#### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

### SECTION 15. Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product	
Point	3 - 40
Contained substance	
Point	75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors  
Not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Two - pack performance coatings.

#### 15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

N-BUTYL ACETATE

METHYL ETHYL KETONE

### SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Repr. 2</b>	Reproductive toxicity, category 2
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>STOT RE 1</b>	Specific target organ toxicity - repeated exposure, category 1
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>Skin Corr. 1B</b>	Skin corrosion, category 1B
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2

### SECTION 16. Other information ... / >>

<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment, acute toxicity, category 1
<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment, chronic toxicity, category 1
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H361</b>	Suspected of damaging fertility or the unborn child.
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H372</b>	Causes damage to organs through prolonged or repeated exposure.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H400</b>	Very toxic to aquatic life.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH212</b>	Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament

**SECTION 16. Other information** ... / >>

11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

**Changes to previous review:**

The following sections were modified:

01 / 02 / 03 / 04 / 05 / 07 / 08 / 09 / 10 / 11 / 12 / 15 / 16.