

Revision nr.5 Dated 03/09/2024 Printed on 03/09/2024 Page n. 1 / 13 Replaced revision:4 (Dated 26/11/2019) ΕN

## **Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the	SubStance/m	inclure and of the comp	any/undertaking	
1.1. Product identifier				
Code:	27R			
Product name	NORDPR	DM SV		
1.2. Relevant identified uses of the substance	e or mixture and	uses advised against		
Intended use	Primer for	r coated surfaces		
1.3. Details of the supplier of the safety data	sheet			
Name	NORD RE	SINE S.p.A.		
Full address	Via Fornace Vecchia, 79			
District and Country	31058	Susegana Italia	(TV)	
	Tel.	+39 0438-437511		
a martina dala se a falsa se anna fan fan anna a	Fax	+39 0438-435155		
e-mail address of the competent person				
responsible for the Safety Data Sheet	annabred	a@nordresine.com		
Supplier:	NORD RE	SINE S.p.A.		
1.4. Emergency telephone number				
For urgent inquiries refer to	+39 0438	437511		

## **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements: H225 H319 H315

Highly flammable liquid and vapour. Causes serious eye irritation. Causes skin irritation.



Revision nr.5 Dated 03/09/2024 Printed on 03/09/2024 Page n. 2 / 13 Replaced revision:4 (Dated 26/11/2019)

#### SECTION 2. Hazards identification ... / >>

H317	May cause an allergic skin reaction.
Precautionary statements:	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P370+P378	In case of fire: use carbon anhydride, foam, nebulized water to extinguish.
P261	Avoid breathing dust / fume / gas / mist / vapours / spray.
P233	Keep container tightly closed.
P333+P313	If skin irritation or rash occurs: Get medical advice / attention.

Contains: 3-AMINOPROPYLTRYETHOXYSILANE

VOC (Directive 2004/42/EC) :	
Binding primers. VOC given in g/litre of product in a ready-to-use condition :	749,60
Limit value:	750,00

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\ge 0.1\%$ .

## **SECTION 3. Composition/information on ingredients**

## 3.2. Mixtures

Contains:

Identification		x = Conc. %	Classification (EC) 1272/2008 (CLP)
ETHANOL			
INDEX	603-002-00-5	75≤x< 100	Flam. Liq. 2 H225, Eye Irrit. 2 H319
EC	200-578-6		
CAS	64-17-5		
REACH Reg.	01-2119457290-43		
3-AMINOPRO	PYLTRYETHOXYSIL	ANE	
INDEX	612-108-00-0	1 ≤ x < 3	Acute Tox. 4 H302, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317
EC	213-048-4		ATE Oral: 500 mg/kg
CAS	919-30-2		
REACH Reg.	01-2119480479-24		
ETHYL METH	YL KETONE		
INDEX	606-002-00-3	0,5 ≤ x < 1	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC	201-159-0		
CAS	78-93-3		
REACH Reg.	01-2119457290-43		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.



ΕN

#### SECTION 4. First aid measures ... / >>

#### Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

#### 4.3. Indication of any immediate medical attention and special treatment needed

If skin irritation or rash occurs: Get medical advice / attention. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment: see section 4.1

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

## SECTION 5. Firefighting measures

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

#### 5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### **SECTION 6.** Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up



#### SECTION 6. Accidental release measures .... / >>

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

## **SECTION 8. Exposure controls/personal protection**

#### 8.1. Control parameters

CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb.,
		kterým se stanoví podmínky ochrany zdraví při práci
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur
		Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ''σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με
		την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία''»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3,
NLD	nedenand	eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	6 I 3 6 6
POL	Poiska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru
		modificarea și completarea hotărârii guvernului nr. 1.093/2006
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК)
	Clavianija	ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	-	



a lat 1 for 16 Martin

# NORD RESINE S.p.A. 27R - NORDPROM SV

Revision nr.5 Dated 03/09/2024 Printed on 03/09/2024 Page n. 5 / 13 Replaced revision:4 (Dated 26/11/2019)

#### SECTION 8. Exposure controls/personal protection ... / >>

EU

OEL EU

Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. ACGIH 2023

TLV-ACGIH

ETHYL METHYL KETONE

reshold Limit V	/alue									
Туре	Country	TWA/8h		5	STEL/15min		Remar	ks / Observa	ations	
		mg/m3	ppm	r	ng/m3	ppm				
TLV	CZE	600	200,4		900	300,6				
AGW	DEU	600	200		600	200	SKIN			
MAK	DEU	600	200		600	200	SKIN			
VLA	ESP	600	200		900	300				
VLEP	FRA	600	200		900	300	SKIN			
TLV	GRC	600	200		900	300				
AK	HUN	600	200		900	300	SKIN			
GVI/KGVI	HRV	600	200		900	300				
VLEP	ITA	600	200		900	300		Allegato X	XXVIII D.Lgs	. 81/08
TGG	NLD	590		:	500		SKIN			
VLE	PRT	600	200		900	300				
NDS/NDSCh	POL	450		1	900		SKIN			
TLV	ROU	600	200	1	900	300				
ПДК	RUS	200			400			п		
MV	SVN	600	200		900	300	SKIN			
WEL	GBR	600	200		399	300	SKIN			
OEL	EU	600	200		900	300				
TLV-ACGIH		590	200		385	300				
redicted no-effe	ct concentr	ation - PNEC								
Normal value ir	n fresh water							55,8	mg/l	
Normal value ir	n marine wat	er						55,8	mg/l	
Normal value for	or fresh wate	r sediment						284,74	mg/kg	
Normal value o	f STP microo	organisms						709	mg/l	
Normal value for	or the food cl	nain (secondary)	poisoning)					100	mg/kg	
Normal value for	or the terrest	rial compartment	t e,					22,5	mg/kg	
lealth - Derived	no-effect lev	el - DNEL / DME	EL							
	Effe	ects on consumer	rs			Ef	fects on worke	ers		
Route of expos	ure Acu	te Acute	C	Chronic	Chronic	Ad	cute	Acute	Chronic	Chronic
	loca	al system	ic lo	ocal	systemic	lo	cal	systemic	local	systemic
Oral					31					
					mg/kg bw/	/d				
Inhalation					106					600
					mg/m3					mg/m3
Skin					412					1161
					mg/kg bw/	/d				mg/kg
					J. J. J.					bw/d



Revision nr.5 Dated 03/09/2024 Printed on 03/09/2024 Page n. 6 / 13 Replaced revision:4 (Dated 26/11/2019)

#### SECTION 8. Exposure controls/personal protection ... / >>

					ETHANOL				
Threshold Limit V	/alue								
Туре	Country	TWA/8h			STEL/15min		Remarks / Observation	ations	
		mg/m3	ppm		mg/m3	ppm			
TLV	CZE	1000			3000				
AGW	DEU	960	500		1920	1000			
MAK	DEU	960	500		1920	1000			
VLA	ESP				1910	1000			
VLEP	FRA	1900	1000		9500	5000			
TLV	GRC	1900	1000						
AK	HUN	1900			7600				
GVI/KGVI	HRV	1900	1000						
TGG	NLD	260			1900		SKIN		
NDS/NDSCh	POL	1900							
WEL	GBR	1920	1000						
TLV-ACGIH					1884	1000			
Predicted no-effe	ct concentra	ation - PNEC							
Normal value ir	n fresh water						0,96	mg/l	
Normal value ir	n marine wate	er					0,79	mg/l	
Normal value for	or fresh water	sediment					3,6	mg/kg	
Normal value for	or marine wat	er sediment					2,9	mg/kg	
Normal value for	or water, inter	mittent release					2,75	mg/l	
Normal value of	f STP microo	rganisms					580	mg/l	
Normal value for	or the terrestr	ial compartment					0,63	mg/kg/d	
Health - Derived r	no-effect leve	el - DNEL / DME	EL						
	Effe	cts on consumer	s			Effects	on workers		
Route of expos	ure Acut	te Acute		Chronic	Chronic	Acute	Acute	Chronic	Chronic
	loca	l system	ic	local	systemic	local	systemic	local	systemic
Inhalation	NPI	NPI		NPI	380	NPI	NPI	NPI	114
					mg/m3				mg/m3
Skin	NPI	NPI		NPI	NPI	NPI	NPI	NPI	NPI

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Protect your hands with gloves of the following type:

Material: Nitrile rubber (NBR) Thickness: 0,35 mm

Breakthrough time: 480 min

Material: Butyl rubber (IIR) Thickness: 0,5 mm Breakthrough time: 480 min

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion. EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

EN



Revision nr.5 Dated 03/09/2024 Printed on 03/09/2024 Page n. 7 / 13 Replaced revision:4 (Dated 26/11/2019)

#### SECTION 8. Exposure controls/personal protection ... / >>

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## **SECTION 9.** Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties Appearance	
Colour	
Odour	
Melting point / freezing point	
Initial boiling point	
Flammability	
Lower explosive limit	
Upper explosive limit	
Flash point	
Auto-ignition temperature	
Decomposition temperature	
рН	
Kinematic viscosity	
Solubility	
Partition coefficient: n-octanol/water	
Vapour pressure	

Density and/or relative density Relative vapour density Particle characteristics

liauid colourless characteristic of solvent -114,5 °C not determined not determined 2,5 % (v/v) 13,5 % (v/v) °C 23 not determined not determined not determined not determined soluble in organic solvents not applicable not available

Value

<

0,8 kg/l not determined not applicable Information

Substance:ETHANOL Reason for missing data:not determined

Substance:ETHANOL Substance:ETHANOL

Reason for missing data:not determined Reason for missing data:not determined Reason for missing data:not determined Reason for missing data:not determined

Substance:ETHANOL Vapour pressure: 45 mmHg

Reason for missing data:not determined

#### 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

 9.2.2. Other salety characteristics	
VOC (Directive 2004/42/EC) :	03 70 %

VOC (Directive 2004/42/EC) :	93,70 % -	749,60	g/litre
VOC (volatile carbon)	49,99 % -	399,90	g/litre

### **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ETHYL METHYL KETONE

Reacts with: light metals, strong oxidants. Attacks various types of plastic materials. Decomposes under the effect of heat. **10.2. Chemical stability** 

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

#### ETHYL METHYL KETONE

May form peroxides with: air,light,strong oxidising agents.Risk of explosion on contact with: hydrogen peroxide,nitric acid,sulphuric acid.May react dangerously with: oxidising agents,trichloromethane,alkalis.Forms explosive mixtures with: air.



#### SECTION 10. Stability and reactivity ... / >>

#### ETHANOL

Risk of explosion on contact with: alkaline metals,alkaline oxides,calcium hypochlorite,sulphur monofluoride,acetic anhydride,acids,concentrated hydrogen peroxide,perchlorates,perchloric acid,perchloronitrile,mercury nitrate,nitric acid,silver,silver nitrate,ammonia,silver oxide,ammonia,strong oxidising agents,nitrogen dioxide.May react dangerously with: bromoacetylene,chlorine acetylene,bromine trifluoride,chromium trioxide,chromyl chloride,fluorine,potassium tert-butoxide,lithium hydride,phosphorus trioxide,black platinum,zirconium (IV) chloride,zirconium (IV) iodide.Forms explosive mixtures with: air.

### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHYL METHYL KETONE

Avoid exposure to: sources of heat.

ETHANOL

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

ETHYL METHYL KETONE

Incompatible with: strong oxidants,inorganic acids,ammonia,copper,chloroform. **10.6. Hazardous decomposition products** 

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

3-AMINOPROPYLTRYETHOXYSILANE 3-AMINOPROPYLTRYETHOXYSILANE: LD50 (oral, rat): 3500 mg/kg LD50 (skin, rabbit): 4000 mg/kg.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

#### ACUTE TOXICITY

ATE (Inhalation) of the mixture: ATE (Oral) of the mixture: ATE (Dermal) of the mixture:

> ETHYL METHYL KETONE LD50 (Dermal): LD50 (Oral): LC50 (Inhalation vapours):

3-AMINOPROPYLTRYETHOXYSILANE ATE (Oral):

ETHANOL

Not classified (no significant component) >2000 mg/kg Not classified (no significant component)

6480 mg/kg Rabbit 2737 mg/kg Rat 23,5 mg/l/8h Rat

500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)



Revision nr.5 Dated 03/09/2024 Printed on 03/09/2024 Page n. 9 / 13 Replaced revision:4 (Dated 26/11/2019)

#### SECTION 11. Toxicological information ... / >>

LD50 (Oral): LC50 (Inhalation vapours): > 5000 mg/kg Rat 120 mg/l/4h Pimephales promelas

#### SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## **SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

#### 12.1. Toxicity

Information not available

#### 12.2. Persistence and degradability

ETHYL METHYL KETONE Solubility in water Rapidly degradable	> 10000 mg/l
ETHANOL Solubility in water Rapidly degradable	1000 - 10000 mg/l

#### 12.3. Bioaccumulative potential

EN

EPY 11.8.0 - SDS 1004.14



Revision nr.5 Dated 03/09/2024 Printed on 03/09/2024 Page n. 10 / 13 Replaced revision:4 (Dated 26/11/2019)

#### SECTION 12. Ecological information ... / >>

ETHYL METHYL KETONE Partition coefficient: n-octanol/water	0,3
ETHANOL Partition coefficient: n-octanol/water	-0,35

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

## **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## **SECTION 14. Transport information**

#### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1993


#### 14.2. UN proper shipping name

ADR / RID:	FLAMMABLE LIQUID, N.O.S. (ETHANOL)
IMDG:	FLAMMABLE LIQUID, N.O.S. (ETHANOL)
IATA:	FLAMMABLE LIQUID, N.O.S. (ETHANOL)

II

#### 14.3. Transport hazard class(es)

ADR / RID:	Class: 3	Label: 3
IMDG:	Class: 3	Label: 3
IATA:	Class: 3	Label: 3



ADR / RID, IMDG, IATA:



@EPY 11.8.0 - SDS 1004.14



Revision nr.5 Dated 03/09/2024 Printed on 03/09/2024 Page n. 11/13 Replaced revision:4 (Dated 26/11/2019)

#### SECTION 14. Transport information ... / >>

#### 14.5. Environmental hazards

ADR / RID:	NO
IMDG:	not marine pollutant
IATA:	NO

#### 14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 33	Limited Quantities: 1 It	Tunnel restriction code: (D/E)
	Special provision: 274,	601, 640C	
IMDG:	EMS: F-E, <u>S-E</u>	Limited Quantities: 1 It	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Passengers:	Maximum quantity: 5 L	Packaging instructions: 353
	Special provision:	A3	

#### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

## **SECTION 15. Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:	
---	--

P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

FIOUUCI	
Point	3 - 40
Contained substance	
Point	75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable

Substances in Candidate List (Art. 59 REACH) On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012: None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention: None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) : Binding primers.

#### 15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances ETHYL METHYL KETONE 3-AMINOPROPYLTRYETHOXYSILANE

### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B



Revision nr.5 Dated 03/09/2024 Printed on 03/09/2024 Page n. 12 / 13 Replaced revision:4 (Dated 26/11/2019)

#### SECTION 16. Other information ... / >>

Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)



#### SECTION 16. Other information ... / >>

- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP) 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- 20. Delegated Regulation (OE) 2024/197 (X/
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

## Changes to previous review:

The following sections were modified: 01 / 02 / 03 / 04 / 08 / 09 / 11 / 12 / 13 / 14 / 15 / 16.