

Printed on 03/10/2024
Page n. 1 / 15
Replaced revision:3 (Dated 02/03/2021)

(TV)

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 27W

Product name **GEL STRIPPER**

1.2. Relevant identified uses of the substance or mixture and uses advised against

ULTRA-ACTIVE UNIVERSAL PAINT STRIPPER.

1.3. Details of the supplier of the safety data sheet

NORD RESINE S.p.A. Name Full address Via Fornace Vecchia, 79 District and Country 31058 Susegana

Italia

Tel. +39 0438-437511 Fax +39 0438-435155

e-mail address of the competent person

responsible for the Safety Data Sheet annabreda@nordresine.com

NORD RESINE S.p.A. Supplier:

1.4. Emergency telephone number

For urgent inquiries refer to Ireland

National Poisons Information Centre

+353 018092166 +353 018092566

Malta

Malta Competition and Consumer Affairs Authority (MCCAA)

+356 2395 2000

Centre Antipoisons: +32 022649636

BfR Bundesinstitut für Risikobewertung: +49 30184120

Netherlands

National Poisons Information Center / University Medical Center Utrecht

+31 88 75 585 61

Croatia

Croatian Institute of Public Health, Division for Toxicology: +38514686910

Swedish Poisons Information Centre: +46104566750

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2020/878.

Hazard classification and indication:



Revision nr.4 Dated 03/10/2024 Printed on 03/10/2024 Page n. 2 / 15 Replaced revision:3 (Dated 02/03/2021)

SECTION 2. Hazards identification .../>>

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

EUH210 Safety data sheet available on request.
EUH208 Contains: (R)-P-MENTHA-1,8-DIENE

May produce an allergic reaction.

Precautionary statements:

Contains: BENZYL ALCOHOL

Product not intended for uses provided for by Directive 2004/42/EC.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

BENZYL ALCOHOL

INDEX 603-057-00-5 $5 \le x < 7$ Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Sens. 1B H317

EC 202-859-9 LD50 Oral: 1200 mg/kg

CAS 100-51-6

REACH Reg. 01-2119492630-38

PROPAN-2-OL

INDEX 603-117-00-0 1 ≤ x < 3 Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336

EC 200-661-7 CAS 67-63-0

REACH Reg. 01-2119457558-25

2-BUTOXYETHANOL

INDEX 603-014-00-0 $1 \le x < 3$ Acute Tox. 3 H331, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315

EC 203-905-0 LD50 Oral: 1300 mg/kg, LC50 Inhalation vapours: 3 mg/l/4h

CAS 111-76-2

REACH Reg. 01-2119475108-36

2-ETHYL-1-HEXANOL

INDEX $1 \le x < 3$ Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335

EC 203-234-3 ATE Inhalation vapours: 11 mg/l

CAS 104-76-7 REACH Reg. 01-2119487289-20

(R)-P-MENTHA-1,8-DIENE

INDEX 601-096-00-2 $0.1 \le x < 0.5$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Skin Sens. 1B H317,

Aquatic Acute 1 H400 M=1, Aquatic Chronic 3 H412

EC 227-813-5 CAS 5989-27-5

The full wording of hazard (H) phrases is given in section 16 of the sheet.



Revision nr.4 Dated 03/10/2024 Printed on 03/10/2024 Page n. 3 / 15 Replaced revision:3 (Dated 02/03/2021)

SECTION 4. First aid measures

4.1. Description of first aid measures

No effects requiring implementation of special first aid measures are expected. The following information represents practical indications of correct behaviour in the event of contact with a chemical product, even if not hazardous.

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice.

Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment: see section 4.1

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).



Revision nr.4 Dated 03/10/2024 Printed on 03/10/2024 Page n. 4 / 15 Replaced revision:3 (Dated 02/03/2021)

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81



POL

ROU

RUS

GBR

NORD RESINE S.p.A. 27W - GEL STRIPPER

Revision nr.4 Dated 03/10/2024 Printed on 03/10/2024 Page n. 5 / 15 Replaced revision:3 (Dated 02/03/2021)

SECTION 8. Exposure controls/personal protection

Polska

România

Россия

United Kingdom

NLD Nederland Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit

PRT Portugal Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os

agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os

riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające

rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych

dla zdrowia w środowisku pracy

Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru

modificarea și completarea hotărârii guvernului nr. 1.093/2006

ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ

НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК)

ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"

SVN Slovenija Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu

(Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)

EH40/2005 Workplace exposure limits (Fourth Edition 2020)

EU OEL EU Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU)

2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive

2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive

91/322/EEC.

TLV-ACGIH ACGIH 2023

(R)-P-MENTHA-1,8-DIENE									
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15mi	in	Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
AGW	DEU	28	5	112	20	SKIN			
MAK	DEU	28	5	112	20	SKIN			
VLA	ESP	168	30			SKIN			
MV	SVN	28	5	112	20	SKIN			



Revision nr.4 Dated 03/10/2024 Printed on 03/10/2024 Page n. 6/15 Replaced revision:3 (Dated 02/03/2021)

SECTION 8. Exposure controls/personal protection .../>>

				2-BUTOX	YETHANOL					
reshold Limit V										
Туре	Country	TWA/8h			EL/15min		Remar	ks / Observa	tions	
		mg/m3	ppm			opm				
TLV	CZE	100	20,4	20		10,8	SKIN			
AGW	DEU	49	10	98		20	SKIN			
MAK	DEU	49	10	98		20	SKIN	Hinweis		
VLA	ESP	98	20	24		50	SKIN			
VLEP	FRA	49	10	24	6	50	SKIN			
TLV	GRC	120	25							
AK	HUN	98	20	24	~	50	SKIN			
GVI/KGVI	HRV	98	20	24	~	50	SKIN			
VLEP	ITA	98	20	24		50	SKIN	Allegato XX	(XVIII D.Lgs.	81/08
TGG	NLD	100		24			SKIN			
VLE	PRT	98	20	24		50	SKIN			
NDS/NDSCh	POL	98		20			SKIN			
TLV	ROU	98	20	24	6	50	SKIN			
ПДК	RUS			10)			П		
MV	SVN	98	20	24	6	50	SKIN			
WEL	GBR	123	25	24	6	50	SKIN			
OEL	EU	98	20	24	6	50	SKIN			
TLV-ACGIH		97	20							
edicted no-effe	ct concentra	ation - PNEC								
Normal value in	fresh water							8,8	mg/l	
Normal value in	marine wate	er						0,88	mg/l	
Normal value for	or fresh water	r sediment						34,6	mg/kg/d	
Normal value for	or marine wa	ter sediment						3,46	mg/kg/d	
Normal value for	or marine wa	ter, intermitte	nt release					26,4	mg/l	
Normal value of	f STP microc	rganisms						463	mg/l	
Normal value for			ry poisoning)					20	mg/kg	
Normal value for								2,33	mg/kg/d	
alth - Derived r	no-effect lev	el - DNEL / D	MEL						0 0	
	Effe	cts on consur	ners			Effects of	on worke	rs		
Route of expos	ure Acu	te Acut	e	Chronic	Chronic	Acute		Acute	Chronic	Chronic
•	loca	l syst		ocal	systemic	local		systemic	local	systemic
Oral		26.7			6,3			,		,
		,	kg bw/d		mg/kg bw/d					
Inhalation	147			NPI	59	246		1091	NPI	98
	mg/				mg/m3	mg/m3		mg/m3		mg/m3
Skin	MEI			NPI	NPI	MED		NPI	NPI	LOW



Revision nr.4 Dated 03/10/2024 Printed on 03/10/2024 Page n. 7 / 15 Replaced revision:3 (Dated 02/03/2021)

SECTION 8. Exposure controls/personal protection .../>>

TLV CAGW EMAK EMAK EMAK EMAK EMAK EMAK EMAK EMAK	Country CZE DEU DEU POL RUS SVN concentrat	TWA/8h mg/m3 40 22 22 240 22	ppm 8,88 5 5		STEL/15min mg/m3 80 44 44	ppm 17,76 10	Remar SKIN SKIN	ks / Observa	itions	
Type (CA) TLV (CA) AGW [CA) MAK [CA) NDS/NDSCh [CA) ПДК [CA) MV (CA)	Country CZE DEU DEU POL RUS SVN concentrat	mg/m3 40 22 22 240	8,88 5 5		mg/m3 80 44	17,76 10	SKIN		itions	
TLV CAGW II MAK II NDS/NDSCh FI ПДК FI MV	CZE DEU DEU POL RUS SVN concentrat	mg/m3 40 22 22 240	8,88 5 5		mg/m3 80 44	17,76 10	SKIN		itions	
AGW I MAK I NDS/NDSCh F ПДК F MV S	DEU DEU POL RUS SVN concentrat	40 22 22 240 22	8,88 5 5		80 44	17,76 10		11		
AGW I MAK I NDS/NDSCh F ПДК F MV S	DEU DEU POL RUS SVN concentrat	22 22 240 22	5 5		44	10		11		
MAK II NDS/NDSCh F ПДК F MV S	DEU POL RUS SVN concentrat	22 240 22	5					11		
NDS/NDSCh F ПДК F MV S	POL RUS SVN concentrat	240			44	10	CIVINI			
ПДК F MV S	RUS SVN concentrat	22	-				SKIIN			
MV S	SVN concentrat		5							
*****	concentrat				5			П		
		ion - PNFC	Э		44	10	SKIN			
realctea no-effect (esh water									
Normal value in fre								1	mg/l	
Normal value in marine water								0,1	mg/l	
Normal value for fresh water sediment								5,27	mg/kg	
Normal value for marine water sediment								0,527	mg/kg	
Normal value for water, intermittent release								2,3	mg/l	
Normal value of S								39	mg/l	
Normal value for the			nt					0,45	mg/kg	
ealth - Derived no-								-,		
20		ts on consum				Effects	on worke	rs		
Route of exposure				Chronic	Chronic	Acute		Acute	Chronic	Chronic
rtoute of exposure	local	syste		local	systemic			systemic	local	systemic
Oral	10001	20	11110	local	4	10001		Systemio	10001	Systemio
Olai			g bw/d		mg/kg by	v/d				
Inhalation		111g/k(g bw/u		5,4	v/ u		110		22
IIIIaiauUII			.2		•					
Clein		mg/m 20	IJ		mg/m3 4			mg/m3 40		mg/m3 8
Skin			a buuld		· ·	u/d				-
		mg/K	g bw/d		mg/kg b	v/a		mg/kg bw/d		mg/kg bw/d

				PROPAN-2-OL				
Threshold Limit V	/alue			11(01)(112 02				
Type	Country	TWA/8h		STEL/15min		Remarks / Observa	ations	
7.	•	mg/m3	ppm	mg/m3	ppm			
TLV	CZE	500	200	1000	400			
AGW	DEU	500	200	1000	400			
MAK	DEU	500	200	1000	400			
VLA	ESP	500	200	1000	400			
VLEP	FRA			980	400			
TLV	GRC	980	400	1225	500			
AK	HUN	500	200	1000	400	SKIN		
GVI/KGVI	HRV	999	400	1250	500			
TGG	NLD	650						
NDS/NDSCh	POL	900		1200		SKIN		
TLV	ROU	200	81	500	203			
ПДК	RUS	10		50		П		
MV	SVN	500	200	1000	400			
WEL	GBR	999	400	1250	500			
TLV-ACGIH		492	200	983	400			
Predicted no-effe	ct concentra	ation - PNEC						
	Normal value in fresh water							
Normal value in						140,9	mg/l	
Normal value for						140,9	mg/l	
Normal value for			, , , , , , , , , , , , , , , , , , , ,			160	mg/kg	
Normal value for	or the terrestr	ial compartme	nt			28	mg/kg	



Revision nr.4 Dated 03/10/2024 Printed on 03/10/2024 Page n. 8 / 15 Replaced revision:3 (Dated 02/03/2021)

mg/kg

SECTION 8. Exposure controls/personal protection/>>

2-ETHYL-1-HEXANOL							
Predicted no-effect concentration - PNEC							
Normal value in fresh water	0,017	mg/l					
Normal value in marine water	0,0017	mg/l					
Normal value for fresh water sediment	0,28	mg/kg					
Normal value for marine water sediment	0,028	mg/kg					
Normal value of STP microorganisms	10	mg/l					
Normal value for the terrestrial compartment	0,047	mg/kg					
Normal value for the atmosphere	0,17	mg/l					

						- /	J.	
Health - Derived no-eff	ect level - D	NEL / DMEL						
	Effects on	consumers			Effects on w	orkers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral			VND	1,1 mg/kg				
Inhalation	53,2 mg/m3	VND	VND	2,3 mg/m3	106,4 mg/m3	VND	VND	53,2 mg/m3
Skin			VND	11,4			VND	23

mg/kg

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Protect your hands with gloves of the following type:

Material: Laminated film - LLDPE

Thickness: 0,06 mm Breakthrough time: 480 min

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Appearance Colour Odour	Value gelatinous liquid LIGHT YELLOW characteristic	Information
Melting point / freezing point Initial boiling point Flammability Lower explosive limit	not determined not determined not determined not determined	Reason for missing data:not determined Reason for missing data:not determined Reason for missing data:not determined





Dated 03/10/2024 Printed on 03/10/2024 Page n. 9 / 15 Replaced revision:3 (Dated 02/03/2021)

SECTION 9. Physical and chemical properties .../>>

Upper explosive limit

Flash point

Auto-ignition temperature Decomposition temperature

nН

Kinematic viscosity

Solubility

Partition coefficient: n-octanol/water

Vapour pressure

Density and/or relative density Relative vapour density Particle characteristics not determined

65 °C

not determined

8,5

not determined partially soluble

not applicable not determined

1,13 kg/l not determined not applicable Reason for missing data:not determined

Reason for missing data:not determined Reason for missing data:not determined

Reason for missing data:not determined

Reason for missing data:not determined

Reason for missing data not determined

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU)

13,94 % - 157,48

g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL

Decomposes under the effect of heat.

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F.Possibility of explosion.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

2-BUTOXYETHANOL

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

BENZÝL ALCOHOL

May react dangerously with: hydrobromic acid,iron,oxidising agents,sulphuric acid.Risk of explosion on contact with: phosphorus trichloride.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

2-BUTOXYETHANOL

Avoid exposure to: sources of heat,naked flames.

BENZYL ALCOHOL

Avoid exposure to: air, sources of heat, naked flames.

10.5. Incompatible materials

BENZYL ALCOHOL

Incompatible with: sulphuric acid,oxidising substances,aluminium.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

2-BUTOXYETHANOL

May develop: hydrogen.



Revision nr.4 Dated 03/10/2024 Printed on 03/10/2024 Page n. 10 / 15 Replaced revision:3 (Dated 02/03/2021)

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l
ATE (Oral) of the mixture: > 2000 mg/kg

ATE (Dermal) of the mixture: Not classified (no significant component)

2-BUTOXYETHANOL

LD50 (Dermal): > 2000 mg/kg Guinea pig
LD50 (Oral): 1300 mg/kg Guinea pig
LC50 (Inhalation vapours): 3 mg/l/4h Guinea pig

BENZYL ALCOHOL

 $\begin{array}{lll} \mbox{LD50 (Dermal):} & 2000 \mbox{ mg/kg Rabbit} \\ \mbox{LD50 (Oral):} & 1200 \mbox{ mg/kg} \\ \mbox{LC50 (Inhalation vapours):} & > 4,1 \mbox{ mg/l/4h Rat} \\ \end{array}$

PROPAN-2-OL

 LD50 (Dermal):
 12800 mg/kg Rat

 LD50 (Oral):
 4710 mg/kg Rat

 LC50 (Inhalation vapours):
 72,6 mg/l/4h Rat

2-ETHYL-1-HEXANOL

LD50 (Oral): 3730 mg/l Rat LC50 (Inhalation vapours): 5,3 mg/l Rat

ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

2-BUTOXYETHANOL Species: rabbit Result: irritating Method: EU Method B.4

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class





Revision nr.4 Dated 03/10/2024 Printed on 03/10/2024 Page n. 11 / 15 Replaced revision:3 (Dated 02/03/2021)

SECTION 11. Toxicological information .../>>

2-BUTOXYETHANOL Species: rabbit Result: irritating Method: OECD 405

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

(R)-P-MENTHA-1,8-DIENE

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

(R)-P-MENTHA-1,8-DIENE

LC50 - for Fish 35 mg/l/96h Oncorhynchus mykiss EC50 - for Crustacea 69,6 mg/l/48h Daphnia pulex

2-BUTOXYETHANOL

EC10 for Algae / Aquatic Plants 370 mg/l/72h

BENZYL ALCOHOL

LC50 - for Fish 10 mg/l/96h Bluegill

2-ETHYL-1-HEXANOL

LC50 - for Fish 17,1 mg/l/96h Leuciscus idus melanotus

EC50 - for Crustacea 39 mg/l/48h Daphnia magna

12.2. Persistence and degradability

(R)-P-MENTHA-1,8-DIENE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable





Revision nr.4 Dated 03/10/2024 Printed on 03/10/2024 Page n. 12 / 15 Replaced revision:3 (Dated 02/03/2021)

SECTION 12. Ecological information .../>>

2-BUTOXYETHANOL

Solubility in water 900000 mg/l

Rapidly degradable

BENZYL ALCOHOL Rapidly degradable

PROPAN-2-OL Rapidly degradable

2-ETHYL-1-HEXANOL Rapidly degradable

12.3. Bioaccumulative potential

(R)-P-MENTHA-1,8-DIENE

Partition coefficient: n-octanol/water 4,38 BCF 1022

2-BUTOXYETHANOL

Partition coefficient: n-octanol/water 0,81

BENZYL ALCOHOL

Partition coefficient: n-octanol/water 1,1

PROPAN-2-OL

Partition coefficient: n-octanol/water 0,05

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable



Revision nr.4 Dated 03/10/2024 Printed on 03/10/2024 Page n. 13 / 15 Replaced revision:3 (Dated 02/03/2021)

SECTION 14. Transport information	/>>
--	-----

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 4

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances BENZYL ALCOHOL 2-ETHYL-1-HEXANOL



Revision nr.4 Dated 03/10/2024 Printed on 03/10/2024 Page n. 14 / 15 Replaced revision:3 (Dated 02/03/2021)

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2
Flammable liquid, category 2
Flam. Liq. 3
Acute Tox. 3
Acute toxicity, category 3
Acute Tox. 4
Asp. Tox. 1
Eye Irrit. 2
Skin Irrit. 2
Flammable liquid, category 3
Acute toxicity, category 3
Acute toxicity, category 4
Asp. Tox. 1
Eye irritation, category 2
Skin Irrit. 2
Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Skin Sens. 1B Skin sensitization, category 1B

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H225 Highly flammable liquid and vapour. **H226** Flammable liquid and vapour.

H331 Toxic if inhaled.
H302 Harmful if swallowed.
H332 Harmful if inhaled.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H335 May cause respiratory irritation.
 H317 May cause an allergic skin reaction.
 H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

EUH210 Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament



Revision nr.4 Dated 03/10/2024 Printed on 03/10/2024 Page n. 15 / 15 Replaced revision:3 (Dated 02/03/2021)

SECTION 16. Other information .../>>

- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 03 / 04 / 08 / 09 / 11 / 12 / 13 / 15 / 16.