

## Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: **30F**  
Product name: **EPOXY-LINER PR (B)**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **FUEL-RESISTANT COATING**

#### 1.3. Details of the supplier of the safety data sheet

Name: **NORD RESINE S.p.A.**  
Full address: **Via Fornace Vecchia, 79**  
District and Country: **31058 Susegana (TV) Italia**  
Tel.: **+39 0438-437511**  
Fax: **+39 0438-435155**e-mail address of the competent person responsible for the Safety Data Sheet: **annabreda@nordresine.com**Supplier: **NORD RESINE S.p.A.**

#### 1.4. Emergency telephone number

For urgent inquiries refer to: **+39 0438 437511**

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Reproductive toxicity, category 1B	H360F	May damage fertility.
Acute toxicity, category 4	H302	Harmful if swallowed.
Acute toxicity, category 4	H332	Harmful if inhaled.
Skin corrosion, category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

Signal words: **Danger**Hazard statements:  
**H360F** May damage fertility.

### SECTION 2. Hazards identification ... / >>

**H302+H332** Harmful if swallowed or if inhaled.  
**H314** Causes severe skin burns and eye damage.  
**H317** May cause an allergic skin reaction.  
**H412** Harmful to aquatic life with long lasting effects.  
**EUH071** Corrosive to the respiratory tract.  
 Restricted to professional users.

**Precautionary statements:**

**P260** Do not breathe dust / fume / gas / mist / vapours / spray.  
**P201** Obtain special instructions before use.  
**P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
**P303+P361+P353** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
**P280** Wear protective gloves/ protective clothing / eye protection / face protection.  
**P310** Immediately call a POISON CENTER / doctor.

**Contains:** 4,4'-ISOPROPYLIDENEDIPHENOL  
 M-PHENYLENEBIS (METHYLAMINE)  
 PHENOL,4,4'- (1-METHYLETHYLIDENE) BISPOLYMER WITH 1,3-BENZENEDIMETHANAMINE AND  
 FORMALDEHYDE  
 BENZYL ALCOHOL

VOC (Directive 2004/42/EC) :

Two - pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition :	319,13
Limit value:	500,00
- Catalysed with :	55,56 % EPOXY-LINER PR (A)

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product contains substances with endocrine disrupting properties in concentration  $\geq$  0.1%.  
 4,4'-ISOPROPYLIDENEDIPHENOL

## SECTION 3. Composition/information on ingredients

### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>BENZYL ALCOHOL</b>		
CAS	100-51-6	35 $\leq$ x < 50
EC	202-859-9	<b>Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319</b>
INDEX	603-057-00-5	<b>LD50 Oral: 1620 mg/kg, STA Inhalation vapours: 11 mg/l</b>
REACH Reg.	01-2119492630-38	
<b>M-PHENYLENEBIS (METHYLAMINE)</b>		
CAS	1477-55-0	25 $\leq$ x < 35
EC	216-032-5	<b>Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1B H317, Aquatic Chronic 3 H412, EUH071</b>
INDEX		<b>STA Oral: 500 mg/kg, STA Inhalation vapours: 11 mg/l</b>
REACH Reg.	01-2119480150-50	
<b>PHENOL,4,4'- (1-METHYLETHYLIDENE) BISPOLYMER WITH 1,3-BENZENEDIMETHANAMINE AND FORMALDEHYDE</b>		
CAS	161278-17-7	19 $\leq$ x < 25
EC	500-607-5	<b>Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Chronic 4 H413</b>
INDEX		<b>STA Oral: 500 mg/kg, STA Dermal: 1100 mg/kg</b>
<b>4,4'-ISOPROPYLIDENEDIPHENOL</b>		
CAS	80-05-7	4 $\leq$ x < 8
EC	201-245-8	<b>Repr. 1B H360F, Eye Dam. 1 H318, STOT SE 3 H335, Skin Sens. 1 H317, Aquatic Chronic 2 H411</b>
INDEX	604-030-00-0	
REACH Reg.	01-2119457856-23	

### SECTION 3. Composition/information on ingredients ... / >>

#### 3-(DIETHYLAMINO)-1,2-PROPANEDIOL

CAS 621-56-7 4 ≤ x < 8 Eye Irrit. 2 H319, Skin Irrit. 2 H315  
EC 210-032-5  
INDEX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### SECTION 4. First aid measures

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

### SECTION 5. Firefighting measures

#### 5.1. Extinguishing media

##### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

##### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

##### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

#### 5.3. Advice for firefighters

##### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

##### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### SECTION 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

### SECTION 6. Accidental release measures ... / >>

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

### SECTION 7. Handling and storage

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

### SECTION 8. Exposure controls/personal protection

#### 8.1. Control parameters

Regulatory References:

CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

### SECTION 8. Exposure controls/personal protection ... / >>

#### BENZYL ALCOHOL

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	CZE	40	8,88	80	17,76		
AGW	DEU	22	5	44	10	SKIN	11
NDS/NDSch	POL	240					
MV	SVN	22	5	44	10	SKIN	

#### M-PHENYLENEBIS (METHYLAMINE)

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
VLEP	FRA			0,1			
MV	SVN	0,1					
TLV-ACGIH				0,018 (C)		SKIN	

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	0,094	mg/l
Normal value in marine water	0,009	mg/l
Normal value for fresh water sediment	0,43	mg/kg
Normal value for marine water sediment	0,043	mg/kg
Normal value for water, intermittent release	0,152	mg/l

#### 4,4'-ISOPROPYLIDENEDIPHENOL

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	CZE	2		5		INHAL	
AGW	DEU	5		5 (C)		INHAL	
VLEP	FRA	2					
AK	HUN	2					
GVI/KGVI	HRV	2				INHAL	
VLEP	ITA	2				INHAL	
VLEP	ITA	2				SKIN	
TGG	NLD	2				INHAL	
VLE	PRT	2				INHAL	
NDS/NDSch	POL	2				INHAL	
TLV	ROU	2				INHAL	
MV	SVN	2		2		INHAL	
WEL	GBR	2					
OEL	EU	2				INHAL	

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	0,018	mg/l
Normal value in marine water	0,018	mg/l
Normal value for fresh water sediment	1,2	mg/kg
Normal value for marine water sediment	0,24	mg/kg
Normal value for water, intermittent release	0,011	mg/l
Normal value of STP microorganisms	320	mg/l
Normal value for the terrestrial compartment	3,7	mg/kg

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		0,004 mg/kg bw/d		0,004 mg/kg bw/d				
Inhalation	1 mg/m3	1 mg/m3	1 mg/m3	1 mg/m3	2 mg/m3	2 mg/m3	2 mg/m3	2 mg/m3
Skin					0,019 mg/kg bw/d	0,031 mg/kg bw/d	0,019 mg/kg bw/d	0,031 mg/kg bw/d

##### Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.  
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

### 8.2. Exposure controls

### SECTION 8. Exposure controls/personal protection ... / >>

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

### SECTION 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	yellow	
Odour	amino	
Melting point / freezing point	Not available	
Initial boiling point	> 200 °C	
Flammability	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Flash point	> 100 °C	
Auto-ignition temperature	Not available	
pH	12	
Kinematic viscosity	Not available	
Solubility	soluble in organic solvents	
Partition coefficient: n-octanol/water	Not available	
Vapour pressure	Not available	
Density and/or relative density	1,09 kg/l	
Relative vapour density	Not available	
Particle characteristics	Not applicable	

#### 9.2. Other information

##### 9.2.1. Information with regard to physical hazard classes

Information not available

##### 9.2.2. Other safety characteristics

Total solids (250°C / 482°F)	0 %	
VOC (Directive 2004/42/EC) :	43,50 % - 474,15	g/litre

### SECTION 9. Physical and chemical properties ... / >>

VOC (volatile carbon) 32,45 % - 353,70 g/litre

### SECTION 10. Stability and reactivity

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

##### BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F.Possibility of explosion.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

##### BENZYL ALCOHOL

May react dangerously with: hydrobromic acid,iron,oxidising agents,sulphuric acid.Risk of explosion on contact with: phosphorus trichloride.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

##### BENZYL ALCOHOL

Avoid exposure to: air,sources of heat,naked flames.

#### 10.5. Incompatible materials

##### BENZYL ALCOHOL

Incompatible with: sulphuric acid,oxidising substances,aluminium.

#### 10.6. Hazardous decomposition products

Information not available

### SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

##### Information on likely routes of exposure

Information not available

##### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

##### Interactive effects

Information not available

##### ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	12,94 mg/l
ATE (Oral) of the mixture:	662,85 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

Corrosive to the respiratory tract.

**SECTION 11. Toxicological information ... / >>**

BENZYL ALCOHOL  
LD50 (Dermal): 2000 mg/kg Rabbit  
LD50 (Oral): 1620 mg/kg Rat  
LC50 (Inhalation vapours): > 4,1 mg/l/4h Rat  
STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

M-PHENYLENEBIS (METHYLAMINE)  
LD50 (Dermal): 3100 mg/kg Rat  
LD50 (Oral): > 200 mg/kg Rat - Sprague-Dawley  
STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)  
LC50 (Inhalation vapours): 1,34 mg/l Rat - Wistar  
STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

PHENOL,4,4'- (1-METHYLETHYLIDENE) BISPOLYMER WITH 1,3-BENZENEDIMETHANAMINE AND FORMALDEHYDE  
STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)  
STA (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

4,4'-ISOPROPYLIDENEDIPHENOL  
LD50 (Dermal): 3000 mg/kg Rabbit  
LD50 (Oral): 4100 mg/kg Rat

SKIN CORROSION / IRRITATION

Corrosive for the skin  
Classification according to the experimental Ph value

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

May damage fertility

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation



**SECTION 11. Toxicological information** ... / >>

Information not available

**STOT - SINGLE EXPOSURE**

Does not meet the classification criteria for this hazard class

**Target organs**

Information not available

**Route of exposure**

Information not available

**STOT - REPEATED EXPOSURE**

Does not meet the classification criteria for this hazard class

**Target organs**

Information not available

**Route of exposure**

Information not available

**ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class

**11.2. Information on other hazards**

Based on the available data, the product contains the following endocrine disruptors in concentrations of 0.1% or greater by weight that may have endocrine disrupting effects on humans and cause adverse effects on the exposed individual or his or her progeny:

4,4'-ISOPROPYLIDENEDIPHENOL

**SECTION 12. Ecological information**

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

**12.1. Toxicity****M-PHENYLENEBIS (METHYLAMINE)**

LC50 - for Fish	87,6 mg/l/96h <i>Oryzias latipes</i>
EC50 - for Crustacea	15,2 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	20,3 mg/l/72h <i>Pseudokirchnerella subcapitata</i>

**BENZYL ALCOHOL**

LC50 - for Fish	10 mg/l/96h Bluegill
-----------------	----------------------

**4,4'-ISOPROPYLIDENEDIPHENOL**

LC50 - for Fish	9,4 mg/l/96h <i>Menidia menidia</i>
EC50 - for Crustacea	10,2 mg/l/48h <i>Daphnia magna</i>

**12.2. Persistence and degradability****M-PHENYLENEBIS (METHYLAMINE)**

Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

**BENZYL ALCOHOL**

Rapidly degradable

**12.3. Bioaccumulative potential**

**SECTION 12. Ecological information** ... / >>

M-PHENYLENEBIS (METHYLAMINE) Partition coefficient: n-octanol/water	0,18
BENZYL ALCOHOL Partition coefficient: n-octanol/water	1,1

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.**12.6. Endocrine disrupting properties**

Based on the available data, the product contains the following endocrine disruptors in concentrations of 0.1% or greater by weight that may have endocrine disrupting effects on the environment and on animal species causing adverse effects on the exposed organisms or on their progeny:

4,4'-ISOPROPYLIDENEDIPHENOL

**12.7. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information****14.1. UN number or ID number**

ADR / RID, IMDG, IATA: 2735

**14.2. UN proper shipping name**

ADR / RID:	AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS (METHYLAMINE) ; PHENOL,4,4'- (1-METHYLETHYLIDENE) BISPOLYMER WITH 1,3-BENZENEDIMETHANAMINE AND FORMALDEHYDE)
IMDG:	AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS (METHYLAMINE) ; PHENOL,4,4'- (1-METHYLETHYLIDENE) BISPOLYMER WITH 1,3-BENZENEDIMETHANAMINE AND FORMALDEHYDE)
IATA:	AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS (METHYLAMINE) ; PHENOL,4,4'- (1-METHYLETHYLIDENE) BISPOLYMER WITH 1,3-BENZENEDIMETHANAMINE AND FORMALDEHYDE)



**SECTION 15. Regulatory information** ... / >>

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Two - pack performance coatings.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Repr. 1B</b>	Reproductive toxicity, category 1B
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Skin Corr. 1B</b>	Skin corrosion, category 1B
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H360F</b>	May damage fertility.
<b>H302+H332</b>	Harmful if swallowed or if inhaled.
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H318</b>	Causes serious eye damage.
<b>H335</b>	May cause respiratory irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH071</b>	Corrosive to the respiratory tract.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation

**SECTION 16. Other information** ... / >>

- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

**Changes to previous review:**

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 11 / 12 / 15 / 16.