

# NORD RESINE S.p.A.

**40K - EPOSEAL W TERGE EXTRA** 

Revision nr.3 Dated 08/04/2021 Printed on 08/04/2021 Page n. 1 / 12 Replaced revision:2 (Dated 09/01/2018)

# **Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 40K

Product name EPOSEAL W TERGE EXTRA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use LAYING AUXILIARY AGENT-DETERGENT FOR EPOSEAL W.

1.3. Details of the supplier of the safety data sheet

Name NORD RESINE S.p.A.
Full address Via Fornace Vecchia, 79

District and Country 31058 Susegana (TV)

Italia

Tel. +39 0438-437511 Fax +39 0438-435155

e-mail address of the competent person

responsible for the Safety Data Sheet annabreda@nordresine.com

Product distribution by: NORD RESINE S.p.A.

1.4. Emergency telephone number

For urgent inquiries refer to +39 0438 437511

#### **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Serious eye damage, category 1 H318 Causes serious eye damage.

Hazardous to the aquatic environment, chronic H412 Harmful to aquatic life with long lasting effects.

toxicity, category 3

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H318 Causes serious eye damage.

**H412** Harmful to aquatic life with long lasting effects.

Precautionary statements:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.





Dated 08/04/2021 Printed on 08/04/2021 Page n. 2 / 12 Replaced revision:2 (Dated 09/01/2018)

SECTION 2. Hazards identification .../>>

P280 Wear eye protection / face protection.

P310 Immediately call a POISON CENTER / doctor.

**P273** Avoid release to the environment.

Contains: COCONUT DIETHANOLAMIDE

2-PROPYLHEPTANOL ETHOXYLATE

Product not intended for uses provided for by Dir. 2004/42/CE.

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

#### **SECTION 3. Composition/information on ingredients**

#### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

**DIPROPYLENE GLYCOL MONOMETHYL ETHER** 

01-2119490100-53

CAS  $34590-94-8 \quad 30 \le x < 50$  Substance with a community workplace exposure limit.

EC 252-104-2

INDEX

Reg. no. 01-2119450011-60

BENZYL ALCOHOL

CAS 100-51-6  $10 \le x < 20$  Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319 EC 202-859-9

INDEX 603-057-00-5 Reg. no. 01-2119492630-38 COCONUT DIETHANOLAMIDE

CAS 68603-42-9 5 ≤ x < 9 Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 2 H411

EC 931-329-6

INDEX Reg. no.

CAS  $160875-66-1 \ 3 \le x < 5$  Acute Tox. 4 H302, Eye Dam. 1 H318

INDEX

ETHYL ACETATE

CAS 141-78-6 0 ≤ x < 1 Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 205-500-4 INDEX 607-022-00-5 Reg. no. 01-2119475103-46

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available



Revision nr.3 Dated 08/04/2021 Printed on 08/04/2021 Page n. 3 / 12 Replaced revision:2 (Dated 09/01/2018)

### **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

#### 5.3. Advice for firefighters

#### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### SECTION 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

#### **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available



Revision nr.3 Dated 08/04/2021 Printed on 08/04/2021 Page n. 4 / 12 Replaced revision:2 (Dated 09/01/2018)

## **SECTION 8. Exposure controls/personal protection**

#### 8.1. Control parameters

Regulatory References:

CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
HUN	Magyarország	A pénzügyminiszter 7/2018. (VIII. 29.) PM rendelete a munkahelyek kémiai biztonságáról szóló 25/2000. (IX. 30.) EüM–SZCSM egyű, TTes rendelet módosításáról.
HRV	Hrvatska	Pravilnik o zaštití radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/18)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018,
		2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
SVN	Slovenija	Uradni list Republike Slovenije 20.12.2019 - Uradnem listu RS št. 78/19 -PRAVILNIK o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2020



Revision nr.3 Dated 08/04/2021 Printed on 08/04/2021 Page n. 5 / 12 Replaced revision:2 (Dated 09/01/2018)

SECTION 8. Exposure controls/personal protection .../>>

	/- I		DIPROPY	LENE GLYC	JE MONOME	IHYLEIHER			
hreshold Limit \		TIA/A/C:		OTEL **-		<b>.</b> , ,			
Туре	•		STEL/15min		Remarks /	Observations			
TIM	CZE	mg/m3	ppm	mg/m3	ppm	CIZINI			
TLV		270	43,74	550	89,1	SKIN			
AGW	DEU	310	50	310	50				
MAK	DEU	310	50	310	50	OLCINI			
VLA	ESP	308	50			SKIN			
VLEP	FRA	308	50	000	450	SKIN			
TLV	GRC	600	100	900	150				
AK	HUN	308				OLCINI			
GVI/KGVI	HRV	308	50			SKIN			
VLEP	ITA	308	50			SKIN			
TGG	NLD	300				OLCINI			
VLE	PRT	308	50			SKIN			
NDS/NDSCh	POL	240		480		SKIN			
TLV	ROU	308	50			SKIN			
MV	SVN	308	50			SKIN			
WEL	GBR	308	50			SKIN			
OEL	EU	308	50			SKIN			
TLV-ACGIH		606	100	909	150	SKIN			
redicted no-effe		ation - PNE	С						
Normal value in							19	mg/l	
Normal value in							1,9	mg/l	
Normal value for							70,2	mg/kg	
Normal value for			-				7,02	mg/kg	
Normal value for			ase				190	mg/l	
Normal value o							4168	mg/l	
Normal value for		•					2,74	mg/kg	
ealth - Derived r									
		cts on cons				Effects on we			
Route of expos			ute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	loca	ıl sys	stemic	local	systemic	local	systemic	local	systemic
Oral					1,67 mg/kg/d				
Inhalation					37,2 mg/m3				310 mg/m3
Skin					15 mg/kg/d				65 mg/kg/d

BENZYL ALCOHOL											
Threshold Limit Value											
Туре	Country	TWA/8h		STEL/15i	STEL/15min		Observations				
		mg/m3	ppm	mg/m3	ppm						
TLV	CZE	40	8,88	80	17,76						
AGW	DEU	22	5	44	10	SKIN	11				
NDS/NDSCh	POL	240									
MV	SVN	22	5	44	10	SKIN					

			COCONUT	DIETHANOLAMI	DE			
Predicted no-effect cor	ncentration	- PNEC						
Normal value in fresh	n water					7	mg/l	
Normal value in mari				0,7	mg/l			
Normal value of STP				830	mg/l			
Health - Derived no-eff	ect level - D	NEL / DMEL					_	
	Effects of	n consumers			Effects on workers			
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				6,25				
				mg/kg bw/d				
Inhalation				21,73		73,4		
				mg/m3		mg/m3		
Skin			0,056	2,5			0,09	4,16
			mg/cm2	mg/kg bw/d			mg/cm2	mg/kg
								bw/d



Dated 08/04/2021 Printed on 08/04/2021 Page n. 6 / 12 Replaced revision:2 (Dated 09/01/2018)

SECTION 8. Exposure controls/personal protection .../>

				ETHYL	ACETATE			
Threshold Limit V	alue							
Туре	Country	TWA/8h		STEL/15min		Remarks / Observation	S	
		mg/m3	ppm	mg/m3	ppm			
TLV	CZE	700	191,1	900	245,7			
AGW	DEU	730	200	1460	400			
MAK	DEU	750	200	1500	400			
VLA	ESP	734	200	1468	400			
VLEP	FRA	734	200	1468	400			
TLV	GRC	734	200	1468	400			
AK	HUN	734		1468				
GVI/KGVI	HRV	734	200	1468	400			
TGG	NLD	734		1468				
VLE	PRT	734	200	1468	400			
NDS/NDSCh	POL	734		1468				
TLV	ROU	400	111	500	139			
MV	SVN	734	200	1468	400			
WEL	GBR	734	200	1468	400			
OEL	EU	734	200	1468	400			
TLV-ACGIH		1441	400					
Predicted no-effect	ct concentra	ation - PNEC						
Normal value in	fresh water					0,26	mg/l	
Normal value in	marine water	er				0,026	mg/l	
Normal value fo	r fresh water	sediment	1,25	mg/kg				
Normal value fo	r marine wat	er sediment	0,125	mg/kg				
Normal value fo	r water, inter	mittent relea	1,65	mg/l				
Normal value of			650	mg/l				
Normal value fo	r the food ch	ain (seconda	200	mg/kg				
Normal value fo	r the terrestr	ial compartm	0,24	mg/kg				

#### Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction. VND = hazard identified but no DNEL/PNEC available; NEA = no exposure expected; NPI = no hazard identified.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.





Revision nr.3 Dated 08/04/2021 Printed on 08/04/2021 Page n. 7 / 12 Replaced revision:2 (Dated 09/01/2018)

### **SECTION 9. Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

PropertiesValueInformationAppearanceliquidColourLIGHT YELLOW

Odour characteristic Odour threshold Not available Not available Melting point / freezing point Not available Initial boiling point Not available Not available Boiling range Flash point 61 Not available **Evaporation Rate** Flammability of solids and gases Not available Not available Lower inflammability limit Upper inflammability limit Not available Not available Lower explosive limit Upper explosive limit Not available Vapour pressure Not available Vapour density Not available 0,985 kg/l Relative density Solubility CAN BE DILUTED Partition coefficient: n-octanol/water Not available

Auto-ignition temperature

Decomposition temperature

Viscosity

Not available

Not available

Not available

Explosive properties

Oxidising properties

Not available

Not available

9.2. Other information

VOC (Directive 2010/75/EC): 65,53 % - 645,45 g/litre

#### **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Forms peroxides with: air.

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F.Possibility of explosion.

ETHYL ACETATE

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

May react violently with: strong oxidising agents.

BENZYL ALCOHOL

May react dangerously with: hydrobromic acid,iron,oxidising agents,sulphuric acid.Risk of explosion on contact with: phosphorus trichloride.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals,hydrides,oleum.May react violently with: fluorine,strong oxidising agents,chlorosulphuric acid,potassium tert-butoxide.Forms explosive mixtures with: air.

### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.





# NORD RESINE S.p.A.

40K - EPOSEAL W TERGE EXTRA

Pated 08/04/2021 Printed on 08/04/2021 Page n. 8 / 12 Replaced revision:2 (Dated 09/01/2018)

#### SECTION 10. Stability and reactivity .../>>

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Avoid exposure to: sources of heat. Possibility of explosion.

BENZYL ALCOHOL

Avoid exposure to: air, sources of heat, naked flames.

ETHYL ACETATE

Avoid exposure to: light, sources of heat, naked flames.

#### 10.5. Incompatible materials

BENZYL ALCOHOL

Incompatible with: sulphuric acid,oxidising substances,aluminium.

**ETHYL ACETATE** 

Incompatible with: acids,bases,strong oxidants,aluminium,nitrates,chlorosulphuric acid.Incompatible materials: plastic materials.

#### 10.6. Hazardous decomposition products

Information not available

### **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: > 20 mg/l
ATE (Oral) of the mixture: >2000 mg/kg

ATE (Dermal) of the mixture: Not classified (no significant component)

BENZYL ALCOHOL

 LD50 (Oral)
 1620 mg/kg Rat

 LD50 (Dermal)
 2000 mg/kg Rabbit

 LC50 (Inhalation)
 > 4,1 mg/l/4h Rat

#### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class



Revision nr.3 Dated 08/04/2021 Printed on 08/04/2021 Page n. 9 / 12 Replaced revision:2 (Dated 09/01/2018) ΕN

### SECTION 11. Toxicological information .../>>

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

#### **SECTION 12. Ecological information**

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

#### 12.1. Toxicity

BENZYL ALCOHOL

LC50 - for Fish 10 mg/l/96h Bluegill

2-PROPYLHEPTANOL ETHOXYLATE

EC50 - for Crustacea > 10 mg/l/48h Daphnia Magna

EC50 - for Algae / Aquatic Plants > 10 mg/l/72h Scenedesmus subspicatus

#### 12.2. Persistence and degradability

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Solubility in water 1000 - 10000 mg/l Rapidly degradable

BENZYL ALCOHOL Rapidly degradable

ETHYL ACETATE

Solubility in water > 10000 mg/l

Rapidly degradable

#### 12.3. Bioaccumulative potential

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Partition coefficient: n-octanol/water 0,0043

BENZYL ALCOHOL

Partition coefficient: n-octanol/water 1,1

ETHYL ACETATE

Partition coefficient: n-octanol/water 0,68 BCF 30

### 12.4. Mobility in soil

Information not available

## 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.





Revision nr.3 Dated 08/04/2021 Printed on 08/04/2021 Page n. 10 / 12 Replaced revision:2 (Dated 09/01/2018)

#### SECTION 12. Ecological information .../>>

#### 12.6. Other adverse effects

Information not available

### **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

**CONTAMINATED PACKAGING** 

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

#### **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 14.1. UN number

Not applicable

#### 14.2. UN proper shipping name

Not applicable

#### 14.3. Transport hazard class(es)

Not applicable

#### 14.4. Packing group

Not applicable

#### 14.5. Environmental hazards

Not applicable

#### 14.6. Special precautions for user

Not applicable

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

#### **SECTION 15. Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

3 - 40





# NORD RESINE S.p.A.

## **40K - EPOSEAL W TERGE EXTRA**

Revision In.3 Dated 08/04/2021 Printed on 08/04/2021 Page n. 11 / 12 Replaced revision:2 (Dated 09/01/2018)

#### SECTION 15. Regulatory information ..../>>

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

#### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2
Acute Tox. 4 Acute toxicity, category 4
Eye Dam. 1 Serious eye damage, category 1
Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

**H225** Highly flammable liquid and vapour.

H302 Harmful if swallowed.
H332 Harmful if inhaled.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

**EUH066** Repeated exposure may cause skin dryness or cracking.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit



Revision nr.3 Dated 08/04/2021 Printed on 08/04/2021 Page n. 12 / 12 Replaced revision:2 (Dated 09/01/2018)

#### SECTION 16. Other information .../>>

- TWA: Time-weighted average exposure limit- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

#### Changes to previous review:

The following sections were modified:

02/03/04/05/07/08/09/10/11/12/14/15/16.