

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 478
Product name: ESC FONDO (B)
UFI : 9480-E086-X00Y-WAA6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: CONDUCTIVE EPOXY BASE COAT

1.3. Details of the supplier of the safety data sheet

Name: NORD RESINE S.p.A.
Full address: Via Fornace Vecchia, 79
District and Country: 31058 Susegana (TV)
Italy
Tel.: +39 0438-437511
Fax: +39 0438-435155
e-mail address of the competent person responsible for the Safety Data Sheet: annabreda@nordresine.com
Supplier: NORD RESINE S.p.A.

1.4. Emergency telephone number

For urgent inquiries refer to

Ireland
National Poisons Information Centre
+353 018092166
+353 018092566

Malta
Malta Competition and Consumer Affairs Authority (MCCAA)
+356 2395 2000

Belgium
Centre Antipoisons: +32 022649636

Germany
BfR Bundesinstitut für Risikobewertung: +49 30184120

Netherlands
National Poisons Information Center / University Medical Center Utrecht
+31 88 75 585 61

Croatia
Croatian Institute of Public Health, Division for Toxicology: +38514686910

Sveden
Swedish Poisons Information Centre: +46104566750

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

SECTION 2. Hazards identification ... / >>

Hazard classification and indication:

Reproductive toxicity, category 2	H361d	Suspected of damaging the unborn child.
Acute toxicity, category 4	H302	Harmful if swallowed.
Skin corrosion, category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

H361d	Suspected of damaging the unborn child.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
EUH071	Corrosive to the respiratory tract.

Precautionary statements:

P260	Do not breathe dust / fume / gas / mist / vapours / spray.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P310	Immediately call a POISON CENTER / doctor.
P264	Wash thoroughly with water and soap after handling.

Contains: salicylic acid
Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-,reaction products with bisphenol A diglycidyl ether homopolymer
M-PHENYLENEBIS (METHYLAMINE)
3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE
BENZYL ALCOHOL

VOC (Directive 2004/42/EC) :

Two-pack reactive performance coatings for specific end use such as floors.

VOC given in g/litre of product in a ready-to-use condition :	135,35
Limit value:	500,00
- Catalysed with :	350,00 % ESC FONDO (A)

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product contains substances with endocrine disrupting properties in concentration \geq 0,1%:

salicylic acid

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
BENZYL ALCOHOL		
INDEX 603-057-00-5	35 ≤ x < 50	Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Sens. 1B H317
EC 202-859-9		LD50 Oral: 1200 mg/kg
CAS 100-51-6		
REACH Reg. 01-2119492630-38		
Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-,reaction products with bisphenol A diglycidyl ether homopolymer		
INDEX 25 ≤ x < 35		Skin Corr. 1B H314, Eye Dam. 1 H318
EC		
CAS 68609-08-5		
REACH Reg. Polymer		
M-PHENYLENEBIS (METHYLAMINE)		
INDEX 15 ≤ x < 20		Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1B H317, Aquatic Chronic 3 H412, EUH071
EC 216-032-5		ATE Oral: 500 mg/kg, LC50 Inhalation mists/powders: 1,34 mg/l/4h
CAS 1477-55-0		
REACH Reg. 01-2119480150-50		
3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE		
INDEX 612-067-00-9	15 ≤ x < 20	Acute Tox. 4 H302, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1A H317
EC 220-666-8		Skin Sens. 1A H317: ≥ 0,001%
CAS 2855-13-2		LD50 Oral: 1030 mg/kg
REACH Reg. 01-2119514687-32		
salicylic acid		
INDEX 607-732-00-5	5 ≤ x < 7	Repr. 2 H361d, Acute Tox. 4 H302, Eye Dam. 1 H318
EC 200-712-3		LD50 Oral: 891 mg/kg
CAS 69-72-7		
REACH Reg. 01-2119486984-17		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Rinse your mouth with running water. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

SECTION 4. First aid measures ... / >>**4.3. Indication of any immediate medical attention and special treatment needed**

Immediately call a POISON CENTER / doctor.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment: see section 4.1

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

SECTION 7. Handling and storage ... / >>

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
	TLV-ACGIH	ACGIH 2023

M-PHENYLENEBIS (METHYLAMINE)

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
VLEP	FRA			0,1		
MV	SVN	0,1				
TLV-ACGIH				0,018 (C)		SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,094	mg/l
Normal value in marine water	0,009	mg/l
Normal value for fresh water sediment	12,4	mg/kg/d
Normal value for marine water sediment	1,24	mg/kg/d
Normal value for marine water, intermittent release	0,152	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	2,44	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		NPI				
Inhalation	NPI	NPI	NPI	NPI	MED	NPI	0,2 mg/m3	1,2 mg/m3
Skin	NPI	NPI	NPI	NPI	MED	NPI	MED	0,33 mg/kg bw/d

SECTION 8. Exposure controls/personal protection ... / >>

BENZYL ALCOHOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	CZE	40	8,88	80	17,76		
AGW	DEU	22	5	44	10	SKIN	11
MAK	DEU	22	5	44	10	SKIN	
NDS/NDSch	POL	240					
ПДК	RUS			5			n
MV	SVN	22	5	44	10	SKIN	

Predicted no-effect concentration - PNEC

Normal value in fresh water	1	mg/l
Normal value in marine water	0,1	mg/l
Normal value for fresh water sediment	5,27	mg/kg
Normal value for marine water sediment	0,527	mg/kg
Normal value for water, intermittent release	2,3	mg/l
Normal value of STP microorganisms	39	mg/l
Normal value for the terrestrial compartment	0,45	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral		20		4				
		mg/kg bw/d		mg/kg bw/d				
Inhalation		27		5,4		110		22
		mg/m3		mg/m3		mg/m3		mg/m3
Skin		20		4		40		8
		mg/kg bw/d		mg/kg bw/d		mg/kg		mg/kg
						bw/d		bw/d

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,06	mg/l
Normal value in marine water	0,006	mg/l
Normal value for fresh water sediment	5,784	mg/kg/d
Normal value for marine water sediment	0,578	mg/kg/d
Normal value for marine water, intermittent release	0,23	mg/l
Normal value of STP microorganisms	3,18	mg/l
Normal value for the terrestrial compartment	1,121	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral			0,300	0,300				
			mg/kg bw/d	mg/kg bw/d				
Inhalation					0,073	0,073		
					mg/m3	mg/m3		

SECTION 8. Exposure controls/personal protection ... / >>

salicylic acid

Predicted no-effect concentration - PNEC

Normal value in fresh water	200	µg/L
Normal value in marine water	1	mg/l
Normal value for fresh water sediment	1,42	mg/kg
Normal value for marine water sediment	142	µg/kg
Normal value for marine water, intermittent release	20	µg/L
Normal value of STP microorganisms	162	mg/l
Normal value for the terrestrial compartment	166	µg/kg
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		4,0 mg/kg		1,0 mg/kg				
Inhalation		NPI	NPI	4,0 mg/m³	NPI	NPI	5,0 mg/m³	5,0 mg/m³
Skin		NPI	NPI	1,0 mg/kg	NPI	NPI	NPI	2,3 mg/kg

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Protect your hands with gloves of the following type:

Material: Butyl rubber (IIR)

Thickness: 0,5 mm

Breakthrough time: 480 min

Material: Laminated film - LLDPE

Thickness: 0,06 mm

Breakthrough time: 480 min

Material: Viton or fluoroelastomer (FKM)

Thickness: 0,3 mm

Breakthrough time: 480 min

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	TYPICAL	
Odour	amino	
Melting point / freezing point	not determined	Reason for missing data: not determined
Initial boiling point	> 200 °C	
Flammability	not applicable	
Lower explosive limit	1,2 % (v/v)	
Upper explosive limit	13 % (v/v)	
Flash point	105 °C	
Auto-ignition temperature	380 °C	
Decomposition temperature	not determined	
pH	10,5	
Kinematic viscosity	not determined	Reason for missing data: not determined
Dynamic viscosity	340 mPas	Method: DIN EN ISO 3219
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	not applicable	
Vapour pressure	0,1 hPa	Temperature: 20 °C
Density and/or relative density	1,04 kg/l	
Relative vapour density	not determined	Reason for missing data: not determined
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC) :	37,00 %	-	384,80	g/litre
VOC (volatile carbon)	28,74 %	-	298,90	g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F. Possibility of explosion.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

BENZYL ALCOHOL

May react dangerously with: hydrobromic acid, iron, oxidising agents, sulphuric acid. Risk of explosion on contact with: phosphorus trichloride.

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

May react dangerously with: strong oxidising agents, concentrated inorganic acids.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

BENZYL ALCOHOL

SECTION 10. Stability and reactivity ... / >>

Avoid exposure to: air, sources of heat, naked flames.
 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE
 Avoid contact with: strong acids, strong oxidants.

10.5. Incompatible materials

BENZYL ALCOHOL
 Incompatible with: sulphuric acid, oxidising substances, aluminium.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
 It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Oral) of the mixture:	917,93 mg/kg
ATE (Dermal) of the mixture:	Not classified (no significant component)

Corrosive to the respiratory tract.

M-PHENYLENEBIS (METHYLAMINE)	
LD50 (Dermal):	> 3100 mg/kg Rat
LD50 (Oral):	> 200 mg/kg Rat - Sprague-Dawley
ATE (Oral):	500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LC50 (Inhalation mists/powders):	1,34 mg/l/4h Rat

BENZYL ALCOHOL	
LD50 (Dermal):	2000 mg/kg Rabbit
LD50 (Oral):	1200 mg/kg
LC50 (Inhalation vapours):	> 4,1 mg/l/4h Rat

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE	
LD50 (Oral):	1030 mg/kg

salicylic acid	
LD50 (Dermal):	2000 mg/kg (rat)
LD50 (Oral):	891 mg/kg (rat)

salicylic acid
 The acute oral toxicity of salicylic acid (purity unknown) was tested in a test similar to OECD guideline 401. Five male Albino rats per group (4 groups) were administered a single dose of the test substance in a corn oil suspension. The dose were 464, 681, 1000 and 1470 mg/kg bw. The animals were then observed for 14 days.
 Under the conditions of this test, the LD50 was 891 mg/kg bw. Signs of intoxication were hypoactivity and muscular weakness. At necropsy, no significant findings were observed in survivors, whereas inflammation of the gastrointestinal tract was observed in

SECTION 11. Toxicological information ... / >>

decedents. Based on the results of this study, salicylic acid would be classified as harmful in male rats by oral route, according to the Directive (67/548/EEC) on dangerous substance.

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Suspected of damaging the unborn child

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product contains the following endocrine disruptors in concentrations of 0.1% or greater by weight that may have endocrine disrupting effects on humans and cause adverse effects on the exposed individual or his or her progeny:
salicylic acid

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity**M-PHENYLENEBIS (METHYLAMINE)**

LC50 - for Fish	87,6 mg/l/96h Oryzias latipes
EC50 - for Crustacea	15,2 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	20,3 mg/l/72h Pseudokirchnerella subcapitata

BENZYL ALCOHOL

LC50 - for Fish	10 mg/l/96h Bluegill
-----------------	----------------------

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

LC50 - for Fish	110 mg/l/96h Fish
EC50 - for Crustacea	23 mg/l/48h Daphnia

salicylic acid

LC50 - for Fish	1,853 g/L/24h
EC50 - for Crustacea	870 mg/l/48h
EC50 - for Algae / Aquatic Plants	100 mg/l/72h
Chronic NOEC for Crustacea	10 mg/l

SECTION 12. Ecological information ... / >>**12.2. Persistence and degradability****M-PHENYLENEBIS (METHYLAMINE)**Solubility in water 1000 - 10000 mg/l
Rapidly degradable**BENZYL ALCOHOL**

Rapidly degradable

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINESolubility in water 1000 - 10000 mg/l
NOT rapidly degradable**salicylic acid**Solubility in water 2,55 g/l
Rapidly degradable**12.3. Bioaccumulative potential****M-PHENYLENEBIS (METHYLAMINE)**

Partition coefficient: n-octanol/water 0,18

BENZYL ALCOHOL

Partition coefficient: n-octanol/water 1,1

salicylic acid

Partition coefficient: n-octanol/water 2,64

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessmentOn the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: UN 2735

SECTION 14. Transport information ... / >>

14.2. UN proper shipping name

ADR / RID: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-,reaction products with bisphenol A diglycidyl ether homopolymer;
M-PHENYLENEBIS (METHYLAMINE))

IMDG: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-,reaction products with bisphenol A diglycidyl ether homopolymer;
M-PHENYLENEBIS (METHYLAMINE))

IATA: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-,reaction products with bisphenol A diglycidyl ether homopolymer;
M-PHENYLENEBIS (METHYLAMINE))

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8

IMDG: Class: 8 Label: 8

IATA: Class: 8 Label: 8



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO

IMDG: not marine pollutant

IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 80	Limited Quantities: 1 L	Tunnel restriction code: (E)
	Special provision: 274		
IMDG:	EMS: F-A, S-B	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 30 L	Packaging instructions: 855
	Passengers:	Maximum quantity: 1 L	Packaging instructions: 851
	Special provision:	A3, A803	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product	
Point	3
Contained substance	
Point	75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

SECTION 15. Regulatory information ... / >>

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Two-pack reactive performance coatings for specific end use such as floors.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

M-PHENYLENEBIS (METHYLAMINE)

BENZYL ALCOHOL

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 2	Reproductive toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Sens. 1A	Skin sensitization, category 1A
Skin Sens. 1B	Skin sensitization, category 1B
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H361d	Suspected of damaging the unborn child.
H302	Harmful if swallowed.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level

SECTION 16. Other information ... / >>

- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

SECTION 16. Other information ... / >>

The following sections were modified:

01 / 02 / 03 / 04 / 08 / 09 / 11 / 12 / 13 / 14 / 15 / 16.