

53K - NORDPUR SW MAT XF COLORABILE (A)

Revision nr.5 Dated 28/04/2023 Printed on 11/05/2023
Page n. 1 / 13
Replaced revision:4 (Dated 16/09/2022)

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 53K

Product name NORDPUR SW MAT XF COLORABILE (A)

PFY0-00QE-K00N-W2TY

1.2. Relevant identified uses of the substance or mixture and uses advised against

FAST SETTING WATER-BASED BI-COMPONENT RESIN

1.3. Details of the supplier of the safety data sheet

Name NORD RESINE S.p.A. Full address Via Fornace Vecchia, 79

(TV) District and Country 31058 Susegana

Italia

Tel. +39 0438-437511 Fax +39 0438-435155

e-mail address of the competent person

responsible for the Safety Data Sheet annabreda@nordresine.com

Supplier: NORD RESINE S.p.A.

1.4. Emergency telephone number

For urgent inquiries refer to +39 0438 437511

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Skin sensitization, category 1A H317 May cause an allergic skin reaction.

Hazardous to the aquatic environment, chronic H412 Harmful to aquatic life with long lasting effects.

toxicity, category 3

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:



53K - NORDPUR SW MAT XF COLORABILE (A)

Revision nr.5 Dated 28/04/2023 Printed on 11/05/2023

Page n. 2 / 13 Replaced revision:4 (Dated 16/09/2022)

SECTION 2. Hazards identification .../>>

P280 Wear protective gloves.

Avoid breathing dust / fume / gas / mist / vapours / spray. P261 If skin irritation or rash occurs: Get medical advice / attention. P333+P313 P362+P364 Take off contaminated clothing and wash it before reuse.

P273 Avoid release to the environment.

Contains: Mixture of: 5-cloro-2-metil - 2H-isotiazol-3-one; 2-metil-2H-isotiazol-3-one (3:1)

VOC (Directive 2004/42/EC): Two - pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition: 85 44 Limit value: 140.00

- Catalysed with: 12,50 % NORDPUR SW MAT XF (B)

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

2-BUTOXYETHANOL

CAS 111-76-2 $1 \le x < 4$ Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315

EC 203-905-0 LD50 Oral: 1200 mg/kg, STA Inhalation vapours: 11 mg/l 603-014-00-0

INDEX REACH Reg. 01-2119475108-36

DIPROPYLENE GLYCOL MONOMETHYL ETHER

34590-94-8 CAS $0 \le x < 1$ Substance with a community workplace exposure limit.

EC 252-104-2

INDEX

REACH Reg. 01-2119450011-60

QUARTZ

CAS 14808-60-7 $0 \le x < 1$ **STOT RE 1 H372**

EC 238-878-4

INDEX

3-IODO-2-PROPYL-n-BUTIL CARBAMATE

CAS 55406-53-6 $0 \le x < 0.25$ Acute Tox. 3 H331, Acute Tox. 4 H302, STOT RE 1 H372, Eye Dam. 1 H318,

Skin Sens. 1 H317, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410

259-627-5 LD50 Oral: >300 mg/l/4h, LC50 Inhalation mists/powders: 0,67 mg/l/4h FC.

INDEX 616-212-00-7 REACH Reg. 01-2120762115-60

Mixture of: 5-cloro-2-metil - 2H-isotiazol-3-one; 2-metil-2H-isotiazol-3-one (3:1)

55965-84-9 $0.0015 \le x < 0.0025$ Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C CAS

H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100,

Aquatic Chronic 1 H410 M=100

Skin Corr. 1C H314: ≥ 0,6%, Skin Irrit. 2 H315: ≥ 0,06%, Skin Sens. 1A H317: EC

≥ 0,0015%, Eye Dam. 1 H318: ≥ 0,6%, Eye Irrit. 2 H319: ≥ 0,06%

INDEX 613-167-00-5 STA Oral: 100 mg/kg, STA Dermal: 50,001 mg/kg, STA Inhalation vapours:

0,501 mg/l, STA Inhalation mists/powders: 0,051 mg/l

01-2120764691-48 REACH Reg.

The full wording of hazard (H) phrases is given in section 16 of the sheet.



53K - NORDPUR SW MAT XF COLORABILE (A)

Revision nr.5 Dated 28/04/2023 Printed on 11/05/2023 Page n. 3 / 13 Replaced revision:4 (Dated 16/09/2022)

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.



53K - NORDPUR SW MAT XF COLORABILE (A)

Revision nr.5 Dated 28/04/2023 Printed on 11/05/2023 Page n. 4 / 13 Replaced revision:4 (Dated 16/09/2022)

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und
		Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung
		gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των
		οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας
		2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με
		την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki
		tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama
		na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3,
		eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os
		agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os
		riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające
		rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych
5011		dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru
0) (1)	O	modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
CDD	Linita d Kinandana	(Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive
		2017/2398; Directive (EO) 2017/164; Directive 2009/1617EO; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021
	ILV-ACGIII	A00111 202 1



53K - NORDPUR SW MAT XF COLORABILE (A)

Revision nr.5 Dated 28/04/2023 Printed on 11/05/2023 Page n. 5/ 1/3 Replaced revision:4 (Dated 16/09/2022)

SECTION 8. Exposure controls/personal protection .../>>

				2-BUTOX	YETHANO	L		
Threshold Limit V	/alue							
Type	Country	TWA/8h		STEL/15r	STEL/15min		bservations	
		mg/m3	ppm	mg/m3	ppm			
TLV	CZE	100	20,4	200	40,8	SKIN		
AGW	DEU	49	10	98 (C)	20 (C)	SKIN		
MAK	DEU	49	10	98	20	SKIN	Hinweis	
VLA	ESP	98	20	245	50	SKIN		
VLEP	FRA	49	10	246	50	SKIN		
TLV	GRC	120	25					
AK	HUN	98		246		SKIN		
GVI/KGVI	HRV	98	20	246	50	SKIN		
VLEP	ITA	98	20	246	50	SKIN		
TGG	NLD	100		246		SKIN		
VLE	PRT	98	20	246	50	SKIN		
NDS/NDSCh	POL	98		200		SKIN		
TLV	ROU	98	20	246	50	SKIN		
MV	SVN	98	20	246	50	SKIN		
WEL	GBR	123	25	246	50	SKIN		
OEL	EU	98	20	246	50	SKIN		
TLV-ACGIH		97	20					

			DIPROPY	LENE GLYC	DL MONOMET	THYL ETHER			
hreshold Limit \	/alue								
Type Country TWA/8h			STEL/15min		Remarks / Observations				
		mg/m3	ppm	mg/m3	ppm				
TLV	CZE	270	43,74	550	89,1	SKIN			
AGW	DEU	310	50	310	50				
MAK	DEU	310	50	310	50				
VLA	ESP	308	50			SKIN			
VLEP	FRA	308	50			SKIN			
TLV	GRC	600	100	900	150				
AK	HUN	308							
GVI/KGVI	HRV	308	50			SKIN			
VLEP	ITA	308	50			SKIN			
TGG	NLD	300							
VLE	PRT	308	50			SKIN			
NDS/NDSCh	POL	240		480		SKIN			
TLV	ROU	308	50			SKIN			
MV	SVN	308	50			SKIN			
WEL	GBR	308	50			SKIN			
OEL	EU	308	50			SKIN			
redicted no-effe	ct concentra	ation - PNE	С						
Normal value in	fresh water						19	mg/l	
Normal value in	marine wate	er					1,9	mg/l	
Normal value for	or fresh water	r sediment					70,2	mg/kg	
Normal value for	or marine wat	ter sedimen	t				7,02	mg/kg	
Normal value for	or water, inter	rmittent rele	ase				190	mg/l	
Normal value of	f STP microo	rganisms					4168	mg/l	
Normal value for			ment				2,74	mg/kg	
ealth - Derived r	no-effect lev	el - DNEL /	DMEL						
	Effe	cts on cons	umers			Effects on w	orkers		
Route of expos	ure Acu	te Ac	ute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	loca	ıl sy	stemic	local	systemic	local	systemic	local	systemic
Oral		,			1,67		•		•
					mg/kg/d				
Inhalation					37,2				310
					mg/m3				mg/m3
Skin					15				65
					mg/kg/d				mg/kg/d



53K - NORDPUR SW MAT XF COLORABILE (A)

Revision nr.5 Dated 28/04/2023 Printed on 11/05/2023 Page n. 6 / 13 Replaced revision:4 (Dated 16/09/2022)

SECTION 8. Exposure controls/personal protection/>>

	QUARTZ								
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15	min	Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
VLA	ESP		0,05			RESP			
VLEP	FRA	0,1				RESP			
GVI/KGVI	HRV	0,1							
VLEP	ITA	0,1				RESP			
TGG	NLD	0,075				RESP			
VLE	PRT	0,025				RESP			
NDS/NDSCh	POL	0,1				RESP			
TLV	ROU	0,1				RESP			
MV	SVN	0,15				RESP			
OEL	EU	0,1				RESP			
TLV-ACGIH		0,025				RESP			

Mixture of: 5-cloro-2-metil - 2H-isotiazol-3-one; 2-metil-2H-isotiazol-3-one (3:1)							
Predicted no-effect concentration - PNEC							
Normal value in fresh water	0,003	mg/l					
Normal value in marine water	0,003	mg/l					
Normal value for fresh water sediment	0,027	mg/kg/d					
Normal value for marine water sediment	0,027	mg/kg/d					
Normal value of STP microorganisms	0,23	mg/l					

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction. VND = hazard identified but no DNEL/PNEC available; NEA = no exposure expected; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Value Information
Appearance liquid



53K - NORDPUR SW MAT XF COLORABILE (A)

Revision nr.5 Dated 28/04/2023 Printed on 11/05/2023 Page n. 7 / 13 Replaced revision:4 (Dated 16/09/2022)

SECTION 9. Physical and chemical properties .../>>

Colour white

Odour characteristic Melting point / freezing point Not available Initial boiling point 100 °C Flammability Not available Lower explosive limit Not available Upper explosive limit Not available °C Flash point 60

Flash point > 60 °C
Auto-ignition temperature Not available

Kinematic viscosity Not available

Solubility partially soluble in water Partition coefficient: n-octanol/water Not available

Vapour pressure

Density and/or relative density

Relative vapour density

Particle characteristics

Not available

Not available

Not available

Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 0 %

VOC (Directive 2004/42/EC) : 6,30 % - 74,37 g/litre VOC (volatile carbon) 3,74 % - 44,17 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL

Decomposes under the effect of heat.
DIPROPYLENE GLYCOL MONOMETHYL ETHER
Forms peroxides with: air.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

2-BUTOXYETHANOL

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

May react violently with: strong oxidising agents.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

2-BUTOXYETHANOL

Avoid exposure to: sources of heat,naked flames. DIPROPYLENE GLYCOL MONOMETHYL ETHER

Avoid exposure to: sources of heat. Possibility of explosion.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

2-BUTOXYETHANOL

May develop: hydrogen.



53K - NORDPUR SW MAT XF COLORABILE (A)

Revision nr.5 Dated 28/04/2023 Printed on 11/05/2023 Page n. 8 / 13 Replaced revision:4 (Dated 16/09/2022)

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture: > 5 mg/l
ATE (Inhalation - vapours) of the mixture: > 20 mg/l
ATE (Inhalation - gas) of the mixture: 0,0 mg/l
ATE (Oral) of the mixture: >2000 mg/kg

ATE (Dermal) of the mixture: Not classified (no significant component)

2-BUTOXYETHANOL

LD50 (Oral): 1200 mg/kg Guinea pig

LC50 (Inhalation vapours): 2,2 mg/l/4h Rat

STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

3-IODO-2-PROPYL-n-BUTIL CARBAMATE

 LD50 (Dermal):
 > 5000 mg/kg Rat

 LD50 (Oral):
 > 300 mg/kg Rat

 LC50 (Inhalation mists/powders):
 0,67 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

ΕN



NORD RESINE S.p.A.

53K - NORDPUR SW MAT XF COLORABILE (A)

Revision nr.5 Dated 28/04/2023 Printed on 11/05/2023 Page n. 9 / 13 Replaced revision:4 (Dated 16/09/2022)

SECTION 11. Toxicological information .../>>

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

Mixture of: 5-cloro-2-metil - 2H-isotiazol-3-one; 2-metil-2H-isotiazol-3-one (3:1)

LC50 - for Fish 0,22 mg/l/96h Onchorhyncus mykiss

EC50 - for Crustacea 0,1 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants 0,048 mg/l/72h Pseudokirchneriella subcapitata

Chronic NOEC for Fish 0,098 mg/l Onchorhyncus mykiss Chronic NOEC for Crustacea 0,004 mg/l Daphnia magna

Chronic NOEC for Algae / Aquatic Plants 0,0012 mg/l Pseudokirchneriella subcapitata



53K - NORDPUR SW MAT XF COLORABILE (A)

Revision nr.5 Dated 28/04/2023 Printed on 11/05/2023 Page n. 10 / 13 Replaced revision:4 (Dated 16/09/2022)

SECTION 12. Ecological information .../>>

3-IODO-2-PROPYL-n-BUTIL CARBAMATE

LC50 - for Fish 0,067 mg/l/96h Oncorhynchus mykiss EC50 - for Crustacea 0,16 mg/l/48h Daphnia Magna

EC50 - for Algae / Aquatic Plants 0,022 mg/l/72h Desmodesmus subspicatus

Chronic NOEC for Fish 0,0084 mg/l Pimephales promelas

Chronic NOEC for Crustacea 0,05 mg/l Daphnia magna

12.2. Persistence and degradability

Mixture of: 5-cloro-2-metil - 2H-isotiazol-3-one; 2-metil-2H-isotiazol-3-one (3:1)

Rapidly degradable

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

2-BUTOXYETHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

3-IODO-2-PROPYL-n-BUTIL CARBAMATE

Rapidly degradable

12.3. Bioaccumulative potential

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Partition coefficient: n-octanol/water 0,0043

2-BUTOXYETHANOL

Partition coefficient: n-octanol/water 0,81

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.



53K - NORDPUR SW MAT XF COLORABILE (A)

Printed on 11/05/2023 Page n. 11 / 13 Replaced revision:4 (Dated 16/09/2022)

SECTION 14. Transport information .../>>

14.1. UN number or ID number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006 Product Point 3 - 40 Contained substance Point 75 Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors Not applicable Substances in Candidate List (Art. 59 REACH) On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%. Substances subject to authorisation (Annex XIV REACH) None Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012: Substances subject to the Rotterdam Convention: Substances subject to the Stockholm Convention: None

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC):

FΝ



NORD RESINE S.p.A.

53K - NORDPUR SW MAT XF COLORABILE (A)

Revision nr.5 Dated 28/04/2023 Printed on 11/05/2023
Page n. 12 / 13
Replaced revision:4 (Dated 16/09/2022)

SECTION 15. Regulatory information/>>

Two - pack performance coatings.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute toxicity, category 2 Acute Tox. 2 Acute Tox. 3 Acute toxicity, category 3

STOT RF 1 Specific target organ toxicity - repeated exposure, category 1

Skin Corr. 1C Skin corrosion, category 1C Serious eye damage, category 1 Eve Dam. 1 Skin Sens. 1A Skin sensitization, category 1A

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1 Hazardous to the aquatic environment, chronic toxicity, category 1 **Aquatic Chronic 1 Aquatic Chronic 3** Hazardous to the aquatic environment, chronic toxicity, category 3

H310 Fatal in contact with skin. Fatal if inhaled. H330 H301 Toxic if swallowed.

Causes damage to organs through prolonged or repeated exposure. H372

Causes severe skin burns and eye damage. H314

H318 Causes serious eye damage. H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects. H410 Harmful to aquatic life with long lasting effects. H412

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament



53K - NORDPUR SW MAT XF COLORABILE (A)

Revision nr.5 Dated 28/04/2023 Printed on 11/05/2023 Page n. 13 / 13 Replaced revision:4 (Dated 16/09/2022)

SECTION 16. Other information .../>>

- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 09 / 12.