

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 878
Product name: TILEPUR BASE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: For non-slip coating of glossy surfaces

1.3. Details of the supplier of the safety data sheet

Name: NORD RESINE S.p.A.
Full address: Via Fornace Vecchia, 79
District and Country: 31058 Susegana (TV) Italia
Tel.: +39 0438-437511
Fax: +39 0438-435155
e-mail address of the competent person responsible for the Safety Data Sheet: annabreda@nordresine.com
Supplier: NORD RESINE S.p.A.

1.4. Emergency telephone number

For urgent inquiries refer to:

Ireland
National Poisons Information Centre
+353 018092166
+353 018092566

Malta
Malta Competition and Consumer Affairs Authority (MCCAA)
+356 2395 2000

Belgium
Centre Antipoisons: +32 022649636

Germany
BfR Bundesinstitut für Risikobewertung: +49 30184120

Netherlands
National Poisons Information Center / University Medical Center Utrecht
+31 88 75 585 61

Croatia
Croatian Institute of Public Health, Division for Toxicology: +38514686910

Sveden
Swedish Poisons Information Centre: +46104566750

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2

H225

Highly flammable liquid and vapour.

SECTION 2. Hazards identification ... / >>

Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P370+P378	In case of fire: use carbon anhydride, foam, nebulized water to extinguish.
P261	Avoid breathing dust / fume / gas / mist / vapours / spray.
P233	Keep container tightly closed.
P312	Call a POISON CENTRE / doctor if you feel unwell.

Contains: 3-AMINOPROPYLTRYETHOXYSILANE
PROPAN-2-OL
ETHYL ACETATE

Product not intended for uses provided for by Directive 2004/42/EC.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients
3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
PROPAN-2-OL		
INDEX 603-117-00-0	75 \leq x < 100	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336
EC 200-661-7		
CAS 67-63-0		
REACH Reg. 01-2119457558-25		

SECTION 3. Composition/information on ingredients ... / >>**ETHYL ACETATE**

INDEX 607-022-00-5 $7 \leq x < 10$
EC 205-500-4
CAS 141-78-6
REACH Reg. 01-2119475103-46

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066**3-AMINOPROPYLTRYETHOXSILANE**

INDEX 612-108-00-0 $1 \leq x < 3$
EC 213-048-4
CAS 919-30-2
REACH Reg. 01-2119480479-24

**Acute Tox. 4 H302, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317
ATE Oral: 500 mg/kg**

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Call a POISON CENTRE / doctor if you feel unwell.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment: see section 4.1

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

SECTION 5. Firefighting measures ... / >>

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

SECTION 8. Exposure controls/personal protection ... / >>

PROPAN-2-OL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	500	200	1000	400	
AGW	DEU	500	200	1000	400	
MAK	DEU	500	200	1000	400	
VLA	ESP	500	200	1000	400	
VLEP	FRA			980	400	
TLV	GRC	980	400	1225	500	
AK	HUN	500	200	1000	400	SKIN
GVI/KGVI	HRV	999	400	1250	500	
TGG	NLD	650				
NDS/NDSch	POL	900		1200		SKIN
TLV	ROU	200	81	500	203	
ПДК	RUS	10		50		n
MV	SVN	500	200	1000	400	
WEL	GBR	999	400	1250	500	
TLV-ACGIH		492	200	983	400	

Predicted no-effect concentration - PNEC

Normal value in fresh water	104,9	mg/l
Normal value in marine water	140,9	mg/l
Normal value for water, intermittent release	140,9	mg/l
Normal value for the food chain (secondary poisoning)	160	mg/kg
Normal value for the terrestrial compartment	28	mg/kg

ETHYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	700	191,1	900	245,7	
AGW	DEU	730	200	1460	400	
MAK	DEU	750	200	1500	400	
VLA	ESP	734	200	1468	400	
VLEP	FRA	734	200	1468	400	
TLV	GRC	734	200	1468	400	
AK	HUN	734	200	1468	400	
GVI/KGVI	HRV	734	200	1468	400	
VLEP	ITA	734	200	1468	400	Allegato XXXVIII D.Lgs. 81/08
TGG	NLD	734		1468		
VLE	PRT	734	200	1468	400	
NDS/NDSch	POL	734		1468		
TLV	ROU	734	200	1468	400	
ПДК	RUS	50		200		n
MV	SVN	734	200	1468	400	
WEL	GBR	734	200	1468	400	
OEL	EU	734	200	1468	400	
TLV-ACGIH		1441	400			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,26	mg/l
Normal value in marine water	0,026	mg/l
Normal value for fresh water sediment	1,25	mg/kg
Normal value for marine water sediment	0,125	mg/kg
Normal value for water, intermittent release	1,65	mg/l
Normal value of STP microorganisms	650	mg/l
Normal value for the food chain (secondary poisoning)	200	mg/kg
Normal value for the terrestrial compartment	0,24	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Effects on workers					
	Acute	Acute systemic	Chronic	Chronic systemic	Acute	Acute systemic	Chronic	Chronic systemic
Oral		NPI		4,5 mg/kg bw/d				
Inhalation	734 mg/m3	734 mg/m3	367 mg/m3	367 mg/m3	1468 mg/m3	1468 mg/m3	734 mg/m3	734 mg/m3
Skin	NPI	NPI	LOW	37 mg/kg bw/d	LOW	NPI	NPI	63 mg/kg bw/d

SECTION 8. Exposure controls/personal protection ... / >>

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Protect your hands with gloves of the following type:

Material: Laminated film - LLDPE

Thickness: 0,06 mm

Breakthrough time: 480 min

Material: Butyl rubber (IIR)

Thickness: 0,35 mm

Breakthrough time: 480 min

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	colourless	
Odour	characteristic of solvent	
Melting point / freezing point	< -80 °C	
Initial boiling point	> 35 °C	Substance:PROPAN-2-OL Initial boiling point: 82,3 °C
Flammability	flammable liquid	
Lower explosive limit	not determined	Reason for missing data:not determined
Upper explosive limit	not determined	Reason for missing data:not determined
Flash point	< 23 °C	
Auto-ignition temperature	425 °C	
Decomposition temperature	not determined	Reason for missing data:not determined
pH	not determined	Reason for missing data:not determined
Kinematic viscosity	not determined	Reason for missing data:not determined
Solubility	soluble in organic solvents	
Partition coefficient: n-octanol/water	not applicable	
Vapour pressure	not available	Substance:PROPAN-2-OL Vapour pressure: 35 mmHg
Density and/or relative density	0,853 kg/l	

SECTION 9. Physical and chemical properties ... / >>Relative vapour density
Particle characteristicsnot determined
not applicable

Reason for missing data: not determined

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU)	95,56 %	-	815,13	g/litre
VOC (volatile carbon)	56,81 %	-	484,59	g/litre

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

ETHYL ACETATE

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals, hydrides, oleum. May react violently with: fluorine, strong oxidising agents, chlorosulphuric acid, potassium tert-butoxide. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHYL ACETATE

Avoid exposure to: light, sources of heat, naked flames.

10.5. Incompatible materials

ETHYL ACETATE

Incompatible with: acids, bases, strong oxidants, chlorosulphuric acid.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

3-AMINOPROPYLTRYETHOXSILANE
3-AMINOPROPYLTRYETHOXSILANE:
LD50 (oral, rat): 3500 mg/kg
LD50 (skin, rabbit): 4000 mg/kg.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008Metabolism, toxicokinetics, mechanism of action and other information

Information not available

SECTION 11. Toxicological information ... / >>Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	Not classified (no significant component)

PROPAN-2-OL	
LD50 (Dermal):	12800 mg/kg Rat
LD50 (Oral):	4710 mg/kg Rat
LC50 (Inhalation vapours):	72,6 mg/l/4h Rat

ETHYL ACETATE	
LD50 (Dermal):	> 20000 mg/kg Rabbit
LD50 (Oral):	4934 mg/kg Rabbit
LC50 (Inhalation vapours):	> 29,3 mg/l/4h Rat

3-AMINOPROPYLTRYETHOXYSILANE	
ATE (Oral):	500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 11. Toxicological information ... / >>**11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

ETHYL ACETATE	
LC50 - for Fish	230 mg/l/96h Pimephales promelas
EC50 - for Crustacea	154 mg/l/48h

12.2. Persistence and degradability

PROPAN-2-OL
Rapidly degradable

ETHYL ACETATE	
Solubility in water	> 10000 mg/l
Rapidly degradable	

12.3. Bioaccumulative potential

PROPAN-2-OL	
Partition coefficient: n-octanol/water	0,05

ETHYL ACETATE	
Partition coefficient: n-octanol/water	0,68
BCF	30

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: UN 1263

14.2. UN proper shipping nameADR / RID: PAINT or PAINT RELATED MATERIAL
IMDG: PAINT or PAINT RELATED MATERIAL
IATA: PAINT or PAINT RELATED MATERIAL**14.3. Transport hazard class(es)**

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3

**14.4. Packing group**

ADR / RID, IMDG, IATA: II

14.5. Environmental hazardsADR / RID: NO
IMDG: not marine pollutant
IATA: NO**14.6. Special precautions for user**

ADR / RID:	HIN - Kemler: 33	Limited Quantities: 5 lt	Tunnel restriction code: (D/E)
	Special provision: 163, 367, 640C, 650		
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 lt	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Passengers:	Maximum quantity: 5 L	Packaging instructions: 353
	Special provision:	A3, A72, A192	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

SECTION 15. Regulatory information ... / >>

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

ETHYL ACETATE

3-AMINOPROPYLTRYETHOXYSILANE

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.

SECTION 16. Other information ... / >>

- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16.