

# EPOXY LINER PR



## TECHNICAL SPECIFICATIONS



## FIELD OF APPLICATION

## APPLICATIONS



## Description

## Field of application

## Advantages

## General preparation of the laying support

## Specific preparation of the laying support

## Preparing the product

## Application of the product

## Consumption

type of application	minimum consumption	maximum consumption	UoM	dilution
As a protective anti-fuel agent on dry supports	0,40	0,45	kg/m <sup>2</sup>	1st coat diluted with 20% by weight of SOLVENT FOR NORPHEN
As a floor top coat	0,70	0,90	kg/m <sup>2</sup>	-
In the absence of a vapour barrier (tanks against the ground or similar situations)	0,35	0,40	kg/m <sup>2</sup>	-

## Cleaning of tools

## Useful application tips

## Technical data

► PRODUCT IDENTIFICATION DATA	UoM	value

# EPOXY LINER PR

► **PRODUCT IDENTIFICATION DATA** UoM      value

► **APPLICATION DATA AND FINAL PERFORMANCES** UoM      Value

► **TECHNICAL DATA** UoM      value

► **TECHNICAL DATA** UoM      value

## Storage of the product

### Packages

VARIANT	PACKAGE	ADR	PACKAGES PER PALLET	COMPONENTS
VERDE BENZINA (1)	kit (A+B) da 7,84 kg	P*	-	A = 5,04 kg (fustino met.) B = 2,80 kg (tanica)
VERDE BENZINA (1)	(A+B) da 23,8 kg	YES	-	A = 15,30 kg (fustino met.) B = 8,50 kg (tanica)

Legenda ADR:

P\* = merce PERICOLOSA imballata in quantità limitata (confezionata come da Cap. 3.4 ADR)

SI' = merce PERICOLOSA

Note:

(1): Fustino con chiusura a cravatta.

### LEGAL NOTES

Advice on how to use our products corresponds to the current state of our knowledge and does not involve the assumption of any guarantee and / or responsibility for the final result of the work. They do not refore exempt the customer from the responsibility of verifying the suitability of the products for the use and the prefixed purposes through preventive tests. The website [www.nordresine.com](http://www.nordresine.com) contains the latest revision of this datasheet.

### EDITION

Issue date:

Revision: