




FLOOR V

CE marking:
• EN 1504-2 (C) - Principles: MC-IR



TECHNICAL SPECIFICATIONS



FIELD OF APPLICATION



APPLICATIONS



Description

Field of application

Advantages

General preparation of the laying support

Specific preparation of the laying support

Preparing the product

Application of the product

Consumption

type of application	minimum consumption	maximum consumption	UoM	dilution
Per coat of the applied product	0,10	0,12	kg/m ²	-

Cleaning of tools

Useful application tips

Technical data

▶ PRODUCT IDENTIFICATION DATA

UoM	value

▶ APPLICATION DATA AND FINAL PERFORMANCES

UoM	Value

▶ TECHNICAL DATA

UoM	value

FLOOR V

► TECHNICAL DATA	UoM	value
------------------	-----	-------

Storage of the product

Packages

VARIANT	PACKAGE	ADR	PACKAGES PER PALLET	COMPONENTS
- (1)	kit (A+B) da 7,5 kg	P*	36 scatole	A = 4,5 kg (fustino met.) B = 3 kg (tanica)

Legenda ADR:

P* = merce PERICOLOSA imballata in quantità limitata (confezionata come da Cap. 3.4 ADR)

Note:

(1): Fustino con chiusura a cravatta.

LEGAL NOTES

Advice on how to use our products corresponds to the current state of our knowledge and does not involve the assumption of any guarantee and / or responsibility for the final result of the work. They do not refore exempt the customer from the responsibility of verifying the suitability of the products for the use and the prefixed purposes through preventive tests. The website www.nordresine.com contains the latest revision of this datasheet.

EDITION

Issue date:

Revision: